



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI

SGI Altix 3000 (1000MHz, Itanium 2)

SPECint_rate2000 = 245

SPECint_rate_base2000 = 245

SPEC license #: 4 | Tested by: SGI | Test date: Apr-2003 | Hardware Avail: Feb-2003 | Software Avail: Apr-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	32	238	218	32	238	218
175.vpr	32	219	237	32	219	237
176.gcc	32	137	299	32	137	299
181.mcf	32	359	186	32	359	186
186.crafty	32	144	257	32	144	257
197.parser	32	378	177	32	378	177
252.eon	32	156	309	32	156	309
253.perlbnk	32	270	247	32	270	247
254.gap	32	208	196	32	208	196
255.vortex	32	197	357	32	197	357
256.bzip2	32	234	238	32	234	238
300.twolf	32	391	285	32	391	285

Hardware

CPU: Intel Itanium 2
CPU MHz: 1000
FPU: Integrated
CPU(s) enabled: 32 cores, 32 chips, 1 core/chip
CPU(s) orderable: 4-64
Parallel: No
Primary Cache: 16KBI + 16KBD (on chip) per CPU
Secondary Cache: 256KB (on chip) per CPU
L3 Cache: 3.0MB (on chip) per CPU
Other Cache: N/A
Memory: 64 GB (16*512MB DIMMS per 4cpu module)
Disk Subsystem: 1 x 36 GB SCSI (Seagate Cheetah 15k rpm)
Other Hardware: None

Software

Operating System: SGI ProPack(TM) v2.1
Compiler: Intel(R) C++ Compiler for Linux 7.1 (Build 20030327)
File System: xfs
System State: Single-user

Notes/Tuning Information

+FDO: PASS1=-prof_gen PASS2=-prof_use

Baseline optimization flags:

C programs: -ipo -O3 +FDO
C++ programs: -ipo -O2 -ansi_alias +FDO

Portability Flags:

176.gcc: -DSPEC_CPU2000_LP64 -Dalloca=_builtin_alloca -D_LIBC
186.crafty: -DLINUX_i386
252.eon: -DSPEC_CPU2000_LP64 -DHAS_ERRLIST
253.perlbnk: -DSPEC_CPU2000_LP64 -DSPEC_CPU2000_NEED_BOOL
-DSPEC_CPU2000_LINUX_IA64 -DSPEC_CPU2000_GLIBC22
254.gap: -DSPEC_CPU2000_LP64 -DSYS_HAS_CALLOC_PROTO -DSYS_IS_USG
-DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
255.vortex: -DSPEC_CPU2000_LP64

Processes were bound to CPUs using dplace.

Peak flags same as baseline (basepeak=true set globally).