



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
HP 9000 rp3440-4 (1000MHz PA-8800)

SPECint_rate2000 = 18.7
SPECint_rate_base2000 = 17.9

SPEC license #: 3 Tested by: HP Richardson Test date: Jan-2004 Hardware Avail: Feb-2004 Software Avail: Feb-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	204	15.9	2	201	16.2
175.vpr	2	186	17.5	2	186	17.5
176.gcc	2	108	23.7	2	108	23.7
181.mcf	2	297	14.0	2	297	14.0
186.crafty	2	109	21.2	2	109	21.2
197.parser	2	291	14.4	2	278	15.0
252.eon	2	178	16.9	2	157	19.2
253.perlbnk	2	225	18.6	2	192	21.7
254.gap	2	235	10.8	2	231	11.0
255.vortex	2	123	35.8	2	116	38.0
256.bzip2	2	227	15.3	2	203	17.2
300.twolf	2	343	20.3	2	338	20.6

Hardware

CPU: PA-8800
CPU MHz: 1000
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 2,4 (order by # cores)
Parallel: no
Primary Cache: 0.75MBI + 0.75MBD (on chip) per core
Secondary Cache: 32MB (off chip) shared by 2 cores
L3 Cache: N/A
Other Cache: N/A
Memory: 6GB (12 * 512MB DIMMs)
Disk Subsystem: 1x73GB 15K rpm SCSI
Other Hardware: N/A

Software

Operating System: HPUX11i-TCOE B.11.11.0312
Compiler: HP C/ANSI C B.11.11.08
HP aC++ Compiler A.03.52
File System: VxFS
System State: Multi-user

Notes/Tuning Information

Portability flags:

```
176.gcc: -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DHP
252.eon: -DFMAX_IS_DOUBLE
253.perlbnk: -DSPEC_CPU2000_HP
254.gap: -DSPEC_CPU2000_HP -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO
        -DSYS_HAS_TIME_PROTO -DSYS_HAS_CALLOC_PROTO
```

Baseline compile flags:

```
C      : +I/+P +Oall +Ostatic_prediction -Wl,-a,archive
C++    : +I/+P +Oall +Ostatic_prediction -Wl,-a,archive
```

Peak compile flags:

```
164.gzip: +I/+P +Oall +Optrs_strongly_typed +Oinline_budget=800
        -Wl,-a,archive +Ostatic_prediction
175.vpr: basepeak=true
176.gcc: basepeak=true
181.mcf: basepeak=true
186.crafty: basepeak=true
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
HP 9000 rp3440-4 (1000MHz PA-8800)

SPECint_rate2000 = 18.7
SPECint_rate_base2000 = 17.9

SPEC license #: 3 | Tested by: HP Richardson | Test date: Jan-2004 | Hardware Avail: Feb-2004 | Software Avail: Feb-2004

Notes/Tuning Information (Continued)

```

197.parser: +I/+P +Oall +Odataprefetch +ESficc +Oinline_budget=400
            +Owhole_program_mode -Wl,-a,archive +Ostatic_prediction
252.eon:    +I/+P +noeh +O4 +Optrs_strongly_typed +Olibcalls +Oentrysched
            +A +ESficc -Wl,-a,archive +Ostatic_prediction
253.perlbnk: +I/+P +Oall +ESlit +ESficc +Optrs_strongly_typed
            +Opromote_indirect_calls -Wl,-a,archive +Ostatic_prediction
            linked with /opt/langtools/lib/fastmem.o
254.gap:    +I/+P +Oall +ESlit +ESficc +Optrs_strongly_typed
            +Opromote_indirect_calls -Wl,-a,archive +Ostatic_prediction
255.vortex: +I/+P +Oall +Oinline_budget=800 +Optrs_strongly_typed
            -Wl,-a,archive +Ostatic_prediction
256.bzip2:  +I/+P +Oall +Odataprefetch +Optrs_strongly_typed +Owhole_program_mode
            +Onoptrs_to_globals +Oinline_budget=80 -Wl,-a,archive +Ostatic_prediction
300.twolf:  +I/+P +Oall +Optrs_strongly_typed -Wl,-a,archive +Ostatic_prediction

```

Kernel Tunables:

```

dbc_max_pct=20
dbc_min_pct=20
maxssiz=401604608
vps_pagesize=4096
vps_ceiling=16384

```

Other notes:

The system under test had the HP-UX 11i v1 December 2003
Technical Computing Operating Environment (version 11.11.0312)
and DART63 (December 2003) compilers installed, with the
following patches applied:

```

GOLDAPPS11i Gold Applications Patches for HP-UX 11i v1, December 2003
GOLDBASE11i Gold Base Patches for HP-UX 11i v1, December 2003
HWENABLE11i Hardware Enablement Patches for HP-UX 11i v1, December 2003
HWETEST1111 Hardware Enablement Patches for PA-8800 (prerelease)
PHSS_29483 aC++ compiler cumulative patch (A.03.52)
PHSS_30002 Fortran90 cumulative patch (B.11.01.74)

```

BCH shell utility command 'co cpu' (configure cpu)
used to deconfigure processors if necessary.