



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices

Rioworks HDAMA, AMD Opteron (TM) Model 240 EE

SPECint_rate2000 = 22.3

SPECint_rate_base2000 = 21.2

SPEC license #: 49 | Tested by: AMD, Austin, TX | Test date: Feb-2004 | Hardware Avail: Feb-2004 | Software Avail: May-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	183	17.7	2	178	18.2
175.vpr	2	174	18.7	2	173	18.8
176.gcc	2	125	20.5	2	108	23.6
181.mcf	2	220	19.0	2	220	19.0
186.crafty	2	104	22.3	2	104	22.3
197.parser	2	206	20.3	2	207	20.2
252.eon	2	128	23.5	2	109	27.6
253.perlbnmk	2	197	21.2	2	179	23.4
254.gap	2	109	23.3	2	111	23.1
255.vortex	2	138	31.9	2	138	31.9
256.bzip2	2	189	18.4	2	178	19.6
300.twolf	2	328	21.2	2	292	23.8

Hardware

CPU: AMD Opteron (TM) Model 240 EE
 CPU MHz: 1400
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 2
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x512MB PC3200 DDR SDRAM, ECC Registered
 Disk Subsystem: SCSI, Seagate Cheetah ST336753LW, Ultra 320
 Other Hardware: None

Software

Operating System: Microsoft Windows 2003 Enterprise Server
 Compiler: Intel C/C++ 7.0 build 20021212Z
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)
 MicroQuill Smartheap Library 6.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

shlw32M6.lib is the SmartHeap library V6.0 from MicroQuill www.microquill.com

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability:

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Baseline C:

+FDO -O3 -QxW -Qipo

Baseline C++:

+FDO -Qipo -GX -GR

Peak tuning:

164.gzip: +FDO -O3 -QaxK -Qipo -Oi-
 175.vpr: +FDO -O3 -QxW -Qipo
 176.gcc: +FDO -O3 -QxK -Qipo -Oi-
 181.mcf: +FDO -Qipo -Oa
 186.crafty: +FDO -O3 -QxW -Qipo
 197.parser: +FDO -O3 -QxW -Qipo -Oa
 252.eon: +FDO -O3 -QaxW -Qipo -Zp4
 253.perlbnmk: +FDO -O3 -Qipo -Oa shlw32M6.lib
 254.gap: +FDO -O3 -QxW -Qipo
 255.vortex: basepeak=1



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices
Rioworks HDAMA, AMD Opteron (TM) Model 240 EE

SPECint_rate2000 = 22.3
SPECint_rate_base2000 = 21.2

SPEC license #: 49 | Tested by: AMD, Austin, TX | Test date: Feb-2004 | Hardware Avail: Feb-2004 | Software Avail: May-2003

Notes/Tuning Information (Continued)

256.bzip2: +FDO -Qipo -Oa -Qunroll1
300.twolf: +FDO -Qxi -Qipo shlw32M6.lib

ONESTEP is used for all base and peak runs

The tested system can be assembled using an ATX case such as the Antec KS-282,
a 460W power supply such as the SPI Sparkle 460w and an AGP video card
BIOS version: 1.82