



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
AlphaServer GS1280 7/1300

SPECfp_rate2000 = 1224

SPECfp_rate_base2000 = 932

SPEC license #: 2 | Tested by: HP | Test date: Jun-2004 | Hardware Avail: Aug-2004 | Software Avail: Jul-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	64	161	738	64	67.3	1766
171.swim	64	76.7	3002	64	76.7	3002
172.mgrid	64	225	594	64	149	896
173.applu	64	124	1260	64	114	1363
177.mesa	64	135	769	64	118	883
178.galgel	64	122	1762	64	121	1783
179.art	64	115	1682	64	72.1	2676
183.equake	64	219	441	64	73.0	1322
187.facerec	64	152	929	64	136	1037
188.amp	64	264	618	64	229	713
189.lucas	64	117	1264	64	109	1359
191.fma3d	64	184	846	64	137	1138
200.sixtrack	64	225	363	64	210	389
301.apsi	64	192	1004	64	182	1062

Hardware

CPU: Alpha 21364
CPU MHz: 1300
FPU: Integrated
CPU(s) enabled: 64 cores, 64 chips, 1 core/chip
CPU(s) orderable: 2 to 64
Parallel: No
Primary Cache: 64KB(I)+64KB(D) on chip
Secondary Cache: 1.75MB on chip per CPU
L3 Cache: None
Other Cache: None
Memory: 2GB per CPU; 256MB RIMMs
Disk Subsystem: 18GB Ultra 320 15KRPM
Other Hardware: None

Software

Operating System: Tru64 UNIX V5.1B-1 + PK4
Compiler: Compaq C V6.5-011-48C5K
Program Analysis Tools V2.0
Spike V5.2 (510 USG)
HP Fortran V5.5A-3548-48D88
HP Fortran 77 V5.5A-3548-48D88
KAP Fortran V4.3 000607
KAP Fortran 77 V4.1 980926
KAP C V4.1 000607
File System: AdvFS, 14x18GB, RAID0
System State: Multi-user

Notes/Tuning Information

Baseline C: cc -arch ev7 -fast -O4 ONESTEP
Fortran: f90 -arch ev7 -fast -O5 ONESTEP

Peak:

All use -g3 -arch ev7 -non_shared ONESTEP
except these (which use only the tunings shown below):
173.applu 188.amp 191.fma3d
Individual benchmark tuning:
168.wupwise: kf77 -call_shared -inline all -tune ev67
-unroll 12 -automatic -align commons -arch ev67
-fkapargs=' -aggressive=c -fuse
-fuselevel=1 -so=2 -r=1 -o=1 -interleave
-ur=6 -ur2=060 ' +PFB
171.swim: same as base
172.mgrid: kf90 -call_shared -arch generic -O5 -inline
manual -nopipeline -transform_loops -unroll 9 -automatic



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
AlphaServer GS1280 7/1300

SPECfp_rate2000 = 1224
SPECfp_rate_base2000 = 932

SPEC license #: 2 | Tested by: HP | Test date: Jun-2004 | Hardware Avail: Aug-2004 | Software Avail: Jul-2004

Notes/Tuning Information (Continued)

```

-fkparms='-aggressive=a -fuse -interleave
-ur=2 -ur3=5 -cachesize=128,16000 ' +PFB
173.applu: kf90 -O5 -transform_loops
-fkparms='-o=0 -nointerleave -ur=14
-ur2=260 -ur3=18' +PFB
177.mesa: kcc -fast -O4 +CFB +IFB
178.galgel: f90 -O5 -fast -unroll 5 -automatic
179.art: kcc -assume whole_program -ldensemalloc
-call_shared -assume restricted_pointers
-unroll 16 -inline none -ckparms='
-fuse -fuselevel=1 -ur=3' +PFB
183.equake: cc -call_shared -arch generic -fast -O4
-ldensemalloc -assume restricted_pointers
-inline speed -unroll 13 -xtaso_short +PFB
187.facerec: f90 -O4 -nopipeline -inline all
-non_shared -speculate all -unroll 7
-automatic -assume accuracy_sensitive
-math_library fast +IFB
188.amp: cc -arch host -O4 -ifo -assume nomath_errno
-assume trusted_short_alignment -fp_reorder
-readonly_strings -ldensemalloc -xtaso_short
-assume restricted_pointers -unroll 9
-inline speed +CFB +IFB +PFB
189.lucas: kf90 -O5 -fkparms='-ur=1' +PFB
191.fma3d: kf90 -O4 -transform_loops -fkparms='-cachesize=128,16000 ' +PFB
200.sixtrack: f90 -fast -O5 -assume accuracy_sensitive
-notransform_loops +PFB
301.apsi: kf90 -O5 -inline none -call_shared -speculate all
-align commons -fkparms=' -aggressive=ab
-tune=ev5 -fuse -ur=1 -ur2=60 -ur3=20
-cachesize=128,16000'

```

Most benchmarks are built using one or more types of profile-driven feedback. The types used are designated by abbreviations in the notes:

+CFB: Code generation is optimized by the compiler, using feedback from a training run. These commands are done before the first compile (in phase "fdo_pre0"):

```

mkdir /tmp/pp
rm -f /tmp/pp/${baseexe}*

```

and these flags are added to the first and second compiles:

```

PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp/pp
PASS2_CFLAGS = -prof_use_feedback -prof_dir /tmp/pp

```

(Peak builds use /tmp/pp above; base builds use /tmp/pb.)

+IFB: Icache usage is improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_postN"):

```

mv ${baseexe} oldexe
spike oldexe -feedback oldexe -o ${baseexe}

```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
AlphaServer GS1280 7/1300

SPECfp_rate2000 = 1224
SPECfp_rate_base2000 = 932

SPEC license #: 2 | Tested by: HP | Test date: Jun-2004 | Hardware Avail: Aug-2004 | Software Avail: Jul-2004

Notes/Tuning Information (Continued)

+PFB: Prefetches are improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_post_makeN"):

```
rm -f *Counts*
mv ${baseexe} oldexe
pixie -stats dstride oldexe 1>pixie.out 2>pixie.err
mv oldexe.pixie ${baseexe}
```

A training run is carried out (in phase "fdo_runN"), and then this command (in phase "fdo_postN"):

```
spike oldexe -fb oldexe -stride_prefetch -o ${baseexe}
```

When Spike is used for both Icache and Prefetch improvements, only one spike command is actually issued, with the Icache options followed by the Prefetch options.

vm:

```
vm_bigpg_enabled = 1
vm_bigpg_thresh = 6
vm_swap_eager = 0
ubc_maxpercent = 50
```

proc:

```
max_per_proc_address_space = 34359738368
max_per_proc_data_size = 34359738368
max_per_proc_stack_size = 34359738368
max_proc_per_user = 2048
max_threads_per_user = 4096
maxusers = 2048
per_proc_address_space = 34359738368
per_proc_data_size = 34359738368
per_proc_stack_size = 34359738368
```

Portability: galgel: -fixed

Information on UNIX V5.1B Patches can be found at <http://ftpl.service.digital.com/public/unix/v5.1b/>

Processes were bound to CPUs using "runon".