



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL360 G4 (3.6GHz, Intel Xeon)

SPECint_rate2000 = 31.7
SPECint_rate_base2000 = 31.1

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jul-2004 Hardware Avail: Nov-2004 Software Avail: Aug-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	123	26.5	2	122	26.6
175.vpr	2	174	18.7	2	167	19.4
176.gcc	2	65.9	38.7	2	65.9	38.7
181.mcf	2	248	16.9	2	249	16.8
186.crafty	2	75.9	30.6	2	75.9	30.6
197.parser	2	146	28.7	2	147	28.5
252.eon	2	73.6	41.0	2	61.6	49.0
253.perlbnk	2	102	40.8	2	99.5	42.0
254.gap	2	71.8	35.5	2	70.6	36.2
255.vortex	2	80.5	54.8	2	80.9	54.5
256.bzip2	2	161	21.6	2	161	21.7
300.twolf	2	169	41.2	2	171	40.7

Hardware

CPU: Intel Xeon (3.6GHz, 1MB L2, 800MHz bus)
 CPU MHz: 3600
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (HT Technology disabled)
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 16K micro-ops I + 16KBD on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 2x1024MB PC2700 DDR-333
 Disk Subsystem: 1x230GB SATA
 Other Hardware:

Software

Operating System: Windows Server 2003 Standard (Build 3790)
 Compiler: Intel C++ Compiler 8.0 Build 20031211Z
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)
 MicroQuill Smartheap Library 7.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
 +FDO*: FDO (-QxP not used in PASS1 to enable cross-compilation)

Base tuning for C programs: -QxP -fast +FDO* shlw32M.lib

Base tuning for C++ programs: -QxP -fast -GX -GR

Portability flags:

176.gcc: -Dalloca=_alloca /F10000000

186.crafty: -DNT_i386

253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT

254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Peak tuning:

164.gzip: -QxP -fast -Oa +FDO ONESTEP=yes

175.vpr: -QxP -fast +FDO ONESTEP=yes

176.gcc: basepeak = 1

181.mcf: -QxP -fast +FDO ONESTEP=yes shlw32M.lib

186.crafty: -QxP -fast -Oa +FDO ONESTEP=yes shlw32M.lib

197.parser: -QxP -fast +FDO ONESTEP=yes

252.eon: -QxP -O2 -Qipo +FDO*

253.perlbnk: -fast -Oa +FDO ONESTEP=yes shlw32M.lib

254.gap: -QxP -fast +FDO ONESTEP=yes



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL360 G4 (3.6GHz, Intel Xeon)

SPECint_rate2000 = 31.7
SPECint_rate_base2000 = 31.1

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jul-2004 | Hardware Avail: Nov-2004 | Software Avail: Aug-2004

Notes/Tuning Information (Continued)

```
255.vortex:  -QxP -fast          +FDO ONESTEP=yes shlw32M.lib
256.bzip2:   -fast -Oa -Qunroll1 +FDO ONESTEP=yes
300.twolf:   -QxP -fast -O3       +FDO* shlw32M.lib [-O3 not in Pass 1]
BIOS Configuration Notes
HT Technology disabled
Adjacent Sector Prefetch disabled
```