



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V210 (1336MHz)

SPECfp2000 = 1117
SPECfp_base2000 = 1006

SPEC license #: 6 Tested by: Sun Microsystems Test date: Jan-2005 Hardware Avail: Jan-2005 Software Avail: Jan-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	145	1103	145	1103
171.swim	3100	379	818	192	1616
172.mgrid	1800	276	651	275	654
173.applu	2100	254	828	209	1003
177.mesa	1400	187	748	163	858
178.galgel	2900	164	1773	141	2061
179.art	2600	27.2	9575	26.3	9884
183.earthquake	1300	89.7	1449	83.2	1563
187.facerec	1900	119	1593	118	1606
188.amp	2200	447	493	424	519
189.lucas	2000	262	764	262	764
191.fma3d	2100	368	571	332	633
200.sixtrack	1100	243	452	234	470
301.apsi	2600	332	782	332	783

Hardware

CPU: UltraSPARC IIIi
CPU MHz: 1336
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KBI+64KBD on chip
Secondary Cache: 1MB(I+D) on chip
L3 Cache: None
Other Cache: None
Memory: 4GB 16-way interleaved
Disk Subsystem: 1 x 73GB
Other Hardware: None

Software

Operating System: Solaris 10
Compiler: Sun Studio 9
File System: ufs
System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
CXX: CC
F90: f90
F77: f90

Floating point base flags:

C: -fast -xipo=2 -xalias_level=std with ONESTEP=yes and feedback
F90: -fast -xipo=2 with ONESTEP=yes and feedback

Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: basepeak = yes
171.swim: -fast -xpad=common:3969 -xpagesize=64K -xprefetch=latx:1.6
-Option iropt -Atile:skewp,-Ainline:cs=700
(no feedback)



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V210 (1336MHz)

SPECfp2000 = 1117
SPECfp_base2000 = 1006

SPEC license #: 6 | Tested by: Sun Microsystems | Test date: Jan-2005 | Hardware Avail: Jan-2005 | Software Avail: Jan-2005

Notes/Tuning Information (Continued)

```
172.mgrid: -fast -xipo=2
173.applu: -fast -xipo=2
           -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
           -Qoption iropt -Aujam:inner=g
177.mesa: -fast -xipo=2 -xalias_level=strong -xrestrict
          -Wc,-Qms_pipe+unoovf
178.galgel: -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
            RM_SOURCES=lapak.f90
179.art: -fast -xipo=2 -xalias_level=std -xprefetch=latx:1.5
183.equake: -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
187.facerec: -fast -xipo=2 -xprefetch=latx:1.5
188.ammp: -fast -xarch=v9b -xipo=2 -xalias_level=std -lmopt -lm
189.lucas: basepeak = yes
191.fma3d: -fast -xipo=2 -stackvar -xprefetch_level=3
           -Qoption iropt -Apf:pdl=1
200.sixtrack: -xO4 -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2 -xprefetch=no
301.apsi: -fast -xipo=2
```

Feedback is done as follows, unless otherwise noted:

```
fdo_pre0: rm -rf ./feedback.profile ./SunWS_cache
PASS1: -xprofile=collect:./feedback
PASS2: -xprofile=use:./feedback
```

Portability:

```
178.galgel: -e -fixed
```

Shell Environments:

```
Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=512K
MPSSSTACK=512K
LD_PRELOAD=mpss.so.1
```

Kernel Parameters (/etc/system):

```
autoup=900
tune_t_fsflushr=1
```