



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell Inc.
PowerEdge SC1425 (3.6Ghz Intel Xeon)

SPECint2000 = 1707
SPECint_base2000 = 1686

SPEC license #: 55 Tested by: Dell Inc., Round Rock, TX Test date: Jan-2005 Hardware Avail: Feb-2005 Software Avail: Oct-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	117	1201	117	1193	
175.vpr	1400	116	1202	116	1202	
176.gcc	1100	54.4	2023	54.4	2023	
181.mcf	1800	95.8	1880	95.8	1880	
186.crafty	1000	74.7	1339	74.3	1345	
197.parser	1800	122	1471	122	1471	
252.eon	1300	58.1	2237	57.8	2248	
253.perlbnk	1800	97.8	1840	85.9	2096	
254.gap	1100	57.4	1915	57.4	1915	
255.vortex	1900	69.5	2733	69.5	2735	
256.bzip2	1500	119	1264	118	1270	
300.twolf	3000	168	1786	166	1809	

Hardware

CPU: Intel Xeon (3.6Ghz, 2MB L2, 800MHz system bus)
CPU MHz: 3600
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K(I) micro-ops + 16KB(D) on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4x512MB (dual-ranked) ECC DDR2-400 SDRAM
Disk Subsystem: 1 x 36GB 15000RPM SCSI
Other Hardware: None

Software

Operating System: Windows 2003 Server, Standard Edition
Compiler: Intel C/C++ Compiler 8.1 (20041019Z)
Intel Fortran Compiler 8.1 (20041019Z)
Microsoft Visual Studio .NET 2003(7.1.3088)
MicroQuill SmartHeap Library 7.1
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: Approved src.alt stdcpp
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast -QxP -Qansi_alias +FDO
C++: -QxP -Qipo -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast -QxP -Qansi_alias -Oa +FDO
175.vpr: basepeak=yes
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -QxP -Oa +FDO shlW32M.lib
197.parser: basepeak=yes
252.eon: -fast -QxP +FDO



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell Inc.
PowerEdge SC1425 (3.6Ghz Intel Xeon)

SPECint2000 =	1707
SPECint_base2000 =	1686

SPEC license #: 55 | Tested by: Dell Inc., Round Rock, TX | Test date: Jan-2005 | Hardware Avail: Feb-2005 | Software Avail: Oct-2004

Notes/Tuning Information (Continued)

```
253.perlbnk: -fast -QxP -Qansi_alias +FDO shlw32M.lib
254.gap:      basepeak=yes
255.vortex   -fast -QxP +FDO
256.bzip2:   -fast -QxP -Qunroll11 -Oa +FDO
300.twolf:   -fast -QxP +FDO shlw32M.lib
```