



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire E6900 (12 processor)

SPECint\_rate2000 = 189  
SPECint\_rate\_base2000 = 170

SPEC license #: 6 Tested by: Sun Microsystems Test date: Jan-2005 Hardware Avail: Feb-2005 Software Avail: Jan-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	24	296	132	24	261	149
175.vpr	24	258	151	24	253	154
176.gcc	24	198	155	24	170	180
181.mcf	24	296	170	24	253	198
186.crafty	24	156	179	24	126	222
197.parser	24	319	157	24	284	176
252.eon	24	152	238	24	150	241
253.perlbnk	24	276	181	24	252	199
254.gap	24	297	103	24	234	131
255.vortex	24	178	297	24	172	308
256.bzip2	24	222	188	24	214	195
300.twolf	24	504	166	24	486	172

### Hardware

CPU: UltraSPARC IV  
CPU MHz: 1350  
FPU: Integrated  
CPU(s) enabled: 24 cores, 12 chips, 2 cores/chip  
CPU(s) orderable: 4, 8, 12, 16, 20, 24 (order by number of chips)  
Parallel: No  
Primary Cache: 32KBI+64KBD per core on chip (64KBI+128KBD on chip)  
Secondary Cache: 8MB(I+D) per core off chip (16MB(I+D) off chip)  
L3 Cache: None  
Other Cache: None  
Memory: 96GB 16-way interleaved  
Disk Subsystem: Sun StorEdge S1 Disk Array (2x36GB)  
Sun StorEdge 6120 Array (14x73GB)  
Other Hardware: None

### Software

Operating System: Solaris 10  
Compiler: Sun Studio 10  
File System: ufs (default ufs logging on with Solaris 10)  
System State: Multi-User

## Notes/Tuning Information

Compiler invocation:

C: cc  
CXX: CC

Integer base flags:

-fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:

ONESTEP=yes and feedback for all benchmarks

164.gzip: -xO4 -xbuiltin=%all -xtarget=native -xalias\_level=std  
-xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp\_filtering\_margin=30,  
-Qeps:do\_spec\_load=1  
175.vpr: -fast -xalias\_level=std -xipo=2 -Wc,-Qeps:enabled=1,  
-Qeps:rp\_filtering\_margin=100,-Qeps:do\_spec\_load=1 -lmopt -lm  
176.gcc: -fast -xipo=2 -l12amm  
181.mcf: -fast -xipo=2 -xprefetch\_level=2 -Wc,-Qeps:enabled=1



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire E6900 (12 processor)

SPECint\_rate2000 = 189  
SPECint\_rate\_base2000 = 170

SPEC license #: 6 | Tested by: Sun Microsystems | Test date: Jan-2005 | Hardware Avail: Feb-2005 | Software Avail: Jan-2005

## Notes/Tuning Information (Continued)

```

186.crafty: -fast -xinline= -xipo=2 -xalias_level=strong -W2,-Ashort_ldst
            Feedback adds -xlinkopt in PASS2
197.parser: -fast -xipo=2 -xalias_level=strong
            -Wc,-Qgsched-T6,-Qipa:valueprediction
252.eon:    -fast -xipo=2 -xalias_level=compatible
253.perlbnk: -fast -xipo=2 -xalias_level=std -xsafe=mem
            -Wc,-Qeps:enabled=1,-Qeps:ws=8,-Qiselect-sw_pf_tbl_th=20,
            -Qiselect-funcalign=32,-Qicache-chbab=1
254.gap:    -fast -xipo=2 -xalias_level=strong -W2,-Abcopy -xvector
            -xprefetch_level=3
255.vortex: -fast -xrestrict -xipo=2 -Wc,-Qeps:enable=1
            -W2,-Ainline:recursion=1:cs=500:irs=6000
            -Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=32
            -Wc,-Qpeep-Sh0 -W2,-crit -ll2amm
256.bzip2:  -fast -xipo -xalias_level=strong -xrestrict
            -Wc,-Qeps:enabled=1 -xsafe=mem -Qeps:rp_filtering_margin=99
300.twolf:  -fast -xalias_level=strong -xsafe=mem -xipo=2
            -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:     -xprofile=collect:./feedback
PASS2:     -xprofile=use:./feedback

```

Portability:

```

176.gcc:   -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
252.eon:   -library=iostream
            srcalt = fmax_errno
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap:   -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
            -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

The system was configured with multiple file systems.  
The O/S was installed on one disk of the Sun StorEdge S1  
Disk Array (ufs, ufs w/logging). The benchmark was run on  
the Sun StorEdge 6120 Array, using H/W Raid 5 and ufs with  
ufs logging file system.