# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## IBM Corporation

IBM eServer xSeries 336 (3.2 GHz Intel Xeon)

SPECfp_rate2000 = 19.4

SPECfp_rate_base2000 = 19.1

SPEC license #: 11 | Tested by: IBM, Research Triangle Park, NC | Test date: May-2005 | Hardware Avail: Feb-2005 | Software Avail: Apr-2005




| Benchmark | Base Copies | Base Runtime | Base Ratio | Copies | Runtime | Ratio |
|---|---|---|---|---|---|---|
| 168.wupwise | 1 | 66.8 | 27.8 | 1 | 66.8 | 27.8 |
| 171.swim | 1 | 138 | 26.0 | 1 | 138 | 26.0 |
| 172.mgrid | 1 | 129 | 16.2 | 1 | 129 | 16.2 |
| 173.applu | 1 | 153 | 15.9 | 1 | 154 | 15.8 |
| 177.mesa | 1 | 99.8 | 16.3 | 1 | 99.8 | 16.3 |
| 178.galgel | 1 | 90.9 | 37.0 | 1 | 90.9 | 37.0 |
| 179.art | 1 | 69.0 | 43.7 | 1 | 69.0 | 43.7 |
| 183.equake | 1 | 71.4 | 21.1 | 1 | 59.9 | 25.2 |
| 187.facerec | 1 | 113 | 19.6 | 1 | 113 | 19.6 |
| 188.ammp | 1 | 194 | 13.2 | 1 | 194 | 13.2 |
| 189.lucas | 1 | 102 | 22.7 | 1 | 101 | 23.0 |
| 191.fma3d | 1 | 156 | 15.6 | 1 | 156 | 15.6 |
| 200.sixtrack | 1 | 190 | 6.70 | 1 | 188 | 6.79 |
| 301.apsi | 1 | 219 | 13.8 | 1 | 219 | 13.8 |

### Hardware

| | |
|---|---|
| CPU: | Intel Xeon (3.2 GHz Xeon, 2MB L2 Cache, 800 MHz system bus) |
| CPU MHz: | 3200 |
| FPU: | Integrated |
| CPU(s) enabled: | 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled) |
| CPU(s) orderable: | 1,2 |
| Parallel: | No |
| Primary Cache: | 12K(I) micro-ops + 16KB(D) on chip |
| Secondary Cache: | 2048KB(I+D) on chip |
| L3 Cache: | N/A |
| Other Cache: | N/A |
| Memory: | 8 x 512 MB ECC PC2-3200 Single Rank |
| Disk Subsystem: | 73GB SCSI 10K RPM |
| Other Hardware: | |

### Software

| | |
|---|---|
| Operating System: | Windows Server 2003 Standard Edition |
| Compiler: | Intel C/C++ Compiler 8.1 (20050409)<br>Intel Fortran Compiler 8.1 (20050405Z)<br>Microsoft Visual Studio .NET 13.0.9466 (for libraries)<br>MicroQuill Smartheap Library 7.30 |
| File System: | NTFS |
| System State: | Default |

## Notes/Tuning Information

```
GENERAL
  ONESTEP=yes
  +FDO:   PASS1=-Qprof_gen  PASS2=-Qprof_use
PORTABILITY
  178.galgel:   -FI /F32000000
BASE TUNING
  C/F77/F90:    -fast -QxP -Qansi_alias     +FDO
PEAK TUNING
  168.wupwise:  basepeak=yes
  171.swim:     -fast -QxP -f77rtl +FDO
  172.mgrid:    basepeak=yes
  173.applu:    -fast -QxP -Qscalar_rep- -Qauto -f77rtl +FDO
  177.mesa:     basepeak=yes
  178.galgel:   basepeak=yes
  179.art:      basepeak=yes
  183.equake:   -fast -QxP -Qansi_alias -Oa -Qrcd +FDO shlW32M.lib
  187.facerec:  basepeak=yes
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation



## Notes/Tuning Information (Continued)

```
188.ammp:     basepeak=yes
189.lucas:    -fast -QxP
191.fma3d:    basepeak=yes
200.sixtrack: -QxP -Qipo +FDO
301.apsi:     -fast -QxP -f77rtl +FDO
```