



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## IBM Corporation

### IBM eServer xSeries 346 (3.0 GHz Intel Xeon)

SPECint\_rate2000 = 35.2

SPECint\_rate\_base2000 = 34.5

SPEC license #: 11 | Tested by: IBM, Research Trinagle Park, NC | Test date: May-2005 | Hardware Avail: Feb-2005 | Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	4	207	31.4	4	208	31.2
175.vpr	4	268	24.2	4	268	24.2
176.gcc	4	110	46.4	4	110	46.4
181.mcf	4	351	23.8	4	351	23.8
186.crafty	4	169	27.5	4	174	26.6
197.parser	4	243	34.4	4	243	34.4
252.eon	4	142	42.6	4	141	42.9
253.perlbnk	4	236	35.4	4	219	38.1
254.gap	4	130	39.4	4	130	39.4
255.vortex	4	158	55.6	4	158	55.9
256.bzip2	4	226	30.8	4	227	30.7
300.twolf	4	397	35.0	4	328	42.4

### Hardware

CPU: Intel Xeon (3.0 GHz Xeon, 2MB L2 Cache, 800 MHz system bus)  
 CPU MHz: 3000  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology enabled)  
 CPU(s) orderable: 1  
 Parallel: No  
 Primary Cache: 12K(I) micro-ops + 16KB(D) on chip  
 Secondary Cache: 2048KB(I+D) on chip  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 8 x 512 MB ECC PC2-3200 Single Rank  
 Disk Subsystem: 73GB SCSI 10K RPM  
 Other Hardware:

### Software

Operating System: Windows Server 2003 Standard Edition  
 Compiler: Intel C/C++ Compiler 8.1 (20050409)  
 Intel Fortran Compiler 8.1 (20050405Z)  
 Microsoft Visual Studio .NET 13.0.9466 (for libraries)  
 MicroQuill Smartheap Library 7.30  
 File System: NTFS  
 System State: Default

## Notes/Tuning Information

### GENERAL

ONESTEP=yes  
 +FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

### PORTABILITY FLAGS

176.gcc: -Dalloca=\_alloca /F10000000  
 186.crafty: -DNT\_i386  
 253.perlbnk: -DSPEC\_CPU2000\_NTOS -DPERLDLL /MT  
 254.gap: -DSYS\_HAS\_CALLOC\_PROTO -DSYS\_HAS\_MALLOC\_PROTO

### BASE TUNING

C: -fast -QxP -Qansi\_alias +FDO  
 C++: -QxP -Qipo -Qcxx\_features +FDO

### PEAK TUNING

164.zip: -fast -QxP -Qansi\_alias -Oa +FDO  
 175.vpr: basepeak=yes  
 176.gcc: basepeak=yes  
 181.mcf: basepeak=yes  
 186.crafty: -fast -QxP -Oa +FDO shlW32M.lib  
 197.parser: basepeak=yes  
 252.eon: -fast -QxP +FDO  
 253.perlbnk: -fast -QxP -Qansi\_alias +FDO shlW32M.lib



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation  
IBM eServer xSeries 346 (3.0 GHz Intel Xeon)

SPECint\_rate2000 = 35.2  
SPECint\_rate\_base2000 = 34.5

SPEC license #: 11 | Tested by: IBM, Research Triangle Park, NC | Test date: May-2005 | Hardware Avail: Feb-2005 | Software Avail: Apr-2005

## Notes/Tuning Information (Continued)

```
254.gap:      basepeak=yes
255.vortex    -fast -QxP +FDO
256.bzip2:    -fast -QxP -Qunroll1 -Oa +FDO
300.twolf:    -fast -QxP +FDO shlw32M.lib
EXTRA LIBRARIES
shlw32M.lib:  MicroQuill SmartHeap Library 7.3
              www.microquill.com
```