



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4100

SPECfp2000 = 2344

SPECfp_base2000 = 2132

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Aug-2005 Hardware Avail: Oct-2005 Software Avail: Nov-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	54.7	2924	52.9	3026	
171.swim	3100	68.4	4531	66.1	4693	
172.mgrid	1800	95.5	1885	89.9	2002	
173.applu	2100	92.4	2273	86.0	2442	
177.mesa	1400	85.8	1631	72.4	1934	
178.galgel	2900	83.3	3480	60.5	4791	
179.art	2600	106	2454	106	2454	
183.equake	1300	69.0	1884	63.7	2040	
187.facerec	1900	64.8	2931	44.0	4322	
188.amp	2200	148	1490	145	1521	
189.lucas	2000	108	1855	108	1855	
191.fma3d	2100	113	1859	110	1916	
200.sixtrack	1100	138	799	135	815	
301.apsi	2600	116	2233	106	2461	

Hardware

CPU: AMD Opteron (TM) 254
CPU MHz: 2800
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1,2 (order by # of chips)
Parallel: No
Primary Cache: 64KBI + 64KBD (on chip) per core
Secondary Cache: 1024KB (I+D) (on chip) per core
L3 Cache: N/A
Other Cache: N/A
Memory: 8GB (4x2GB, PC3200 CL3 DDR SDRAM ECC Registered)
Disk Subsystem: SAS, 36GB, 10K RPM
Other Hardware: None

Software

Operating System: Solaris 10 3/05 HW1
Compiler: Sun Studio 11
File System: ufs
System State: Multi-user

Notes/Tuning Information

Compiler invocation:

C: cc
F90: f90
F77: f90

FDO: PASS1= -xprofile=collect:./feedback PASS2= -xprofile=use:./feedback
fdo_pre0: rm -rf ./feedback.profile

Floating point base flags:

F90: -fast -xipo=2 -xarch=amd64 -xprefetch_level=3 ONESTEP=yes
C: -fast -xcrossfile -xalias_level=std -xpagesize=2m ONESTEP=yes

Floating point peak flags:

ONESTEP=yes for all benchmarks

168.wupwise: -fast -xpad=common:3969 -xipo=2 -xarch=amd64 -xprefetch_level=3 -xpagesize_heap=2m



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4100

SPECfp2000 = 2344

SPECfp_base2000 = 2132

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Aug-2005 Hardware Avail: Oct-2005 Software Avail: Nov-2005

Notes/Tuning Information (Continued)

```

171.swim:      -fast -xpad=common:3969 -xipo=2 -xvector=simd -xprefetch_level=3 -Qoption iropt
               -Atile:skewp,-Ainline:cs=700 -xarch=amd64 -Qoption ube_ipa -inl_alt
               -xpagesize_stack=2m
172.mgrid:    -fast -stackvar -xpad=common:900 -xipo=2 -xarch=amd64 -xprefetch_level=3 -xvector
               -xpagesize=2m -Qoption ld -M,/usr/lib/ld/map.bssalign
173.applu:    -fast -stackvar -xO4 -xipo=2 -xprefetch_level=3 -xarch=amd64
               -qoption iropt -Rloop_dist -xpagesize_heap=2m
177.mesa:    -fast -xO4 -xipo=2 -Wd,-iropt-prof -xarch=amd64 -xalias_level=strong -xpagesize=2m +FDO
178.galgel:   -fast -xipo=2 -xpagesize_heap=2m -xprefetch_level=3 -xvector=simd -xarch=amd64
               RM_SOURCES=lapak.f90
               EXTRALIBS=-xlic_lib=sunperf
179.art:      basepeak=yes
183.equake:   -fast -xipo=2 -xprefetch -xalias_level=strong -xpagesize=2m -lmopt -lm +FDO
187.facerec:  -fast -xO4 -xipo=2 -xprefetch_level=3 -xpagesize=2m
               RM_SOURCES=cfft.f90 cffti.f90 cfftf.f90
               EXTRALIBS=-xlic_lib=sunperf
188.ammp:    -fast -xO4 -xipo=2 -xarch=amd64 -xalias_level=std -xpagesize_heap=2m -lmopt -lm
189.lucas:    basepeak=yes
191.fma3d:   -fast -fsimple=1 -xipo=2 -xprefetch_level=3 -xarch=amd64 -xpagesize_heap=2m +FDO
200.sixtrack: -fast -xipo=2 -O -xprefetch_level=3 -xarch=amd64 -xpagesize_heap=2m
               -Qoption ld -M,/usr/lib/ld/map.bssalign +FDO
301.apsi:    -fast -xO4 -xipo=2 -xprefetch_level=3 -xarch=amd64 -xpagesize=2m

```

Portability:

178.galgel: -e -fixed -DSPEC_CPU2000_LP64

Shell Environments:

Stack size set to unlimited via "ulimit -s unlimited"

Kernel Parameters (/etc/system):

autoup=900
tune_t_fsflushr=1

Processes were bound to CPU using submit=pbind

Default BIOS setting was used ; Only one CPU was present on the system