



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries 226 (2.8 GHz Xeon, 2MB L2 Cache)

SPECint2000 = 1387

SPECint_base2000 = 1380

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: Jun-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
164.gzip	1400	151	925	150	933	[Bar chart showing ratio 933]			
175.vpr	1400	148	948	144	971	[Bar chart showing ratio 971]			
176.gcc	1100	67.4	1632	67.4	1632	[Bar chart showing ratio 1632]			
181.mcf	1800	106	1691	106	1691	[Bar chart showing ratio 1691]			
186.crafty	1000	96.3	1038	96.6	1035	[Bar chart showing ratio 1035]			
197.parser	1800	154	1165	154	1169	[Bar chart showing ratio 1169]			
252.eon	1300	73.8	1760	74.1	1754	[Bar chart showing ratio 1754]			
253.perlbmk	1800	108	1663	107	1675	[Bar chart showing ratio 1675]			
254.gap	1100	73.0	1507	71.3	1542	[Bar chart showing ratio 1542]			
255.vortex	1900	78.0	2437	77.8	2441	[Bar chart showing ratio 2441]			
256.bzip2	1500	142	1054	142	1056	[Bar chart showing ratio 1056]			
300.twolf	3000	209	1437	209	1436	[Bar chart showing ratio 1436]			

Hardware

CPU: Intel Xeon 2.8 GHz (800 MHz system bus)
CPU MHz: 2800
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12K(I) micro-ops + 16KB(D) on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4 x 2048 MB ECC PC2-3200 Single Rank
Disk Subsystem: 73GB SCSI 15K RPM
Other Hardware:

Software

Operating System: Windows Server 2003 Standard Edition
Compiler: Intel C/C++ Compiler 9.0 (20050624Z) for 32-bit applications
Intel Fortran Compiler 9.0 (20050624Z) for 32-bit applications
Microsoft Visual Studio .NET 13.0.9466 (for libraries)
MicroQuill Smartheap Library 7.30
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: srcalt=stdcpp
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast -Qansi_alias +FDO shlw32M.lib
C++: -fast -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast +FDO
175.vpr: -fast +FDO
176.gcc: basepeak=yes
181.mcf: -fast +FDO shlw32M.lib
186.crafty: -fast -Oa +FDO shlw32M.lib
197.parser: -fast +FDO
252.eon: -fast +FDO



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries 226 (2.8 GHz Xeon, 2MB L2 Cache)

SPECint2000 = 1387

SPECint_base2000 = 1380

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: Jun-2005

Notes/Tuning Information (Continued)

```
253.perlbnk: -fast -Oa +FDO shlw32M.lib
254.gap:      -fast +FDO
255.vortex   -fast +FDO shlw32M.lib
256.bzip2:   -fast -Qunroll11 -Oa +FDO shlw32M.lib
300.twolf:   -fast +FDO shlw32M.lib
EXTRA LIBRARIES
shlw32M.lib: MicroQuill SmartHeap Library 7.1
              www.microquill.com
```