



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G4 (2.8GHz, Intel dual-core Xeon)

SPECint_rate2000 = 16.0
SPECint_rate_base2000 = 16.0

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Sep-2005 Hardware Avail: Oct-2005 Software Avail: Jun-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	149	10.9	1	150	10.8
175.vpr	1	148	10.9	1	145	11.2
176.gcc	1	67.6	18.9	1	67.6	18.9
181.mcf	1	105	19.8	1	105	19.8
186.crafty	1	97.4	11.9	1	97.5	11.9
197.parser	1	155	13.5	1	155	13.5
252.eon	1	74.3	20.3	1	74.4	20.3
253.perlbnk	1	108	19.3	1	108	19.4
254.gap	1	72.8	17.5	1	71.5	17.8
255.vortex	1	78.7	28.0	1	78.6	28.0
256.bzip2	1	142	12.2	1	142	12.2
300.twolf	1	211	16.5	1	211	16.5

Hardware

CPU: Intel dual-core Xeon (2.8GHz, 2x2MB L2, 800MHz bus)
CPU MHz: 2800
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD (on chip) per core
Secondary Cache: 2048KB(I+D) (on chip) per core
L3 Cache: N/A
Other Cache: N/A
Memory: 4x2048MB PC2-3200
Disk Subsystem: 1x72.8GB 15K Ultra320 SCSI
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 9.0 Build 20050624Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning for C programs: -fast +FDO ONESTEP=yes shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO ONESTEP=yes

Portability flags:

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERL DLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Peak tuning:

164.gzip: -fast +FDO ONESTEP=yes
175.vpr: -fast +FDO ONESTEP=yes
176.gcc: basepeak = 1
181.mcf: -fast +FDO ONESTEP=yes shlw32M.lib
186.crafty: -fast -Oa +FDO ONESTEP=yes shlw32M.lib
197.parser: -fast +FDO ONESTEP=yes
252.eon: -fast +FDO
253.perlbnk: -fast -Oa +FDO ONESTEP=yes shlw32M.lib
254.gap: -fast +FDO ONESTEP=yes
255.vortex: -fast +FDO ONESTEP=yes shlw32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G4 (2.8GHz, Intel dual-core Xeon)

SPECint_rate2000 = 16.0
SPECint_rate_base2000 = 16.0

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Sep-2005 | Hardware Avail: Oct-2005 | Software Avail: Jun-2005

Notes/Tuning Information (Continued)

```
256.bzip2: -fast -Oa -Qunroll1 +FDO ONESTEP=yes shlw32M.lib
300.twolf: -fast +FDO shlw32M.lib
BIOS Configuration Notes
Hyper-Threading Technology disabled
Other Configuration Notes
/NUMPROC=1 flag was added to boot.ini to invoke uniprocessor environment.
```