



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro X6DHP-TG Motherboard

SPECint_rate2000 = 41.4
SPECint_rate_base2000 = 41.4

SPEC license #01176 | Tested by: Supermicro | Test date: Oct-2005 | Hardware Avail: Sep-2005 | Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	171	38.0	4	173	37.6
175.vpr	4	255	25.5	4	246	26.4
176.gcc	4	91.2	56.0	4	91.2	56.0
181.mcf	4	375	22.3	4	375	22.3
186.crafty	4	138	33.7	4	137	33.8
197.parser	4	201	41.5	4	201	41.5
252.eon	4	110	54.9	4	110	54.7
253.perlbnk	4	173	48.2	4	174	47.9
254.gap	4	112	45.7	4	112	45.7
255.vortex	4	130	67.6	4	130	67.6
256.bzip2	4	200	34.9	4	203	34.3
300.twolf	4	266	52.4	4	265	52.6

Hardware

CPU: Intel Xeon Processor (3.80 GHz, 2MB L2, 800 MHz bus)
 CPU MHz: 3800
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology Enabled)
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 12k micro-ops I + 16KBD on chip
 Secondary Cache: 2048KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 6GB (6x1GB 2 X 1GB DDR 333 REG ECC)
 Disk Subsystem: 1 X 40GB IDE
 Other Hardware: N/A

Software

Operating System: Windows 2003 EE SP1
 Compiler: Intel C++ Compiler 9.0 Build 20050430Z (32-bit)
 Microsoft Visual Studio .Net 2003(for libraries)
 SmartHeap Library Version 7.4 from <http://www.microquill.com/>
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
shlw32M.lib is the SmartHeap Library
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: Approved stdcpp src.alt used
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro
X6DHP-TG Motherboard

SPECint_rate2000 = 41.4

SPECint_rate_base2000 = 41.4

SPEC license #01176 | Tested by: Supermicro | Test date: Oct-2005 | Hardware Avail: Sep-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

```
255.vortex      basepeak=yes
256.bzip2:      -fast -Oa -Qunroll1 +FDO
300.twolf:      -fast -O3 +FDO shlW32M.lib
New 32-bit Windows tools used, approved in May-2005
Product description located as of:
http://www.supermicro.com/products/motherboard/Xeon800/E7520/X6DHP-TG.cfm
The system bus runs at 800MHz
```