CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated
Altos G5350 (AMD Opteron (TM) 246)

SPECfp_rate2000 = 17.7

SPECfp_rate_base2000 = 16.4

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Nov-2005 | Hardware Avail: Jul-2005 | Software Avail: Jun-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	73.5	25.2	1	74.0	25.1
171.swim	1	157	22.9	1	156	23.1
172.mgrid	1	140	14.9	1	140	14.9
173.applu	1	169	14.4	1	160	15.2
177.mesa	1	184	8.80	1	94.6	17.2
178.galgel	1	124	27.1	1	114	29.6
179.art	1	72.7	41.5	1	72.7	41.5
183.equake	1	92.7	16.3	1	91.5	16.5
187.facerec	1	121	18.3	1	121	18.3
188.ammp	1	229	11.1	1	199	12.8
189.lucas	1	128	18.1	1	114	20.3
191.fma3d	1	167	14.6	1	164	14.8
200.sixtrack	1	181	7.07	1	180	7.08
301.apsi	1	233	12.9	1	234	12.9

Hardware

CPU:	AMD Opteron (TM) 246
CPU MHz:	2000
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	64KBI + 64KBD on chip, per core
Secondary Cache:	1024KB (I+D) on chip, per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4 x 1024MB, DDR400 CL3 ECC
Disk Subsystem:	1 x 36GB 10000RPM U320 SCSI HDD
Other Hardware:	None

Software

Operating System:	Microsoft Windows Server 2003 Enterprise Edition (Build 3790)
Compiler:	Intel C++ 9.0 build 20050430Z for IA32 Intel Fortran 9.0 build 20050722Z for IA32 PGI Fortran compiler 6.0-5 PGI C compiler 6.0-5 ACML Version 2.5.3 (bundled with PGI 6.0-5)
File System:	NTFS
System State:	default

Notes/Tuning Information

```
+FDO:
 icl, ifort  : PASS1=-Qprof_gen  PASS2=-Qprof_use
 pgf90       : PASS1=-Mpfi       PASS2=-Mpfo
ifort is the Intel Fortran compiler, icl is the Intel C++ compiler and
pgf90 is the PGI Fortran 90 compiler.
pgcc is the PGI C compiler.
ONESTEP is set to 1 for every compile with the PGI compilers.
Portability:
178.galgel:                 -Mfixed
Baseline: C      :  pgcc    -fastsse -Mipa=fast,inline
Baseline: Fortran:  pgf90   -fastsse -Mipa=fast,inline +FDO
Peak tuning:
168.wupwise:        pgf90   -fastsse -Mipa=fast,inline -Mnovect
171.swim:           ifort   -Qipo  -O3  -QaxN -QxW -Qunroll0 +FDO
172.mgrid:          pgf90   -fastsse -Mipa=fast,inline
173.applu:          ifort   -Qipo  -O3 -QaxN -QxW -auto +FDO
177.mesa:           icl     -Qipo -arch:SSE2 -Qunroll1 -Qansi_alias +FDO
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
                    -Qoption,f,-ip_ninl_max_stats=1500,-ip_ninl_max_total_stats=4500
178.galgel:         pgf90   -fastsse -Mipa=fast,safe RM_SOURCES=lapak.f90
                            -Munix -lacml
179.art:            pgcc     basepeak=yes
183.equake:         icl     -fast -arch:SSE2 -QaxW +FDO
187.facerec:        pgf90   -fastsse -Mipa=fast,inline +FDO
188.ammp:           icl     -Oa   -arch:SSE2  -Zp4 -Qansi_alias
189.lucas:          ifort   -Qipo -QxW -Qunroll1
191.fma3d:          pgf90   -Mipa=fast,inline -fastsse -Mnovect +FDO
200.sixtrack:       pgf90   -fastsse -Mipa=fast,inline
301.apsi:           pgf90   -fastsse -Mipa=fast,inline
```