CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX300 S2, Intel Xeon processor 3.20GHz, 2MB L2

SPECfp_rate2000 = 31.4

SPECfp_rate_base2000 = 31.4

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	74.0	50.2	2	74.0	50.2
171.swim	2	265	27.1	2	265	27.1
172.mgrid	2	174	24.0	2	174	24.0
173.applu	2	212	23.0	2	212	23.0
177.mesa	2	100	32.3	2	100	32.3
178.galgel	2	99.9	67.3	2	99.9	67.3
179.art	2	83.2	72.5	2	83.2	72.5
183.equake	2	78.9	38.2	2	78.9	38.2
187.facerec	2	125	35.3	2	125	35.3
188.ammp	2	221	23.1	2	221	23.1
189.lucas	2	177	26.2	2	177	26.2
191.fma3d	2	201	24.3	2	201	24.3
200.sixtrack	2	172	14.8	2	172	14.8
301.apsi	2	234	25.8	2	234	25.8

Hardware

CPU:	Intel Xeon processor 3.20GHz, 2MB L2, 800MHz system bus
CPU MHz:	3200
FPU:	Integrated
CPU(s) enabled:	2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	12k micro-ops I + 16KBD on chip
Secondary Cache:	2048KB(I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8x512 MB DDRII-RAM PC2-3200R
Disk Subsystem:	Fujitsu MAS3184NC (U320, 15krpm)
Other Hardware:	none

Software

Operating System:	Windows Server 2003 Enterprise Edition + SP1
Compiler:	Intel C and Fortran Compiler 9.0 Build 20050722Z (for 32-bit applications) Microsoft Visual Studio .Net 2003 7.1.3088 (for libraries) SmartHeap Library Version 7.4 from http://www.microquill.com
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
GENERAL
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use

Portability flags
   178.galgel:  -FI /F32000000

Base tuning flags
   for Fortran programs: -fast -Qansi_alias +FDO shlW32M.lib
   for C programs:       -fast +FDO shlw32M.lib

Peak tuning flags
   same as baseline (basepeak=true set globally)

New 32-bit Windows tools used, approved in May-2005

The system bus runs at 800 MHz
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries