



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation  
IBM System p5 575 (2200 MHz, 8 CPU)

SPECint\_rate2000 = 200  
SPECint\_rate\_base2000 = 196

SPEC license #: 11 | Tested by: IBM | Test date: Dec-2005 | Hardware Avail: Feb-2006 | Software Avail: Feb-2006

| Benchmark   | Base Copies | Base Runtime | Base Ratio | Copies | Runtime | Ratio |
|-------------|-------------|--------------|------------|--------|---------|-------|
| 164.gzip    | 16          | 206          | 126        | 16     | 200     | 130   |
| 175.vpr     | 16          | 147          | 177        | 16     | 145     | 180   |
| 176.gcc     | 16          | 102          | 200        | 16     | 102     | 201   |
| 181.mcf     | 16          | 86.4         | 387        | 16     | 107     | 312   |
| 186.crafty  | 16          | 126          | 147        | 16     | 103     | 181   |
| 197.parser  | 16          | 182          | 184        | 16     | 185     | 181   |
| 252.eon     | 16          | 111          | 218        | 16     | 111     | 218   |
| 253.perlbnk | 16          | 243          | 138        | 16     | 217     | 154   |
| 254.gap     | 16          | 112          | 182        | 16     | 111     | 183   |
| 255.vortex  | 16          | 115          | 307        | 16     | 110     | 321   |
| 256.bzip2   | 16          | 134          | 208        | 16     | 129     | 217   |
| 300.twolf   | 16          | 278          | 200        | 16     | 284     | 196   |

### Hardware

CPU: POWER5+  
 CPU MHz: 2200  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 8 chips, 1 core/chip (SMT on)  
 CPU(s) orderable: 8,16  
 Parallel: No  
 Primary Cache: 64KBI+32KBD (on chip)/core  
 Secondary Cache: 1920KB unified, shared (on chip)/chip  
 L3 Cache: 36MB unified (off-chip)/DCM, 8 DCMs/SUT  
 Other Cache: None  
 Memory: 64x512MB  
 Disk Subsystem: 2x73GB SCSI, 15K RPM  
 Other Hardware: None

### Software

Operating System: AIX 5L V5.3  
 Compiler: XL C/C++ Enterprise Edition Version 8.0 for AIX  
 File System: AIX/JFS2  
 System State: Multi-user

## Notes/Tuning Information

### Portability Flags:

```
176.gcc: -ma -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DAIX
253.perlbnk: -DSPEC_CPU2000_AIX
254.gap: -DSYS_IS_BSD -DSYS_STRING_H
        -DSYS_HAS_MALLOC_PROTO -DSYS_HAS_CALLOC_PROTO
300.twolf: -DHAVE_SIGNED_CHAR
```

### Base Optimization Flags:

```
C: -qpdf1/pdf2
   -O5 -blpdata -D_ILS_MACROS
C++: -qpdf1/pdf2
      -O4 -qalign=natural
```

### Peak Optimization Flags

```
164.gzip: -qpdf1/pdf2
          -O4 -qfdpr -blpdata
          fdpr -q -O3
175.vpr: -qpdf1/pdf2
         -O5 -qfdpr -blpdata
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation  
IBM System p5 575 (2200 MHz, 8 CPU)

SPECint\_rate2000 = 200  
SPECint\_rate\_base2000 = 196

SPEC license #: 11 | Tested by: IBM | Test date: Dec-2005 | Hardware Avail: Feb-2006 | Software Avail: Feb-2006

## Notes/Tuning Information (Continued)

```

176.gcc:      fdpr -q -O3
              -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata
181.mcf:      -qpdf1/pdf2
              -O4 -qalign=natural -blpdata
186.crafty:   -qpdf1/pdf2
              -O4 -qalign=natural -q64 -lhm -blpdata
197.parser:   -qpdf1/pdf2
              -O4 -qfdpr -D_ILS_MACROS -blpdata
              fdpr -q -O3
252.eon:      -qpdf1/pdf2
              -O4 -qalign=natural
253.perlbnk:  -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata -lhm
254.gap:      -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata
255.vortex:   -qpdf1/pdf2
              -O4 -qfdpr -lhm -blpdata
              fdpr -q -O3
256.bzip2:    -qpdf1/pdf2
              -O5 -qfdpr -blpdata
              fdpr -q -O3
300.twolf:    -O5 -qfdpr -blpdata
              fdpr -q -O3

```

The installed OS level is AIX 5L for POWER version 5.3 with the 5300-04 Recommended Technology Level.

SMT: Acronym for "Simultaneous Multi-Threading". A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. (Enabled by default)

DCM: Acronym for "Dual-Chip Module" (one dual-core processor chip + one L3-cache chip)

SUT: Acronym for "System Under Test"

Extended C: IBM XL C for AIX invoked as cc  
C++: IBM XL C for AIX invoked as xlc

ulimits set to unlimited.

Large page mode and memory affinity were set as follows:

```

vmo -r -o lpgg_regions=1600 -o lpgg_size=16777216
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
shutdown -rF
export MEMORY_AFFINITY=MCM

```

The following config-file entry was used to assign each benchmark process to a core:

```
submit = bindprocessor \$$ \$$SPECUSERNUM; $command
```

The "bindprocessor" AIX command binds a process to a CPU core.