CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) D975XBX motherboard(3.73 GHz, Intel(R) Pentium(R) processor Extreme Edition 965)

SPECint_rate2000 = 43.7

SPECint_rate_base2000 = 43.7

SPEC license #: 13 | Tested by: Intel(R) Corporation | Test date: Mar-2006 | Hardware Avail: Mar-2006 | Software Avail: Apr-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	168	38.6	4	170	38.2
175.vpr	4	230	28.3	4	226	28.7
176.gcc	4	85.9	59.4	4	85.9	59.4
181.mcf	4	276	30.3	4	276	30.3
186.crafty	4	141	32.9	4	141	32.9
197.parser	4	194	43.2	4	193	43.4
252.eon	4	113	53.6	4	113	53.2
253.perlbmk	4	174	48.1	4	174	47.9
254.gap	4	106	48.0	4	106	48.0
255.vortex	4	124	71.1	4	124	71.1
256.bzip2	4	179	38.8	4	180	38.8
300.twolf	4	270	51.5	4	270	51.6

Hardware

CPU:	Intel(R) Pentium(R) processor Extreme Edition 965(3.73 GHz, 1066 MHz bus)
CPU MHz:	3733
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	12k micro-ops I + 16KBD per core
Secondary Cache:	2MB(I+D) per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	1 GB (2 512MB Micron MT16HTF6464AY-667B3 DDR2 667 CL5-5-5 DIMMs)
Disk Subsystem:	Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)
Other Hardware:	ATI Radeon X1900 XTX PCI express

Software

Operating System:	Windows XP Professional SP2
Compiler:	Intel(R) C++ Compiler 9.0 for 32-bit Build 20050430Z Microsoft Visual Studio .Net 2003(for libraries) SmartHeap Library Version 7.4 from http://www.microquill.com/
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
Base tuning for C programs:   -fast +FDO shlW32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlW32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip:     -fast -Qansi_alias -Oa  +FDO
175.vpr:      -fast -Qansi_alias +FDO
176.gcc:      basepeak=yes
181.mcf:      basepeak=yes
186.crafty:   -fast -Qansi_alias -Oa +FDO
197.parser:   -fast -Qansi_alias  +FDO
252.eon:      -fast +FDO
253.perlbmk:  -fast -Qansi_alias +FDO shlW32M.lib
254.gap:      basepeak=yes
255.vortex    basepeak=yes
Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Product description located as of 03/2006
http://www.intel.com/products/motherboard/D975XBX/index.htm
The system bus runs at 1066 MHz