



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation  
IBM System p5 505Q (1650 MHz, 1 CPU)

SPECint2000 = 1371  
SPECint\_base2000 = 1311

SPEC license #: 11 | Tested by: IBM Austin | Test date: Jun-2006 | Hardware Avail: Aug-2006 | Software Avail: Aug-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	187	747	181	774	
175.vpr	1400	118	1185	118	1185	
176.gcc	1100	72.7	1513	72.7	1513	
181.mcf	1800	62.9	2864	61.6	2923	
186.crafty	1000	95.3	1049	78.9	1267	
197.parser	1800	156	1152	154	1170	
252.eon	1300	91.6	1419	90.1	1443	
253.perlbmk	1800	204	881	183	982	
254.gap	1100	94.5	1163	94.2	1167	
255.vortex	1900	89.0	2135	84.6	2246	
256.bzip2	1500	121	1236	115	1307	
300.twolf	3000	206	1454	198	1515	

### Hardware

CPU: POWER5+  
 CPU MHz: 1650  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 1 chip, 2 cores/chip (SMT off)  
 CPU(s) orderable: 4 cores  
 Parallel: No  
 Primary Cache: 64 KB I + 32 KB D on chip per core  
 Secondary Cache: 1920 KB I+D on chip per chip  
 L3 Cache: 36 MB I+D off chip per chip  
 Other Cache: None  
 Memory: 16 GB (8x2 GB)  
 Disk Subsystem: 1x73GB SCSI, 15K RPM  
 Other Hardware: None

### Software

Operating System: AIX 5L V5.3  
 Compiler: XL C/C++ Enterprise Edition Version 8.0 for AIX  
 XL Fortran Enterprise Edition Version 10.1 for AIX  
 Other Software: ESSL 4.2.0.4  
 File System: AIX/JFS2  
 System State: Multi-user

## Notes/Tuning Information

### Portability Flags:

```
176.gcc: -ma -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DAIX
253.perlbmk: -DSPEC_CPU2000_AIX
254.gap: -DSYS_IS_BSD -DSYS_STRING_H
          -DSYS_HAS_MALLOC_PROTO -DSYS_HAS_CALLOC_PROTO
300.twolf: -DHAVE_SIGNED_CHAR
```

### Base Optimization Flags:

```
C: -qpdf1/pdf2
   -O5 -blpdata -D_ILS_MACROS
C++: -qpdf1/pdf2
      -O4 -qalign=natural
```

### Peak Optimization Flags

```
164.gzip: -qpdf1/pdf2
          -O4 -qfdpr -blpdata
          fdpr -q -O3
175.vpr: basepeak=1
176.gcc: basepeak=1
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation  
IBM System p5 505Q (1650 MHz, 1 CPU)

SPECint2000 = 1371  
SPECint\_base2000 = 1311

SPEC license #: 11 | Tested by: IBM Austin | Test date: Jun-2006 | Hardware Avail: Aug-2006 | Software Avail: Aug-2006

## Notes/Tuning Information (Continued)

```

181.mcf:      -qpdf1/pdf2
              -O5 -blpdata -qalign=natural -qhot=arraypad -qfdpr -Q -qmaxmem=-1
              fdpr -q -O3
186.crafty:  -qpdf1/pdf2
              -O4 -qalign=natural -q64 -lhmu -blpdata
197.parser:  -qpdf1/pdf2
              -O4 -qfdpr -D_ILS_MACROS -blpdata
              fdpr -q -O3
252.eon:     -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural
253.perlbnk: -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata -lhmu
254.gap:     -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata
255.vortex:  -qpdf1/pdf2
              -O4 -qfdpr -lhmu -blpdata
              fdpr -q -O3
256.bzip2:   -qpdf1/pdf2
              -O5 -qfdpr -blpdata
              fdpr -q -O3
300.twolf:   -O5 -qfdpr -blpdata
              fdpr -q -O3

```

The installed OS level is AIX 5L for POWER Version 5.3 with the 5300-05 Recommended Technology Level. The installed C/C++ compiler is XL C/C++ Enterprise Edition Version 8.0 for AIX with the March 2006 PTF. The installed Fortran copiler is XL Fortran Enterprise Edition Version 10.1 with the May 2006 AIX PTF.

SMT: Acronym for "Simultaneous Multi-Threading". A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. (Enabled by default)

SUT: Acronym for "System Under Test"

PTF: IBM identifier for "Program Fix Level"

```

Extended C:   IBM XL C for AIX invoked as cc
ANSI C89:     IBM XL C for AIX invoked as xlc
C++:         IBM XL C for AIX invoked as xlc

```

ulimits set to unlimited.

Large page mode and memory affinity were set as follows:

```

vmo -r -o lpgg_regions=128 -o lpgg_size=16777216
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
bosboot -aD
shutdown -rF
export MEMORY_AFFINITY=MCM

```

The following config-file entry was used to assign each benchmark process to a core:

```
submit = bindprocessor \${$} \${SPECUSERNUM}; $command
```

The "bindprocessor" AIX command binds a process to a CPU core.

Three cores were deconfigured and SMT disabled using the AIX commands

```

smtctl -m off -w boot
bosboot -aD
shutdown -rF
drmgr -r -c cpu
drmgr -r -c cpu
drmgr -r -c cpu

```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 505Q (1650 MHz, 1 CPU)

SPECint2000 = 1371

SPECint\_base2000 = 1311

SPEC license #: 11 | Tested by: IBM Austin | Test date: Jun-2006 | Hardware Avail: Aug-2006 | Software Avail: Aug-2006

## Notes/Tuning Information (Continued)