



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R520 (3.0 GHz Intel Xeon Processor 5050)

SPECint_rate2000 = 61.9

SPECint_rate_base2000 = 61.8

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: May-2006 | Hardware Avail: Nov-2006 | Software Avail: Nov-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	216	60.1	8	216	60.1
175.vpr	8	343	37.9	8	336	38.6
176.gcc	8	116	87.6	8	116	87.6
181.mcf	8	655	25.5	8	655	25.5
186.crafty	8	178	52.1	8	178	52.1
197.parser	8	260	64.2	8	259	64.6
252.eon	8	138	87.1	8	139	86.9
253.perlbnk	8	221	75.8	8	221	75.6
254.gap	8	156	65.4	8	156	65.4
255.vortex	8	169	105	8	169	105
256.bzip2	8	278	50.0	8	278	50.1
300.twolf	8	343	81.1	8	343	81.1

Hardware

CPU: Intel Xeon Processor 5050 (3.0 GHz, 2x2MB L2, 667MHz system bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K(I) micro-ops + 16KB(D) on chip, per core
Secondary Cache: 2048KB(I+D) on chip, per core
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 2048MB ECC FB-DIMM 533
Disk Subsystem: 1 x 73GB 10000RPM SAS HDD
Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790), Service Pack 1
Compiler: Intel C++ Compiler 9.0 Build 20051130Z for IA32
Microsoft Visual Studio .Net 2003 (7.1.3091, for libraries)
shlw32M.lib is SmartHeap Library Version 7.4 from http://www.microquill.com/
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: basepeak=yes
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: basepeak=yes
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
256.bzip2: -fast -Oa -Qunroll1 +FDO
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated
Acer Altos R520 (3.0 GHz Intel Xeon Processor 5050)

SPECint_rate2000 = 61.9
SPECint_rate_base2000 = 61.8

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: May-2006 | Hardware Avail: Nov-2006 | Software Avail: Nov-2005

Notes/Tuning Information (Continued)

300.twolf: -fast +FDO shlw32M.lib
Enable hardware prefetching and adjacent cache line prefetch BIOS setting

This result was measured on the Acer Alto R720.
The Altos R520 and Altos R720 are electronically equivalent.