CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

Motherboard H8DM8-2, AMD Opteron(TM) 2220 SE

SPECint_rate2000 = 86.6

SPECint_rate_base2000 = 76.2

SPEC license #01176 | Tested by: Supermicro | Test date: Oct-2006 | Hardware Avail: Sep-2006 | Software Avail: Aug-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	82.2	79.0	4	81.9	79.3
175.vpr	4	112	57.8	4	106	61.2
176.gcc	4	59.5	85.8	4	59.0	86.5
181.mcf	4	291	28.7	4	173	48.3
186.crafty	4	40.2	115	4	39.1	119
197.parser	4	143	58.3	4	112	74.2
252.eon	4	46.4	130	4	38.6	156
253.perlbmk	4	98.6	84.7	4	85.3	98.0
254.gap	4	63.1	80.9	4	63.1	80.9
255.vortex	4	70.4	125	4	66.0	134
256.bzip2	4	99.9	69.6	4	99.9	69.6
300.twolf	4	212	65.7	4	161	86.6

Hardware

CPU:	AMD Opteron(TM) 2220 SE processor
CPU MHz:	2800
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	64KBI + 64KBD on chip per core
Secondary Cache:	1024KB (I+D) on chip per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8x2048MB, DDR2-667 Dual Rank CL4 ECC Reg
Disk Subsystem:	SATA, 400 GB
Other Hardware:	None

Software

Operating System:	SuSE Linux Enterprise Server 9 for AMD64, SP3
Compiler:	PathScale EKOPath(TM) Compiler Suite, Release 2.3
File System:	Linux/reiserfs
System State:	Multi-user, run level 3

Notes/Tuning Information

```
Tested by Supermicro Computer, Inc.

 +FDO: PASS1= -fb_create fbdata  PASS2= -fb_opt fbdata

 Baseline optimization flags:
   C programs:       -Ofast +FDO
   C++ programs:     -Ofast +FDO

 Portability Flags:
   186.crafty:  -DLINUX_i386
   252.eon:     -DHAS_ERRLIST -DSPEC_CPU2000_LP64
   253.perlbmk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
                -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
   254.gap:     -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
                -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
   255.vortex:  -DSPEC_CPU2000_LP64

 Peak Tuning:
 164.gzip:    -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
 175.vpr:     -O3 -ipa -m32 +FDO
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
176.gcc:     -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO
181.mcf:     -O3 -ipa -IPA:field_reorder=on -m32 +FDO
186.crafty:  -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
197.parser:  -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon:     -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
             -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
             -LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbmk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
             -fno-math-errno -IPA:plimit=10000 +FDO
255.vortex:  -Ofast -OPT:goto=off -CG:p2align=on
             -GRA:optimize_boundary=on -IPA:min_hotness=120 +FDO
256.bzip2:   basepeak = true
300.twolf:   -O2 -CG:gcm=off:p2align_freq=100000
             -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
             -WOPT:mem_opnds=on -m32 +FDO
Taskset utility used to bind CPU(s) to processes
Memory populated at location DIMMA 1A, DIMMA 1B, DIMMA 2A, DIMMA 2B for CPU1 and DIMMB 1A, DIMMB 1B, DIMMB 2A, DIMMB 2B for CPU2
Tested systems can be used with SC811S-520 case,
To ensure system stability, a 550W (minimum) ATX power supply [ 4-pin (+12V), 8-pin (+12V) and 24-pin are required]
Product description located as of H8DM8: http://www.supermicro.com/Aplus/motherboard/Opteron2000/MCP55/H8DM8-2.cfm
```