



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL460c (2.66GHz, Intel Xeon processor 5150)

SPECint2000 = 2696
SPECint_base2000 = 2696

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Oct-2006 Hardware Avail: Jun-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	88.4	1584	88.4	1584	
175.vpr	1400	66.8	2097	66.8	2097	
176.gcc	1100	39.8	2767	39.8	2767	
181.mcf	1800	45.9	3925	45.9	3925	
186.crafty	1000	32.3	3092	32.3	3092	
197.parser	1800	93.8	1919	93.8	1919	
252.eon	1300	36.2	3589	36.2	3589	
253.perlbmk	1800	56.3	3195	56.3	3195	
254.gap	1100	47.7	2308	47.7	2308	
255.vortex	1900	45.7	4158	45.7	4158	
256.bzip2	1500	69.7	2152	69.7	2152	
300.twolf	3000	103	2914	103	2914	

Hardware

CPU: Intel Xeon processor 5150 (2.66 GHz, 4 MB L2 shared, 1333 MHz bus)
CPU MHz: 2660
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4 MB I+D on chip per chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8 GB (8x1 GB PC2-5300F)
Disk Subsystem: 2x72 GB 10 K SAS
Other Hardware:

Software

Operating System: RedHat Enterprise Linux 4.0 Advanced Server for AMD64/EM64T, Update 3 Kernel 2.6.9-34.EL
Compiler: Intel C++ Compiler for EM64T-based applications, (Version 9.1 Build 20060323)
Intel Fortran Compiler for EM64T-based applications, (Version 9.1 Build 20060323)
File System: ext2
System State: Multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1=-prof_gen PASS2=-prof_use
Base tuning for C programs: -fast -auto_ilp32 +FDO ONESTEP=yes
Base tuning for C++ programs: -fast
Portability flags:
  -DSPEC_CPU2000_LP64 applied to all benchmarks
186.crafty: -DLINUX_i386
252.eon: -DHAS_ERRLIST
253.perlbmk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
254.gap: -DSYS_IS_USG
Peak tuning:
  basepeak=1 for all modules
BIOS Configuration Notes
  Power Regulator set to Static High Performance Mode
Other Configuration Notes
  Single processor kernel used
```