



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itautec

Servidor Itautec MX221 (Intel Xeon 5030 processor, 2.66GHz)

SPECint_rate2000 = 30.5

SPECint_rate_base2000 = 30.5

SPEC license #: 9001 | Tested by: Itautec | Test date: Nov-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	4	243	26.8	4	243	26.8
175.vpr	4	334	19.4	4	334	19.4
176.gcc	4	122	41.8	4	122	41.8
181.mcf	4	472	17.7	4	472	17.7
186.crafty	4	206	22.5	4	206	22.5
197.parser	4	275	30.4	4	275	30.4
252.eon	4	135	44.8	4	135	44.8
253.perlbnk	4	255	32.8	4	255	32.8
254.gap	4	150	34.0	4	150	34.0
255.vortex	4	174	50.8	4	174	50.8
256.bzip2	4	274	25.4	4	274	25.4
300.twolf	4	363	38.3	4	363	38.3

Hardware

CPU: Intel Xeon 5030 processor (2.66GHz, 2x2MB L2, 667MHz system bus)
 CPU MHz: 2667
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip (Hyper-Threading Technology enabled)
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 2MB (I+D) on chip, per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8GB (8x1GB DDR2-RAM PC2-4200 FB-DIMM CL4 ECC)
 Disk Subsystem: 1 x 120GB Serial ATA 7200 RPM
 Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
 Compiler: Intel C++ Compiler 9.1
 Build 20060519Z (for 32-bit applications),
 Microsoft Visual Studio .NET 7.0.9466 (for libraries),
 MicroQuill SmartHeap for SMP Library 8.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

for C programs: -fast +FDO sh1SMPMt.lib
 for C++ programs: -fast -Qcxx_features +FDO

EXTRA LIBRARIES

MicroQuill SmartHeap for SMP Library 8.0 available from
<http://www.microquill.com/>