



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Bull

NovaScale B280 (Intel Xeon processor 5130, 2.0 GHz)

SPECint2000 = 2103

SPECint_base2000 = 2101

SPEC license #: 20 | Tested by: Bull | Test date: Dec-2006 | Hardware Avail: Jan-2007 | Software Avail: Dec-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	112	1246	113	1240	
175.vpr	1400	90.4	1548	88.7	1578	
176.gcc	1100	46.2	2380	46.2	2380	
181.mcf	1800	55.4	3247	55.4	3247	
186.crafty	1000	54.8	1825	54.8	1825	
197.parser	1800	108	1663	108	1667	
252.eon	1300	50.0	2601	50.0	2601	
253.perlbnk	1800	75.0	2401	75.0	2401	
254.gap	1100	53.3	2065	53.4	2061	
255.vortex	1900	54.2	3505	54.2	3505	
256.bzip2	1500	96.9	1548	96.9	1548	
300.twolf	3000	128	2336	128	2336	

Hardware

CPU: Intel Xeon Processor 5130 (2.0 GHz, 4MB L2, 1333MHz bus)
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip
CPU(s) orderable: 1 to 2 chips
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 4096KB(I+D) on chip per chip (shared by 2 cores)
L3 Cache: N/A
Other Cache: N/A
Memory: 8GB (1GB DIMMx8, FB-DIMM PC2-5300F ECC CL5)
Disk Subsystem: 1x73GB SAS 10000 rpm
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32 bits), Service Pack 1
Compiler: Intel(R) C++ Compiler for 32-bit app., Version 9.1, - Build 20061103Z Package ID: W_CC_C_9.1.033
Microsoft Visual Studio .NET 2003 (for libraries)
MicroQuill SmartHeap Library 8.0 (shlW32M.lib)
File System: NTFS
System State: Default

Notes/Tuning Information

Portability flags:

```
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
```

Feedback optimization:

```
+FDO: PASS1= -Qprof_gen PASS2= -Qprof_use
```

Baseline Tuning Flags:

```
for C programs:
-fast +FDO ONESTEP=yes shlW32M.lib
for C++ program 252.eon:
-fast -Qcxx_features +FDO ONESTEP=yes
```

Peak Tuning Flags:

```
164.gzip: -fast +FDO ONESTEP=yes
175.vpr: -fast +FDO ONESTEP=yes
176.gcc: basepeak=yes
181.mcf: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Bull

NovaScale B280 (Intel Xeon processor 5130, 2.0 GHz)

SPECint2000 = 2103

SPECint_base2000 = 2101

SPEC license #: 20 | Tested by: Bull | Test date: Dec-2006 | Hardware Avail: Jan-2007 | Software Avail: Dec-2006

Notes/Tuning Information (Continued)

186.crafty: basepeak=yes
197.parser: -fast +FDO ONESTEP=yes
252.eon: basepeak=yes
253.perlbnk: basepeak=yes
254.gap: -fast +FDO ONESTEP=yes
255.vortex: basepeak=yes
256.bzip2: basepeak=yes
300.twolf: basepeak=yes

Other Configuration Notes

/NUMPROC=1 flag was added to boot.ini to invoke uniprocessor environment

For information about Bull please see:
<http://www.bull.com>