SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Ultra Enterprise 2

SPECint®2006 = --

SPECint_base2006 = 1.00

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Mar-2006
Hardware Availability: Apr-1997
Software Availability: Oct-2005

Hardware

CPU Name:	UltraSPARC II
CPU Characteristics:	
CPU MHz:	296
FPU:	Integrated
CPU(s) enabled:	2 cores, 2 chips, 1 core/chip
CPU(s) orderable:	1-2 chips
Primary Cache:	16 KB I + 16 KB D on chip per chip
Secondary Cache:	2 MB I+D off chip per chip
L3 Cache:	None
Other Cache:	None
Memory:	2 GB
Disk Subsystem:	2x36GB 10K RPM SCSI (1 sys disk, 1 for SPEC)
Other Hardware:	None

Software

Operating System:	Solaris 10 3/05
Compiler:	Sun Studio 11
Auto Parallel:	No
File System:	ufs
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	Not Applicable
Other Software:	None

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Ultra Enterprise 2

SPECint2006 = --

SPECint_base2006 = 1.00

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Mar-2006
Hardware Availability: Apr-1997
Software Availability: Oct-2005

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	9922	0.985	9734	1.00	**9766**	**1.00**						
401.bzip2	9656	0.999	**9644**	**1.00**	9644	1.00						
403.gcc	8059	0.999	**8058**	**0.999**	8023	1.00						
429.mcf	9358	0.975	**9306**	**0.980**	9303	0.980						
445.gobmk	10257	1.02	**10283**	**1.02**	10449	1.00						
456.hmmer	**9408**	**0.992**	9409	0.992	9338	0.999						
458.sjeng	11780	1.03	**11787**	**1.03**	12419	0.974						
462.libquantum	20708	1.00	20702	1.00	**20704**	**1.00**						
464.h264ref	**22015**	**1.01**	21925	1.01	22334	0.991						
471.omnetpp	6012	1.04	**6087**	**1.03**	6166	1.01						
473.astar	7032	0.998	7006	1.00	**7017**	**1.00**						
483.xalancbmk	6818	1.01	**6869**	**1.00**	6904	0.999						

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
Stack limit set to 131072
```

Platform Notes

```
Although two CPUs were enabled during testing,
the SPEC CPU2006 benchmarks used only 1 CPU.
```

Base Compiler Invocation

C benchmarks:
`cc`

C++ benchmarks:
`CC`

Base Portability Flags

400.perlbench: `-DSPEC_CPU_SOLARIS_SPARC`
403.gcc: `-DSPEC_CPU_SOLARIS`
462.libquantum: `-DSPEC_CPU_SOLARIS`
483.xalancbmk: `-DSPEC_CPU_SOLARIS`

Base Optimization Flags

C benchmarks:
```
-g -fast -xpagesize=4M
```

C++ benchmarks:
```
-g0 -library=stlport4 -fast -xpagesize=4M
```

Base Other Flags

C benchmarks:
```
-V
```

C++ benchmarks:
```
-verbose=version
```

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/sun-studio.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/sun-studio.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v89.
Report generated on Tue Jul 22 09:58:02 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 24 August 2006.