



SPEC[®] CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems Sun Fire X4200

SPECint[®]_rate2006 = 42.8

SPECint_rate_base2006 = 37.8

CPU2006 license: 6


Test sponsor: Sun Microsystems

Tested by: Sun Microsystems

Test date: Apr-2006

Hardware Availability: Dec-2005

Software Availability: Jul-2006



Hardware

CPU Name: AMD Opteron 285
 CPU Characteristics:
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1-2 chips
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8x2 GB, PC3200 CL3 DDR ECC Reg)
 Disk Subsystem: SAS,36GB,10K RPM
 Other Hardware: None

Software

Operating System: Solaris 10 1/06
 Compiler: Sun Studio 11 with patch 120759-06
 Auto Parallel: No
 File System: ufs
 System State: Default
 Base Pointers: 64-bit
 Peak Pointers: 32/64-bit
 Other Software: None



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4200

SPECint_rate2006 = 42.8
SPECint_rate_base2006 = 37.8

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Apr-2006
Hardware Availability: Dec-2005
Software Availability: Jul-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	821	47.6	<u>821</u>	<u>47.6</u>	826	47.3	4	<u>814</u>	<u>48.0</u>	820	47.6	813	48.1
401.bzip2	4	1196	32.3	1201	32.1	<u>1200</u>	<u>32.2</u>	4	1151	33.5	<u>1136</u>	<u>34.0</u>	1130	34.2
403.gcc	4	1210	26.6	<u>1207</u>	<u>26.7</u>	1207	26.7	4	993	32.4	<u>994</u>	<u>32.4</u>	995	32.4
429.mcf	4	<u>1473</u>	<u>24.8</u>	1473	24.8	1472	24.8	4	900	40.5	900	40.6	<u>900</u>	<u>40.6</u>
445.gobmk	4	819	51.2	819	51.2	<u>819</u>	<u>51.2</u>	4	710	59.1	<u>710</u>	<u>59.1</u>	710	59.1
456.hammer	4	703	53.1	<u>704</u>	<u>53.0</u>	707	52.8	4	<u>574</u>	<u>65.0</u>	576	64.8	574	65.0
458.sjeng	4	945	51.2	<u>944</u>	<u>51.3</u>	944	51.3	4	890	54.4	<u>890</u>	<u>54.4</u>	892	54.2
462.libquantum	4	<u>2214</u>	<u>37.4</u>	2214	37.4	2214	37.4	4	2126	39.0	<u>2126</u>	<u>39.0</u>	2127	39.0
464.h264ref	4	<u>1511</u>	<u>58.6</u>	1512	58.5	1511	58.6	4	1423	62.2	<u>1426</u>	<u>62.1</u>	1427	62.0
471.omnetpp	4	963	26.0	959	26.1	<u>960</u>	<u>26.0</u>	4	899	27.8	<u>898</u>	<u>27.8</u>	898	27.9
473.astar	4	950	29.6	948	29.6	<u>948</u>	<u>29.6</u>	4	<u>899</u>	<u>31.2</u>	900	31.2	899	31.2
483.xalancbmk	4	772	35.7	<u>772</u>	<u>35.8</u>	769	35.9	4	<u>696</u>	<u>39.6</u>	697	39.6	696	39.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Processes were bound to cores using "submit" and "pbind".

```
ulimit -s 131072 (shell): increases stack
```

```
/etc/system parameters
tune_t_fsflushr=1
```

Controls how many seconds elapse between runs of the page flush daemon, fsflush.

```
autoup=900
```

Causes pages older than the listed number of seconds to be written by fsflush.

Platform Notes

Default BIOS settings were used.



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4200

SPECint_rate2006 = 42.8

SPECint_rate_base2006 = 37.8

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Apr-2006
Hardware Availability: Dec-2005
Software Availability: Jul-2006

Base Compiler Invocation

C benchmarks:
cc

C++ benchmarks:
CC

Base Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_SOLARIS_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64 -DSPEC_CPU_SOLARIS
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_SOLARIS
464.h264ref: -DSPEC_CPU_LP64
471.omnetpp: -DSPEC_CPU_LP64
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LP64 -DSPEC_CPU_SOLARIS

Base Optimization Flags

C benchmarks:
-fast -xipo=2 -xarch=amd64a

C++ benchmarks:
-fast -xipo=2 -xarch=amd64a -library=stlport4

Base Other Flags

C benchmarks:
-V

C++ benchmarks:
-verbose=version

Peak Compiler Invocation

C benchmarks:
cc

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4200

SPECint_rate2006 = 42.8
SPECint_rate_base2006 = 37.8

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Apr-2006
Hardware Availability: Dec-2005
Software Availability: Jul-2006

Peak Compiler Invocation (Continued)

C++ benchmarks:
CC

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_SOLARIS_X64
403.gcc: -DSPEC_CPU_SOLARIS
462.libquantum: -DSPEC_CPU_SOLARIS
483.xalancbmk: -DSPEC_CPU_SOLARIS

Peak Optimization Flags

C benchmarks:

400.perlbench: -fast -xarch=amd64a
401.bzip2: ONESTEP -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=2m
-xcrossfile -xarch=sse2a -M /usr/lib/ld/map.bssalign
403.gcc: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xbuiltin=%none
429.mcf: -fast -xpagesize=2m -M /usr/lib/ld/map.bssalign
445.gobmk: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xarch=amd64a
-xrestrict -xalias_level=strong -xdepend
456.hmmer: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xarch=amd64a
458.sjeng: -fast -xarch=amd64a -xipo=2 -xprefetch=auto
-xprefetch_level=3 -xpagesize=2m
462.libquantum: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xarch=amd64a
-xipo=2 -xunroll=8
464.h264ref: -fast -xarch=amd64a -xipo=2 -xvector -xunroll=8
-xalias_level=strong -xrestrict

C++ benchmarks:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4200

SPECint_rate2006 = 42.8
SPECint_rate_base2006 = 37.8

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Apr-2006
Hardware Availability: Dec-2005
Software Availability: Jul-2006

Peak Optimization Flags (Continued)

471.omnetpp: -fast -xarch=amd64a -xipo=2 -xprefetch_level=3
-xpagesize=2m -Qoption ube -fsimple=3 -library=stlport4

473.astar: -fast -xarch=amd64a -xipo=2 -xprefetch_level=3
-xpagesize=2m -library=stlport4

483.xalancbmk: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xarch=sse2a -library=stlport4

Peak Other Flags

C benchmarks:
-V

C++ benchmarks:
-verbose=version

The flags file that was used to format this result can be browsed at
<http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio-Opteron.20090715.02.html>

You can also download the XML flags source by saving the following link:
<http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio-Opteron.20090715.02.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v91.
Report generated on Tue Jul 22 10:01:01 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 24 August 2006.