SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation
IBM System x3800

SPECint®2006 = Not Run

SPECint_base2006 = 10.4

CPU2006 license: 11
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Dec-2006
Hardware Availability: Oct-2006
Software Availability: Aug-2006



Hardware

CPU Name:	Intel Xeon 7140N
CPU Characteristics:	667 MHz bus
CPU MHz:	3333
FPU:	Integrated
CPU(s) enabled:	8 cores, 4 chips, 2 cores/chip, 2 threads/core
CPU(s) orderable:	1,2,4 chips
Primary Cache:	12 K micro-ops I + 16 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core
L3 Cache:	16 MB I+D on chip per chip
Other Cache:	None
Memory:	32 GB (16 x 2048 MB ECC PC2-3200)
Disk Subsystem:	73 GB SAS, 10k RPM
Other Hardware:	None

Software

Operating System:	Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
Compiler:	Intel C++ Compiler for IA32 version 9.1 Build no 20060816 Microsoft Visual Studio .Net 2003 (for libraries)
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	Not Applicable
Other Software:	Smart Heap Library, Version 8

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation
IBM System x3800

SPECint2006 = Not Run

SPECint_base2006 = 10.4

CPU2006 license: 11
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Dec-2006
Hardware Availability: Oct-2006
Software Availability: Aug-2006

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	785	12.4	**785**	**12.4**	785	12.4						
401.bzip2	1060	9.10	**1060**	**9.10**	1060	9.10						
403.gcc	993	8.11	**993**	**8.11**	987	8.16						
429.mcf	**675**	**13.5**	675	13.5	675	13.5						
445.gobmk	1116	9.40	1116	9.40	**1116**	**9.40**						
456.hmmer	1285	7.26	**1285**	**7.26**	1285	7.26						
458.sjeng	1543	7.84	**1543**	**7.84**	1543	7.84						
462.libquantum	**1768**	**11.7**	1768	11.7	1768	11.7						
464.h264ref	**1161**	**19.1**	1161	19.1	1161	19.1						
471.omnetpp	709	8.81	**709**	**8.81**	709	8.81						
473.astar	826	8.50	825	8.50	**826**	**8.50**						
483.xalancbmk	476	14.5	**476**	**14.5**	476	14.5						

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
Bios Settings
  Hardware Prefetch enabled
  Memory Array set to High-Performance Memory Array
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Base Optimization Flags

C benchmarks:

```
-fast /F512000000 shlw32m.lib            -link /FORCE:MULTIPLE
```

Continued on next page

Base Optimization Flags (Continued)

C++ benchmarks:
```
-fast -Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic91-flags.20090715.01.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic91-flags.20090715.01.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:13:07 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 25 January 2007.