



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp[®]2006 = 15.4

CELSIUS V840, AMD Opteron 2218

SPECfp_base2006 = 12.5

CPU2006 license: 22


Test date: Jan-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Nov-2006

Tested by: Fujitsu Siemens Computers

Software Availability: Aug-2006



Hardware

CPU Name: AMD Opteron 2218
 CPU Characteristics: Dual Core, 2.6 GHz, 2 MB L2-cache
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core

Continued on next page

Software

Operating System: SLES 10 for AMD64/EM64T
 Compiler: QLogic Pathscale Compiler Suite 2.5
 Auto Parallel: Yes
 File System: ext3
 System State: Multi-User SuSE Run Level 3
 Base Pointers: 64-bit
 Peak Pointers: 64-bit
 Other Software: --



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp2006 = **15.4**

CELSIUS V840, AMD Opteron 2218

SPECfp_base2006 = **12.5**

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Jan-2007

Hardware Availability: Nov-2006

Software Availability: Aug-2006

L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8x2GB DDR2-667 CL5 dual rank ECC DIMMs registered)
 Disk Subsystem: SATA II, 80 GB
 Other Hardware: None

Results Table

| Benchmark | Base | | | | | | Peak | | | | | |
|---------------|---------|-------|-------------|-------------|-------------|-------------|-------------|-------------|------------|-------------|-------------|-------------|
| | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 776 | 17.5 | 777 | 17.5 | 777 | 17.5 | 246 | 55.3 | 243 | 56.0 | 244 | 55.6 |
| 416.gamess | 1511 | 13.0 | 1511 | 13.0 | 1511 | 13.0 | 1458 | 13.4 | 1462 | 13.4 | 1457 | 13.4 |
| 433.milc | 799 | 11.5 | 786 | 11.7 | 790 | 11.6 | 771 | 11.9 | 768 | 12.0 | 780 | 11.8 |
| 434.zeusmp | 820 | 11.1 | 819 | 11.1 | 818 | 11.1 | 820 | 11.1 | 819 | 11.1 | 818 | 11.1 |
| 435.gromacs | 622 | 11.5 | 622 | 11.5 | 622 | 11.5 | 546 | 13.1 | 548 | 13.0 | 545 | 13.1 |
| 436.cactusADM | 999 | 12.0 | 994 | 12.0 | 997 | 12.0 | 364 | 32.9 | 354 | 33.8 | 353 | 33.8 |
| 437.leslie3d | 819 | 11.5 | 821 | 11.4 | 823 | 11.4 | 819 | 11.5 | 821 | 11.4 | 823 | 11.4 |
| 444.namd | 705 | 11.4 | 706 | 11.4 | 705 | 11.4 | 689 | 11.6 | 689 | 11.6 | 689 | 11.6 |
| 447.dealII | 616 | 18.6 | 617 | 18.5 | 616 | 18.6 | 613 | 18.7 | 614 | 18.6 | 613 | 18.7 |
| 450.soplex | 844 | 9.89 | 846 | 9.85 | 850 | 9.81 | 788 | 10.6 | 785 | 10.6 | 783 | 10.6 |
| 453.povray | 371 | 14.4 | 369 | 14.4 | 370 | 14.4 | 316 | 16.8 | 314 | 16.9 | 317 | 16.8 |
| 454.calculix | 1188 | 6.95 | 1190 | 6.93 | 1188 | 6.94 | 1188 | 6.95 | 1190 | 6.93 | 1188 | 6.94 |
| 459.GemsFDTD | 957 | 11.1 | 959 | 11.1 | 962 | 11.0 | 466 | 22.8 | 467 | 22.7 | 467 | 22.7 |
| 465.tonto | 731 | 13.5 | 740 | 13.3 | 731 | 13.5 | 731 | 13.5 | 740 | 13.3 | 731 | 13.5 |
| 470.ibm | 860 | 16.0 | 933 | 14.7 | 950 | 14.5 | 932 | 14.7 | 938 | 14.7 | 947 | 14.5 |
| 481.wrf | 770 | 14.5 | 769 | 14.5 | 770 | 14.5 | 627 | 17.8 | 631 | 17.7 | 634 | 17.6 |
| 482.sphinx3 | 1372 | 14.2 | 1372 | 14.2 | 1767 | 11.0 | 1364 | 14.3 | 1359 | 14.3 | 1362 | 14.3 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

powersave -f is applied to set CPU to maximum frequency prior to run
stacksize is set to unlimited prior to run

General Notes

Binaries are generated on an Opteron-based system running Suse 9.3.

BIOS default settings with
Node memory interleave disabled, SRAT enabled

For information about Fujitsu Siemens Computers in your country please see:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp2006 = 15.4

CELSIUS V840, AMD Opteron 2218

SPECfp_base2006 = 12.5

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Jan-2007

Hardware Availability: Nov-2006

Software Availability: Aug-2006

General Notes (Continued)

<http://www.fujitsu-siemens.com/countries>

Base Compiler Invocation

C benchmarks:
pathcc

C++ benchmarks:
pathCC

Fortran benchmarks:
pathf95

Benchmarks using both Fortran and C:
pathcc pathf95

Base Portability Flags

```

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64
436.cactusADM: -DSPEC_CPU_LP64 -fno-second-underscore
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.deallI: -DSPEC_CPU_LP64 -DSPEC_CPU_TABLE_WORKAROUND
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX -fno-second-underscore
482.sphinx3: -DSPEC_CPU_LP64

```

Base Optimization Flags

C benchmarks:
-Ofast

C++ benchmarks:
-Ofast

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp2006 = 15.4

CELSIUS V840, AMD Opteron 2218

SPECfp_base2006 = 12.5

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Jan-2007

Hardware Availability: Nov-2006

Software Availability: Aug-2006

Base Optimization Flags (Continued)

Fortran benchmarks:
-Ofast

Benchmarks using both Fortran and C:
-Ofast

Peak Compiler Invocation

C benchmarks:
pathcc

C++ benchmarks:
pathCC

Fortran benchmarks:
pathf95

Benchmarks using both Fortran and C:
pathcc pathf95

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast

470.lbm: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2)

482.sphinx3: -Ofast -apo

C++ benchmarks:

444.namd: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast

447.dealII: -Ofast -fno-exceptions

450.soplex: -O3 -OPT:IEEE_arith=3 -CG:load_exe=0 -CG:movnti=1
-LNO:minvariant=off -fno-exceptions

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp2006 = 15.4

CELSIUS V840, AMD Opteron 2218

SPECfp_base2006 = 12.5

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Jan-2007

Hardware Availability: Nov-2006

Software Availability: Aug-2006

Peak Optimization Flags (Continued)

453.povray: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
-fno-fast-math

Fortran benchmarks:

410.bwaves: -Ofast -apo

416.gamess: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: Same as 410.bwaves

465.tonto: basepeak = yes

Benchmarks using both Fortran and C:

435.gromacs: -O3 -OPT:rsqrt=2 -OPT:ro=3

436.cactusADM: -Ofast -apo

454.calculix: basepeak = yes

481.wrf: Same as 436.cactusADM

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090715.14.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090715.14.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 10:22:27 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 20 February 2007.