SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

Servidor Itautec MX201 (Intel Xeon E5310)

SPECint®_rate2006 = 52.1

SPECint_rate_base2006 = 52.1

CPU2006 license: 9001
Test sponsor: Itautec
Tested by: Itautec

Test date: Feb-2007
Hardware Availability: Feb-2007
Software Availability: May-2006



Hardware

CPU Name:	Intel Xeon E5310
CPU Characteristics:	1066MHz system bus
CPU MHz:	1600
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1-2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	8 GB (8x1GB DDR2-RAM PC2-5300F CAS 5-5-5)
Disk Subsystem:	146 GB SCSI, 10000RPM
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler:	Intel C++ Compiler for IA32 version 9.1 Package ID W_CC_C_9.1.025 Build no 20060519Z Microsoft Visual Studio .NET 2003 7.1.3088 (for libraries)
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	Microquill SmartHeap Library v.8.0 for SMP

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

Servidor Itautec MX201 (Intel Xeon E5310)

SPECint_rate2006 = 52.1

SPECint_rate_base2006 = 52.1

CPU2006 license: 9001
Test sponsor: Itautec
Tested by: Itautec

Test date: Feb-2007
Hardware Availability: Feb-2007
Software Availability: May-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	907	86.2	926	84.4	**916**	**85.3**	8	907	86.2	926	84.4	**916**	**85.3**
401.bzip2	8	1496	51.6	1486	52.0	**1491**	**51.8**	8	1496	51.6	1486	52.0	**1491**	**51.8**
403.gcc	8	2852	22.6	**2871**	**22.4**	2871	22.4	8	2852	22.6	**2871**	**22.4**	2871	22.4
429.mcf	8	**1670**	**43.7**	1670	43.7	1672	43.6	8	**1670**	**43.7**	1670	43.7	1672	43.6
445.gobmk	8	1023	82.0	1023	82.0	**1023**	**82.0**	8	1023	82.0	1023	82.0	**1023**	**82.0**
456.hmmer	8	**1395**	**53.5**	1396	53.5	1395	53.5	8	**1395**	**53.5**	1396	53.5	1395	53.5
458.sjeng	8	1249	77.5	**1250**	**77.5**	1250	77.5	8	1249	77.5	**1250**	**77.5**	1250	77.5
462.libquantum	8	7042	23.5	7034	23.6	**7039**	**23.5**	8	7042	23.5	7034	23.6	**7039**	**23.5**
464.h264ref	8	1356	131	1358	130	**1356**	**131**	8	1356	131	1358	130	**1356**	**131**
471.omnetpp	8	1623	30.8	**1625**	**30.8**	1625	30.8	8	1623	30.8	**1625**	**30.8**	1625	30.8
473.astar	8	1287	43.6	1291	43.5	**1290**	**43.5**	8	1287	43.6	1291	43.5	**1290**	**43.5**
483.xalancbmk	8	834	66.2	**835**	**66.1**	835	66.1	8	834	66.2	**835**	**66.1**	835	66.1

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
This result was measured on the Servidor Itautec MX221.
The Servidor Itautec MX221 and the Servidor Itautec MX201
are electronically equivalent.
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Base Optimization Flags

C benchmarks:

```
-fast /F512000000 shlSMPMt.lib            -link /FORCE:MULTIPLE
```

Continued on next page

Base Optimization Flags (Continued)

C++ benchmarks:
-fast -Qcxx_features /F512000000 shlSMPMt.lib
-link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Optimization Flags

C benchmarks:

400.perlbench: basepeak = yes

401.bzip2: basepeak = yes

403.gcc: basepeak = yes

429.mcf: basepeak = yes

445.gobmk: basepeak = yes

456.hmmer: basepeak = yes

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: basepeak = yes

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Itautec-ic91-flags.20090714.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Itautec-ic91-flags.20090714.xml

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

Servidor Itautec MX201 (Intel Xeon E5310)

SPECint_rate2006 = 52.1

SPECint_rate_base2006 = 52.1

CPU2006 license: 9001
Test sponsor: Itautec
Tested by: Itautec

Test date: Feb-2007
Hardware Availability: Feb-2007
Software Availability: May-2006

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:30:11 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 7 March 2007.