SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 2900 (Intel Xeon processor 5160, 3.00GHz)

SPECint®_rate2006 = Not Run

SPECint_rate_base2006 = 53.7

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Mar-2007
Hardware Availability: Jul-2006
Software Availability: Nov-2006



Hardware

CPU Name:	Intel Xeon 5160
CPU Characteristics:	1333 MHz Bus Speed
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per chip
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8 x 2 GB 667MHz CL5 DDR2 FB-DIMM SDRAM)
Disk Subsystem:	1 x 73GB SAS 15k RPM
Other Hardware:	None

Software

Operating System:	Microsoft Windows Server 2003 Enterprise x64 Edition + SP1(64-bit)
Compiler:	Intel C++ Compiler 9.1 for IA32 (20061103Z) Microsoft Visual Studio 2005
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	Not Applicable
Other Software:	MicroQuill SmartHeap Library 8.0

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 2900 (Intel Xeon processor 5160, 3.00GHz)

SPECint_rate2006 = Not Run

SPECint_rate_base2006 = 53.7

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Mar-2007
Hardware Availability: Jul-2006
Software Availability: Nov-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	471	83.0	**471**	**83.0**	471	83.0							
401.bzip2	4	754	51.2	749	51.5	**750**	**51.5**							
403.gcc	4	**1225**	**26.3**	1225	26.3	1222	26.4							
429.mcf	4	745	48.9	744	49.0	**744**	**49.0**							
445.gobmk	4	560	75.0	**559**	**75.0**	559	75.0							
456.hmmer	4	746	50.0	746	50.0	**746**	**50.0**							
458.sjeng	4	692	70.0	692	70.0	**692**	**70.0**							
462.libquantum	4	2603	31.8	**2603**	**31.8**	2603	31.8							
464.h264ref	4	720	123	721	123	**721**	**123**							
471.omnetpp	4	718	34.8	**718**	**34.8**	718	34.8							
473.astar	4	622	45.2	622	45.2	**622**	**45.2**							
483.xalancbmk	4	424	65.1	424	65.2	**424**	**65.1**							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Snoop Filter enabled in BIOS
```

Base Compiler Invocation

C benchmarks:

```
icl -Qc99
```

C++ benchmarks:

```
icl
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`
483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Base Optimization Flags

C benchmarks:

```
-fast /F512000000 shlW32M.lib           -link /FORCE:MULTIPLE
```

Continued on next page

Base Optimization Flags (Continued)

C++ benchmarks:
```
-fast -Qcxx_features /F512000000 shlW32M.lib
-link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/dell.cpu2006.ic91.flags.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/dell.cpu2006.ic91.flags.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:52:21 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 3 April 2007.