SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 1950 (Intel Xeon processor 5120, 1.86GHz)

SPECint®_rate2006 = Not Run

SPECint_rate_base2006 = 37.9

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Mar-2007
Hardware Availability: Jul-2006
Software Availability: Nov-2006



Hardware

CPU Name:	Intel Xeon 5120
CPU Characteristics:	1066 MHz Bus Speed
CPU MHz:	1866
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per chip
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8 x 2 GB 667MHz CL5 DDR2 FB-DIMM SDRAM)
Disk Subsystem:	1 x 73 GB SAS 15k RPM
Other Hardware:	None

Software

Operating System:	Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
Compiler:	Intel C++ Compiler 9.1 for IA32 (20061103Z) Microsoft Visual Studio 2005
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	Not Applicable
Other Software:	MicroQuill SmartHeap Library 8.0

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 1950 (Intel Xeon processor 5120, 1.86GHz)

SPECint_rate2006 = Not Run

SPECint_rate_base2006 = 37.9

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Mar-2007
Hardware Availability: Jul-2006
Software Availability: Nov-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	**737**	**53.0**	737	53.0	737	53.0							
401.bzip2	4	1116	34.6	1113	34.7	**1114**	**34.6**							
403.gcc	4	1569	20.5	**1578**	**20.4**	1584	20.3							
429.mcf	4	901	40.5	**902**	**40.5**	903	40.4							
445.gobmk	4	873	48.1	874	48.0	**874**	**48.0**							
456.hmmer	4	1196	31.2	**1196**	**31.2**	1196	31.2							
458.sjeng	4	**1074**	**45.1**	1074	45.1	1074	45.1							
462.libquantum	4	3082	26.9	3082	26.9	**3082**	**26.9**							
464.h264ref	4	**1145**	**77.3**	1147	77.2	1144	77.4							
471.omnetpp	4	**881**	**28.4**	882	28.4	880	28.4							
473.astar	4	894	31.4	890	31.5	**891**	**31.5**							
483.xalancbmk	4	596	46.3	**596**	**46.3**	596	46.3							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Snoop Filter enabled in BIOS
```

General Notes

```
32-bit binaries were built on Windows XP Professional x64 Edition
```

Base Compiler Invocation

C benchmarks:

```
icl -Qc99
```

C++ benchmarks:

```
icl
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`
483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Base Optimization Flags

C benchmarks:

```
-fast /F512000000 shlW32M.lib -link /FORCE:MULTIPLE
```

C++ benchmarks:

```
-fast -Qcxx_features /F512000000 shlW32M.lib
-link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/dell.cpu2006.ic91.flags.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/dell.cpu2006.ic91.flags.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:57:03 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 17 April 2007.