



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440
(Intel Xeon processor 5120,1.86GHz)

SPECint®2006 = 11.7

SPECint_base2006 = 11.3

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2007

Hardware Availability: Feb-2007

Software Availability: Dec-2006



Hardware

CPU Name: Intel Xeon 5120
 CPU Characteristics: 1.86 GHz, 4 MB L2, 1066 MHz system bus
 CPU MHz: 1866
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 2 cores/chip
 CPU(s) orderable: 2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip
 L3 Cache: None
 Other Cache: None
 Memory: 24 GB (12x2 GB) FB-DIMM PC2-5300F ECC CL5
 Disk Subsystem: 1x73 GB SAS, 15000 RPM
 Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition X64 Edition Service Pack 1
 Compiler: Intel C++ Compiler for IA32 version 9.1
 Package ID W_CC_C_9.1.033 Build no 20061103Z
 Microsoft Visual Studio .NET 2003 (lib & linker)
 Auto Parallel: No
 File System: NTFS
 System State: Default
 Base Pointers: 32-bit
 Peak Pointers: 32-bit
 Other Software: MicroQuill SmartHeap Library 8.0 (shIW32M.lib)



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440
(Intel Xeon processor 5120,1.86GHz)

SPECint2006 = 11.7

SPECint_base2006 = 11.3

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Feb-2007
Software Availability: Dec-2006

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	724	13.5	<u>725</u>	<u>13.5</u>	726	13.5	666	14.7	<u>666</u>	<u>14.7</u>	666	14.7
401.bzip2	997	9.67	999	9.66	<u>999</u>	<u>9.66</u>	972	9.93	972	9.93	<u>972</u>	<u>9.93</u>
403.gcc	1001	8.05	<u>1003</u>	<u>8.03</u>	1004	8.01	975	8.26	<u>976</u>	<u>8.25</u>	977	8.24
429.mcf	660	13.8	<u>659</u>	<u>13.8</u>	659	13.8	707	12.9	<u>708</u>	<u>12.9</u>	708	12.9
445.gobmk	855	12.3	<u>855</u>	<u>12.3</u>	855	12.3	<u>757</u>	<u>13.9</u>	757	13.9	757	13.9
456.hammer	1196	7.80	<u>1196</u>	<u>7.80</u>	1196	7.80	1164	8.01	1164	8.01	<u>1164</u>	<u>8.01</u>
458.sjeng	1059	11.4	1059	11.4	<u>1059</u>	<u>11.4</u>	974	12.4	<u>975</u>	<u>12.4</u>	975	12.4
462.libquantum	1770	11.7	<u>1770</u>	<u>11.7</u>	1770	11.7	1753	11.8	<u>1752</u>	<u>11.8</u>	1752	11.8
464.h264ref	1140	19.4	1140	19.4	<u>1140</u>	<u>19.4</u>	<u>1112</u>	<u>19.9</u>	1112	19.9	1112	19.9
471.omnetpp	684	9.14	<u>682</u>	<u>9.16</u>	682	9.17	<u>620</u>	<u>10.1</u>	620	10.1	619	10.1
473.astar	783	8.96	<u>783</u>	<u>8.97</u>	783	8.97	<u>782</u>	<u>8.98</u>	782	8.98	782	8.98
483.xalancbmk	<u>485</u>	<u>14.2</u>	485	14.2	485	14.2	<u>480</u>	<u>14.4</u>	480	14.4	480	14.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

/NUMPROC=1 flags was added to boot.ini invoke uniprocessor environment

General Notes

The NovaScale R440 and the NovaScale R460 models are electronically equivalent.
The results have been measured on a NovaScale R460 model.

Base Compiler Invocation

C benchmarks:
icl -Qvc7.1 -Qc99
C++ benchmarks:
icl -Qvc7.1

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440
(Intel Xeon processor 5120,1.86GHz)

SPECint2006 = 11.7

SPECint_base2006 = 11.3

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Feb-2007
Software Availability: Dec-2006

Base Optimization Flags

C benchmarks:
-fast /F512000000 shlw32m.lib -link /FORCE:MULTIPLE
C++ benchmarks:
-fast -Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks:
icl -Qvc7.1 -Qc99
C++ benchmarks:
icl -Qvc7.1

Peak Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

Peak Optimization Flags

C benchmarks:
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE
C++ benchmarks:
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

Peak Other Flags

C benchmarks:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440
(Intel Xeon processor 5120,1.86GHz)

SPECint2006 = 11.7

SPECint_base2006 = 11.3

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Feb-2007
Software Availability: Dec-2006

Peak Other Flags (Continued)

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
<http://www.spec.org/cpu2006/flags/flags.20090714.00.html>

You can also download the XML flags source by saving the following link:
<http://www.spec.org/cpu2006/flags/flags.20090714.00.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:10:14 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 12 June 2007.