



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440
(Intel Xeon processor 5140,2.33GHz)

SPECfp®2006 = 13.4

SPECfp_base2006 = 13.2

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2007

Hardware Availability: Mar-2007

Software Availability: Dec-2006



Hardware

CPU Name: Intel Xeon 5140
 CPU Characteristics: 2.33 GHz, 4 MB L2, 1333 MHz system bus
 CPU MHz: 2333
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 to 2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip

Continued on next page

Software

Operating System: SuSE Linux Enterprise Server 10 (EM64T) kernel 2.6.16.21-0.8-smp
 Compiler: Intel C++ Compiler for Intel EM64T-based applications, Version 9.1
 Package ID l_cc_c_9.1.045 Build no 20061101
 Intel Fortran Compiler for Intel EM64T-based applications, Version 9.1
 Package ID l_fc_c_9.1.040 Build no 20061101
 Auto Parallel: No

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440
(Intel Xeon processor 5140,2.33GHz)

SPECfp2006 = 13.4

SPECfp_base2006 = 13.2

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2007

Hardware Availability: Mar-2007

Software Availability: Dec-2006

L3 Cache: None
Other Cache: None
Memory: 24 GB (12x2 GB) FB-DIMM PC2-5300F ECC CL5
Disk Subsystem: 1x73 GB SAS, 15000 RPM
Other Hardware: None

File System: ext2
System State: Multi-user run level 3
Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<u>733</u>	<u>18.5</u>	733	18.6	733	18.5	732	18.6	731	18.6	<u>732</u>	<u>18.6</u>
416.gamess	<u>1222</u>	<u>16.0</u>	1224	16.0	1220	16.0	1321	14.8	1324	14.8	<u>1322</u>	<u>14.8</u>
433.milc	916	10.0	916	10.0	<u>916</u>	<u>10.0</u>	919	9.99	919	9.99	<u>919</u>	<u>9.99</u>
434.zeusmp	<u>737</u>	<u>12.3</u>	737	12.3	738	12.3	762	11.9	763	11.9	<u>763</u>	<u>11.9</u>
435.gromacs	503	14.2	502	14.2	<u>502</u>	<u>14.2</u>	<u>486</u>	<u>14.7</u>	486	14.7	486	14.7
436.cactusADM	<u>842</u>	<u>14.2</u>	836	14.3	845	14.1	865	13.8	848	14.1	<u>860</u>	<u>13.9</u>
437.leslie3d	<u>807</u>	<u>11.6</u>	809	11.6	801	11.7	<u>810</u>	<u>11.6</u>	809	11.6	810	11.6
444.namd	<u>654</u>	<u>12.3</u>	655	12.2	654	12.3	665	12.1	665	12.1	<u>665</u>	<u>12.1</u>
447.dealII	<u>538</u>	<u>21.3</u>	538	21.3	537	21.3	523	21.9	<u>523</u>	<u>21.9</u>	523	21.9
450.soplex	726	11.5	<u>726</u>	<u>11.5</u>	725	11.5	709	11.8	<u>709</u>	<u>11.8</u>	709	11.8
453.povray	330	16.1	<u>329</u>	<u>16.2</u>	328	16.2	<u>252</u>	<u>21.1</u>	252	21.1	252	21.1
454.calculix	<u>669</u>	<u>12.3</u>	669	12.3	670	12.3	652	12.7	653	12.6	<u>652</u>	<u>12.6</u>
459.GemsFDTD	962	11.0	961	11.0	<u>962</u>	<u>11.0</u>	969	10.9	968	11.0	<u>968</u>	<u>11.0</u>
465.tonto	766	12.8	<u>767</u>	<u>12.8</u>	767	12.8	739	13.3	<u>740</u>	<u>13.3</u>	747	13.2
470.lbm	2289	6.00	<u>2292</u>	<u>5.99</u>	2299	5.98	2287	6.01	<u>2295</u>	<u>5.99</u>	2300	5.97
481.wrf	741	15.1	740	15.1	<u>741</u>	<u>15.1</u>	<u>769</u>	<u>14.5</u>	768	14.5	769	14.5
482.sphinx3	1189	16.4	<u>1198</u>	<u>16.3</u>	1199	16.3	1097	17.8	1107	17.6	<u>1098</u>	<u>17.8</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Environment stack size set to 'unlimited'

system was booted uniprocessor by setting "maxcpus=0"
kernel parameter in menu.lst

/usr/bin/taskset utility used to bind CPU(s) to processes

General Notes

The NovaScale R440 and the NovaScale R460 models are electronically equivalent.
The results have been measured on a NovaScale R460 model.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440
(Intel Xeon processor 5140,2.33GHz)

SPECfp2006 = 13.4

SPECfp_base2006 = 13.2

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Mar-2007
Software Availability: Dec-2006

Base Compiler Invocation

C benchmarks:
icc
C++ benchmarks:
icpc
Fortran benchmarks:
ifort
Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast
C++ benchmarks:
-fast
Fortran benchmarks:
-fast
Benchmarks using both Fortran and C:
-fast



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440
(Intel Xeon processor 5140,2.33GHz)

SPECfp2006 = 13.4

SPECfp_base2006 = 13.2

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Mar-2007
Software Availability: Dec-2006

Peak Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:
-prof_gen(pass 1) -prof_use(pass 2) -fast -auto_ilp32

C++ benchmarks:
-prof_gen(pass 1) -prof_use(pass 2) -fast -auto_ilp32

Fortran benchmarks:
-prof_gen(pass 1) -prof_use(pass 2) -fast

Benchmarks using both Fortran and C:
-prof_gen(pass 1) -prof_use(pass 2) -fast -auto_ilp32

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/EM64T_Intel91_flags.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/EM64T_Intel91_flags.xml



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440
(Intel Xeon processor 5140,2.33GHz)

SPECfp2006 = 13.4

SPECfp_base2006 = 13.2

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Mar-2007
Software Availability: Dec-2006

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:10:40 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 12 June 2007.