SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Supermicro X7DB8+ (Intel Xeon processor X5365, 3.00 GHz)

SPECint®2006 = 20.8

SPECint_base2006 = 18.9

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: May-2007
Hardware Availability: Sep-2007
Software Availability: Jun-2007



Hardware

CPU Name:	Intel Xeon X5365
CPU Characteristics:	Quad Core, 3.0 GHz
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8 * 2GB Samsung DDR2 5300F, 2 rank, CL5-5-5, ECC)
Disk Subsystem:	Seagate, SCSI, 73GB, 10Krpm, 1 disk only
Other Hardware:	None

Software

Operating System:	64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp for x86_64
Compiler:	Intel C++ Compiler for Linux32 version 10.0 Build 20070426 Package ID: l_cc_p_10.0.023
Auto Parallel:	No
File System:	ReiserFS
System State:	Multi-user, run level 3
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	SmartHeap library V8.1 Binutils 2.17.50.0.15

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Supermicro X7DB8+ (Intel Xeon processor X5365, 3.00 GHz)

SPECint2006 = 20.8

SPECint_base2006 = 18.9

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: May-2007
Hardware Availability: Sep-2007
Software Availability: Jun-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	480	20.4	**481**	**20.3**	484	20.2	405	24.1	405	24.1	**405**	**24.1**
401.bzip2	647	14.9	**641**	**15.1**	639	15.1	**601**	**16.1**	602	16.0	600	16.1
403.gcc	447	18.0	**447**	**18.0**	446	18.0	447	18.0	**447**	**18.0**	446	18.0
429.mcf	468	19.5	469	19.5	**468**	**19.5**	**440**	**20.7**	437	20.9	441	20.7
445.gobmk	**536**	**19.6**	536	19.6	536	19.6	**490**	**21.4**	490	21.4	490	21.4
456.hmmer	593	15.7	591	15.8	**592**	**15.8**	**465**	**20.0**	466	20.0	465	20.1
458.sjeng	690	17.5	694	17.4	**693**	**17.5**	619	19.5	618	19.6	**619**	**19.6**
462.libquantum	**839**	**24.7**	838	24.7	839	24.7	675	30.7	675	30.7	**675**	**30.7**
464.h264ref	714	31.0	712	31.1	**713**	**31.0**	676	32.8	675	32.8	**675**	**32.8**
471.omnetpp	468	13.3	**466**	**13.4**	466	13.4	430	14.5	429	14.6	**430**	**14.6**
473.astar	**499**	**14.1**	500	14.1	499	14.1	461	15.2	**459**	**15.3**	459	15.3
483.xalancbmk	**281**	**24.5**	281	24.5	281	24.6	**281**	**24.5**	281	24.5	281	24.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
Bios settings:
Hardware Prefetcher:      Enabled
Adjacent Sector Prefetch: Disabled
All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hmmer,
for peak, are compiled in 64-bit mode
```

Base Compiler Invocation

C benchmarks:
`icc`

C++ benchmarks:
`icpc`

Base Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_IA32`
462.libquantum: `-DSPEC_CPU_LINUX`
483.xalancbmk: `-DSPEC_CPU_LINUX`

Base Optimization Flags

C benchmarks:
`-fast`

C++ benchmarks:
`-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs`
`-L/spec/cpu2006.1.0/lib -lsmartheap`

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks (except as noted below):
`icc`

401.bzip2: `/opt/intel/cce/10.0.023/bin/icc`

456.hmmer: `/opt/intel/cce/10.0.023/bin/icc`

C++ benchmarks:
`icpc`

Peak Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_IA32`
401.bzip2: `-DSPEC_CPU_LP64`
456.hmmer: `-DSPEC_CPU_LP64`
462.libquantum: `-DSPEC_CPU_LINUX`
483.xalancbmk: `-DSPEC_CPU_LINUX`

Peak Optimization Flags

C benchmarks:

400.perlbench: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -ansi-alias`
`-prefetch`

401.bzip2: `-L/opt/intel/cce/10.0.023/lib -I/opt/intel/cce/10.0.023/include`
`-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast`

Continued on next page

Peak Optimization Flags (Continued)

403.gcc: `basepeak = yes`

429.mcf: `-fast -prefetch`

445.gobmk: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-xT -O2 -ipo -no-prec_div -ansi-alias`

456.hmmer: `-L/opt/intel/cce/10.0.023/lib -I/opt/intel/cce/10.0.023/include -prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll2 -ansi-alias`

458.sjeng: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll4`

462.libquantum: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll4 -Ob0 -prefetch -opt-streaming-stores always`

464.h264ref: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll2 -ansi-alias`

C++ benchmarks:

471.omnetpp: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-xT -O3 -ipo -no-prec_div -ansi-alias -Wl,-z,muldefs -L/spec/cpu2006.1.0/lib -lsmartheap`

473.astar: `Same as 471.omnetpp`

483.xalancbmk: `basepeak = yes`

Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090715.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090715.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:08:17 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 12 June 2007.