



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon processor E5310,
1.60 GHz

SPECint®_rate2006 = 40.0

SPECint_rate_base2006 = 37.3

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Jul-2007

Hardware Availability: Nov-2006

Software Availability: Jun-2007



SPECint_rate_base2006 = 37.3

SPECint_rate2006 = 40.0

Hardware

CPU Name: Intel Xeon E5310
 CPU Characteristics: 1067 MHz system bus
 CPU MHz: 1600
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 8 GB (8x1 GB DDR2 PC2-5300F, 2 rank, CAS 5-5-5, with ECC)
 Disk Subsystem: Seagate ST3146854SS (SAS, 146GB, 15000rpm)
 Other Hardware: None

Software

Operating System: SUSE LINUX Enterprise Server 10 (x86_64), Kernel 2.6.16.21-0.8-smpp
 Compiler: Intel C++ Compiler for IA32/EM64T application, Version 10.0 - Build 20070308, Package-ID: I_cc_p_10.0.023
 Auto Parallel: No
 File System: ext2
 System State: Multiuser, Runlevel 3
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: Smart Heap Library, Version 8.1
 binutils-2.17.tar.gz, Version 2.17



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon processor E5310,
1.60 GHz

SPECint_rate2006 = 40.0

SPECint_rate_base2006 = 37.3

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Jul-2007

Hardware Availability: Nov-2006

Software Availability: Jun-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	907	43.1	910	42.9	915	42.7	4	761	51.3	763	51.2	760	51.4
401.bzip2	4	1289	30.0	1300	29.7	1294	29.8	4	1200	32.2	1197	32.2	1197	32.2
403.gcc	4	865	37.2	869	37.1	860	37.5	4	865	37.2	869	37.1	860	37.5
429.mcf	4	964	37.8	964	37.8	964	37.8	4	958	38.1	959	38.0	960	38.0
445.gobmk	4	1000	41.9	1001	41.9	1001	41.9	4	917	45.7	916	45.8	917	45.7
456.hmmmer	4	1119	33.4	1116	33.4	1117	33.4	4	883	42.3	887	42.1	886	42.1
458.sjeng	4	1265	38.3	1268	38.2	1266	38.2	4	1124	43.0	1127	43.0	1123	43.1
462.libquantum	4	2866	28.9	2862	29.0	2862	29.0	4	2878	28.8	2884	28.7	2888	28.7
464.h264ref	4	1356	65.3	1353	65.4	1355	65.3	4	1285	68.9	1290	68.6	1283	69.0
471.omnetpp	4	878	28.5	883	28.3	897	27.9	4	815	30.7	816	30.6	817	30.6
473.aster	4	984	28.5	983	28.6	984	28.5	4	965	29.1	968	29.0	964	29.1
483.xalancbmk	4	565	48.8	568	48.6	571	48.4	4	565	48.8	568	48.6	571	48.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

All binaries were built with 32-bit Intel compiler except:
401.bzip2 and 456.hmmmer in peak were built with 64-bit Intel
compiler by changing the path for include and library files.

BIOS configuration:
Adjacent Sector Prefetch = Disable

This result was measured on the PRIMERGY RX300 S3. The PRIMERGY RX300 S3
and the PRIMERGY TX300 S3 are electronically equivalent.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com>

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon processor E5310,
1.60 GHz

SPECint_rate2006 = 40.0

SPECint_rate_base2006 = 37.3

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Jul-2007

Hardware Availability: Nov-2006

Software Availability: Jun-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-xT -O3 -ipo -no-prec-div -ansi-alias
-L/opt/SmartHeap_8_1/lib -lsmarheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/cce/10.0.023/bin/icc
-I/opt/intel/cce/10.0.023/include
-L/opt/intel/cce/10.0.023/lib

456.hmmer: /opt/intel/cce/10.0.023/bin/icc
-I/opt/intel/cce/10.0.023/include
-L/opt/intel/cce/10.0.023/lib

C++ benchmarks:

icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon processor E5310,
1.60 GHz

SPECint_rate2006 = 40.0

SPECint_rate_base2006 = 37.3

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Jul-2007

Hardware Availability: Nov-2006

Software Availability: Jun-2007

Peak Portability Flags (Continued)

483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof_gen(pass 1) -prof_use(pass 2) -fast

401.bzip2: -fast

403.gcc: basepeak = yes

429.mcf: -prof_gen(pass 1) -prof_use(pass 2) -fast -prefetch
-L/opt/SmartHeap_8_1/lib -lsmartheap

445.gobmk: Same as 400.perlbench

456.hmmer: -prof_gen(pass 1) -prof_use(pass 2) -fast -unroll2

458.sjeng: -prof_gen(pass 1) -prof_use(pass 2) -fast -unroll4

462.libquantum: -prof_gen(pass 1) -prof_use(pass 2) -fast -prefetch
-opt-streaming-stores always

464.h264ref: -prof_gen(pass 1) -prof_use(pass 2) -fast -unroll2
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof_gen(pass 1) -prof_use(pass 2) -fast -ansi-alias
-L/opt/SmartHeap_8_1/lib -lsmartheap

473.astar: Same as 471.omnetpp

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/FSC_Intel_flags.html



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon processor E5310,
1.60 GHz

SPECint_rate2006 = 40.0

SPECint_rate_base2006 = 37.3

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Jul-2007

Hardware Availability: Nov-2006

Software Availability: Jun-2007

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/FSC_Intel_flags.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 12:58:10 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 August 2007.