



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint®_rate2006 = 83.3

IBM BladeCenter LS41 (AMD Opteron 8214)

SPECint_rate_base2006 = 74.4

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jul-2007

Hardware Availability: Oct-2006

Software Availability: Mar-2007



Hardware

CPU Name: AMD Opteron 8214
 CPU Characteristics:
 CPU MHz: 2200
 FPU: Integrated
 CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip
 CPU(s) orderable: 1, 2, 3, 4 chips
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: None
 Other Cache: None
 Memory: 32 GB (16 x 2GB DDR2-5300 ECC)
 Disk Subsystem: 1 x 36 GB SAS, 10000 RPM
 Other Hardware: None

Software

Operating System: SLES 10 (x86_64), 2.6.16.21-0.8-smp
 Compiler: QLogic PathScale Compiler Suite, Release 3.0
 Auto Parallel: No
 File System: ext3
 System State: Multi-user, run level 3
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap 8.1



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = 83.3

IBM BladeCenter LS41 (AMD Opteron 8214)

SPECint_rate_base2006 = 74.4

CPU2006 license: 11

Test date: Jul-2007

Test sponsor: IBM Corporation

Hardware Availability: Oct-2006

Tested by: IBM Corporation

Software Availability: Mar-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	999	78.2	989	79.0	994	78.7	8	808	96.7	809	96.6	813	96.2
401.bzip2	8	1237	62.4	1238	62.4	1241	62.2	8	1229	62.8	1232	62.7	1235	62.5
403.gcc	8	1217	52.9	1218	52.9	1220	52.8	8	959	67.1	959	67.1	961	67.0
429.mcf	8	1209	60.3	1214	60.1	1213	60.2	8	890	82.0	891	81.9	891	81.9
445.gobmk	8	943	89.0	945	88.8	945	88.8	8	802	105	800	105	801	105
456.hammer	8	867	86.1	864	86.4	868	86.0	8	637	117	640	117	638	117
458.sjeng	8	1186	81.6	1188	81.4	1184	81.8	8	1094	88.5	1092	88.6	1090	88.8
462.libquantum	8	2233	74.2	2217	74.8	2218	74.7	8	2218	74.7	2217	74.8	2216	74.8
464.h264ref	8	1364	130	1353	131	1368	129	8	1318	134	1319	134	1317	134
471.omnetpp	8	879	56.9	889	56.2	879	56.9	8	875	57.2	874	57.2	880	56.8
473.astar	8	943	59.5	943	59.6	945	59.4	8	943	59.5	943	59.6	945	59.4
483.xalanbmk	8	615	89.7	616	89.7	616	89.6	8	609	90.6	612	90.3	609	90.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

taskset utility used to bind CPU(s) to processes

Base Compiler Invocation

C benchmarks:
pathcc

C++ benchmarks:
pathCC

Base Portability Flags

```

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hammer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalanbmk: -DSPEC_CPU_LINUX

```



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = 83.3

IBM BladeCenter LS41 (AMD Opteron 8214)

SPECint_rate_base2006 = 74.4

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jul-2007

Hardware Availability: Oct-2006

Software Availability: Mar-2007

Base Optimization Flags

C benchmarks:

-Ofast -OPT:malloc_alg=1

C++ benchmarks:

-Ofast -m32 -L/tools/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:

-IPA:max_jobs=2

C++ benchmarks:

-IPA:max_jobs=2

Peak Compiler Invocation

C benchmarks:

pathcc

C++ benchmarks:

pathCC

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalanbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
-LNO:opt=0

401.bzip2: -O3 -LNO:ou_prod_max=10 -OPT:Ofast -OPT:alias=disjoint

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = 83.3

IBM BladeCenter LS41 (AMD Opteron 8214)

SPECint_rate_base2006 = 74.4

CPU2006 license: 11

Test date: Jul-2007

Test sponsor: IBM Corporation

Hardware Availability: Oct-2006

Tested by: IBM Corporation

Software Availability: Mar-2007

Peak Optimization Flags (Continued)

403.gcc: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -m32 -O3
-OPT:Ofast

429.mcf: -m32 -O3 -ipa -L/tools/SmartHeap_8.1/lib -lsmartheap

445.gobmk: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
-OPT:alias=disjoint -LNO:simd=0 -LNO:minvariant=off
-WOPT:retype_expr=on

456.hmmr: -O2 -OPT:alias=disjoint -OPT:malloc_alg=1 -CG:cflow=0

458.sjeng: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
-IPA:plimit=50000 -IPA:pu_reorder=2

462.libquantum: -O3 -ipa -CG:local_fwd_sched=on -IPA:space=1000

464.h264ref: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
-IPA:plimit=20000 -OPT:alias=disjoint -LNO:prefetch=0

C++ benchmarks:

471.omnetpp: -Ofast -CG:gcm=off -m32
-L/tools/SmartHeap_8.1/lib -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: -Ofast -m32 -OPT:unroll_times_max=8
-L/tools/SmartHeap_8.1/lib -lsmartheap

Peak Other Flags

C benchmarks:

-IPA:max_jobs=2

C++ benchmarks:

-IPA:max_jobs=2

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.13.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.13.xml



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = 83.3

IBM BladeCenter LS41 (AMD Opteron 8214)

SPECint_rate_base2006 = 74.4

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jul-2007

Hardware Availability: Oct-2006

Software Availability: Mar-2007

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 12:25:45 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 21 August 2007.