



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint®_rate2006 = 41.9

PowerEdge 2970 (AMD Opteron 2218, 2.60 GHz)

SPECint_rate_base2006 = 38.2

CPU2006 license: 55


Test date: Nov-2007

Test sponsor: Dell Inc.

Hardware Availability: Sep-2007

Tested by: Dell Inc.

Software Availability: Oct-2007



Hardware

CPU Name: AMD Opteron 2218
 CPU Characteristics:
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8x2GB, DDR2-667 CL5 ECC Dual Rank)
 Disk Subsystem: 1 x 73 GB SAS 10k RPM
 Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
 Compiler: The Portland Group (PGI) PGI pgcc 7.1-0 C Compiler PGI pgCC 7.1-0 C++ Compiler
 Auto Parallel: No
 File System: ReiserFS
 System State: Multi-user, run level 3
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap 8.0 32-bit Library for Linux



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint_rate2006 = 41.9

PowerEdge 2970 (AMD Opteron 2218, 2.60 GHz)

SPECint_rate_base2006 = 38.2

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Nov-2007
Hardware Availability: Sep-2007
Software Availability: Oct-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	<u>922</u>	<u>42.4</u>	923	42.3	920	42.5	4	767	51.0	769	50.8	<u>767</u>	<u>51.0</u>
401.bzip2	4	1286	30.0	<u>1286</u>	<u>30.0</u>	1291	29.9	4	1268	30.4	<u>1267</u>	<u>30.5</u>	1266	30.5
403.gcc	4	<u>1557</u>	<u>20.7</u>	1561	20.6	1547	20.8	4	<u>1005</u>	<u>32.0</u>	1006	32.0	997	32.3
429.mcf	4	1581	23.1	<u>1581</u>	<u>23.1</u>	1581	23.1	4	1184	30.8	<u>1185</u>	<u>30.8</u>	1185	30.8
445.gobmk	4	831	50.5	834	50.3	<u>833</u>	<u>50.4</u>	4	<u>775</u>	<u>54.1</u>	776	54.1	772	54.3
456.hmmer	4	<u>606</u>	<u>61.5</u>	604	61.8	607	61.5	4	576	64.8	<u>577</u>	<u>64.7</u>	578	64.6
458.sjeng	4	999	48.5	1000	48.4	<u>999</u>	<u>48.4</u>	4	949	51.0	947	51.1	<u>949</u>	<u>51.0</u>
462.libquantum	4	1650	50.2	1654	50.1	<u>1650</u>	<u>50.2</u>	4	1650	50.2	1654	50.1	<u>1650</u>	<u>50.2</u>
464.h264ref	4	1232	71.9	1248	70.9	<u>1241</u>	<u>71.3</u>	4	1232	71.9	1248	70.9	<u>1241</u>	<u>71.3</u>
471.omnetpp	4	1053	23.7	1053	23.8	<u>1053</u>	<u>23.7</u>	4	1053	23.7	1053	23.8	<u>1053</u>	<u>23.7</u>
473.astar	4	965	29.1	<u>965</u>	<u>29.1</u>	964	29.1	4	965	29.1	<u>965</u>	<u>29.1</u>	964	29.1
483.xalancbmk	4	<u>652</u>	<u>42.3</u>	651	42.4	652	42.3	4	649	42.6	645	42.8	<u>646</u>	<u>42.8</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
'ulimit -s unlimited' was used to set environment stack size
'ulimit -l 2457600' was used to set environment locked pages in memory quantity
'numactl' was used to bind one copy per core, and memory to a local NUMA node
Set vm/nr_hugepages=1200 in /etc/sysctl.conf
mount -t hugetlbfs nodev /mnt/hugepages
Environment variable PGI_HUGE_PAGES set to 150
```

Base Compiler Invocation

C benchmarks:
pgcc

C++ benchmarks:
pgcpp

Base Portability Flags

```
400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint_rate2006 = 41.9

PowerEdge 2970 (AMD Opteron 2218, 2.60 GHz)

SPECint_rate_base2006 = 38.2

CPU2006 license: 55

Test date: Nov-2007

Test sponsor: Dell Inc.

Hardware Availability: Sep-2007

Tested by: Dell Inc.

Software Availability: Oct-2007

Base Portability Flags (Continued)

458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-fast -Mipa=fast -Mipa=inline -Mipa=noarg -Mfprelaxed
-Msmartalloc=huge:64 -tp k8-64 -Bstatic_pgi

C++ benchmarks:

-fastsse -Mipa=fast -Mipa=inline -Mfprelaxed -Msmartalloc --zc_eh
-tp k8-32 -Bstatic_pgi -lsmartheap

Base Other Flags

C benchmarks:

-w

C++ benchmarks:

-w -L/proj/qa/smartheap/SmartHeap_8/lib

Peak Compiler Invocation

C benchmarks:

pgcc

C++ benchmarks:

pgcpp

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint_rate2006 = 41.9

PowerEdge 2970 (AMD Opteron 2218, 2.60 GHz)

SPECint_rate_base2006 = 38.2

CPU2006 license: 55

Test date: Nov-2007

Test sponsor: Dell Inc.

Hardware Availability: Sep-2007

Tested by: Dell Inc.

Software Availability: Oct-2007

Peak Optimization Flags

C benchmarks:

400.perlbench: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=inline(pass 2) -fast
-O4 -Mfp relaxed -Msmartalloc=huge:8 -Mnounroll -tp k8-64
-Bstatic_pgi

401.bzip2: -Mpfi(pass 1) -Mpfo(pass 2) -fast -O4
-Msmartalloc=huge:64 -tp k8-64 -Bstatic_pgi

403.gcc: -fastsse -Mfp relaxed -Msmartalloc=huge:32 -Mipa=fast
-Mipa=inline -tp k8-32 -Bstatic_pgi

429.mcf: -fastsse -Mipa=fast -Mipa=inline -Msmartalloc=huge:16
-tp k8-32 -Bstatic_pgi

445.gobmk: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=fast(pass 2) -fast -O4
-Msmartalloc=huge:32 -Mfp relaxed -Mnovect -tp k8-64
-Bstatic_pgi

456.hmmer: -fast -Msmartalloc=huge:32 -Mfp relaxed -Msafeptr
-Mipa=const -Mipa=ptr -Mipa=arg -tp k8-64 -Bstatic_pgi

458.sjeng: -Mpfi(pass 1) -Mipa=fast(pass 2) -Mipa=inline(pass 2)
-Mipa=noarg(pass 2) -Mpfo(pass 2) -fast
-Msmartalloc=huge:32 -Mfp relaxed -tp k8-64 -Bstatic_pgi

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: basepeak = yes

473.astar: basepeak = yes

483.xalancbmk: -fastsse -O4 -Mipa=fast -Mipa=inline -Mfp relaxed
-Msmartalloc --zc_eh -tp k8-32 -Bstatic_pgi -lsmartheap

Peak Other Flags

C benchmarks:

-w

C++ benchmarks:

-w -L/proj/qa/smartheap/SmartHeap_8/lib



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint_rate2006 = 41.9

PowerEdge 2970 (AMD Opteron 2218, 2.60 GHz)

SPECint_rate_base2006 = 38.2

CPU2006 license: 55

Test date: Nov-2007

Test sponsor: Dell Inc.

Hardware Availability: Sep-2007

Tested by: Dell Inc.

Software Availability: Oct-2007

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/pgi710_flags.20090714.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/pgi710_flags.20090714.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 14:36:13 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 27 November 2007.