



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro Motherboard X7DWA-N

SPECfp®_rate2006 = 83.4

SPECfp_rate_base2006 = 78.7

CPU2006 license: 001176


Test sponsor: Supermicro

Tested by: Supermicro

Test date: Oct-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon X5482
 CPU Characteristics: Quad Core, 3.20GHz
 CPU MHz: 3200
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1, 2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

Software

Operating System: 64-Bit Suse Linux Enterprise Server 10 w/ SP1
 Compiler: Intel C++ and Fortran Compiler for Linux32 and Linux64 version 10.1
 Build 20070725
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Multi-user, run level 3
 Base Pointers: 64-bit
 Peak Pointers: 32/64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro Motherboard X7DWA-N

SPECfp_rate2006 = 83.4

SPECfp_rate_base2006 = 78.7

CPU2006 license: 001176
Test sponsor: Supermicro
Tested by: Supermicro

Test date: Oct-2007
Hardware Availability: Nov-2007
Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8 * 2 GB PC2-6400 FBDIMM, CL-5-5-5, ECC)
Disk Subsystem: WD WD5000YS Caviar RE2, 500GB SATA, 7200RPM
Other Hardware: None

Other Software: None

Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
410.bwaves	8	2500	43.5	2502	43.4	<u>2501</u>	<u>43.5</u>	4	<u>1297</u>	<u>41.9</u>	1297	41.9	1298	41.9		
416.gamess	8	833	188	<u>833</u>	<u>188</u>	835	188	8	<u>822</u>	<u>190</u>	821	191	823	190		
433.milc	8	<u>2418</u>	<u>30.4</u>	2417	30.4	2419	30.4	8	2372	31.0	<u>2369</u>	<u>31.0</u>	2367	31.0		
434.zeusmp	8	869	83.7	<u>865</u>	<u>84.2</u>	863	84.3	8	858	84.8	848	85.9	<u>855</u>	<u>85.2</u>		
435.gromacs	8	<u>354</u>	<u>161</u>	354	161	354	161	8	356	161	352	162	<u>353</u>	<u>162</u>		
436.cactusADM	8	1158	82.6	<u>1153</u>	<u>82.9</u>	1152	83.0	1	106	112	<u>105</u>	<u>114</u>	104	114		
437.leslie3d	8	2130	35.3	2132	35.3	<u>2131</u>	<u>35.3</u>	4	1137	33.1	<u>1137</u>	<u>33.1</u>	1137	33.1		
444.namd	8	478	134	477	135	<u>477</u>	<u>134</u>	8	<u>477</u>	<u>135</u>	481	133	474	135		
447.dealII	8	632	145	<u>574</u>	<u>160</u>	571	160	8	<u>560</u>	<u>163</u>	594	154	559	164		
450.soplex	8	1552	43.0	<u>1534</u>	<u>43.5</u>	1533	43.5	8	1429	46.7	<u>1378</u>	<u>48.4</u>	1370	48.7		
453.povray	8	<u>203</u>	<u>210</u>	202	211	205	207	8	<u>171</u>	<u>249</u>	170	251	172	248		
454.calculix	8	509	130	<u>513</u>	<u>129</u>	513	129	8	363	182	<u>365</u>	<u>181</u>	370	178		
459.GemsFDTD	8	2465	34.4	<u>2450</u>	<u>34.6</u>	2447	34.7	8	<u>2359</u>	<u>36.0</u>	2355	36.0	2362	35.9		
465.tonto	8	578	136	584	135	<u>581</u>	<u>135</u>	8	570	138	565	139	<u>565</u>	<u>139</u>		
470.lbm	8	3590	30.6	<u>3587</u>	<u>30.6</u>	3586	30.7	4	<u>1479</u>	<u>37.2</u>	1478	37.2	1494	36.8		
481.wrf	8	1279	69.8	<u>1282</u>	<u>69.7</u>	1288	69.4	8	1284	69.6	<u>1289</u>	<u>69.3</u>	1289	69.3		
482.sphinx3	8	2280	68.4	<u>2292</u>	<u>68.0</u>	2298	67.9	4	<u>1357</u>	<u>57.5</u>	1360	57.3	1352	57.7		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Tested systems can be used with CSE-825TQ-R700LPV case,
To ensure system stability, a 500W (minimum)
ATX power supply [4-pin (+12V), 8-pin (+12V) and 24-pin are required]
Product description located as of
<http://www.supermicro.com/products/motherboard/Xeon1333/5400/X7WA-N.cfm>
The system bus runs at 1600 MHz
BIOS Setting: Default
The taskset command was used with submit to bind benchmark copies to processors.
Except for 436.cactusADM peak runs which did not use submit.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro
Motherboard X7DWA-N

SPECfp_rate2006 = 83.4

SPECfp_rate_base2006 = 78.7

CPU2006 license: 001176
Test sponsor: Supermicro
Tested by: Supermicro

Test date: Oct-2007
Hardware Availability: Nov-2007
Software Availability: Nov-2007

Base Compiler Invocation

C benchmarks:
icc
C++ benchmarks:
icpc
Fortran benchmarks:
ifort
Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast
C++ benchmarks:
-fast
Fortran benchmarks:
-fast
Benchmarks using both Fortran and C:
-fast



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Supermicro
Motherboard X7DWA-N**

SPECfp_rate2006 = 83.4

SPECfp_rate_base2006 = 78.7

CPU2006 license: 001176
Test sponsor: Supermicro
Tested by: Supermicro

Test date: Oct-2007
Hardware Availability: Nov-2007
Software Availability: Nov-2007

Peak Compiler Invocation

C benchmarks (except as noted below):

```
/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icpc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

Fortran benchmarks (except as noted below):

ifort

```
437.leslie3d: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/ifort
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.deallI: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Supermicro
Motherboard X7DWA-N**

SPECfp_rate2006 = 83.4

SPECfp_rate_base2006 = 78.7

CPU2006 license: 001176
Test sponsor: Supermicro
Tested by: Supermicro

Test date: Oct-2007
Hardware Availability: Nov-2007
Software Availability: Nov-2007

Peak Optimization Flags (Continued)

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro
Motherboard X7DWA-N

SPECfp_rate2006 = 83.4

SPECfp_rate_base2006 = 78.7

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

Test date: Oct-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.22.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.22.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.1.
Report generated on Tue Jul 22 15:09:38 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 21 December 2007.