



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

**SPECint®2006 = 26.5**

## IBM System x3650 (Intel Xeon X5450)

**SPECint\_base2006 = 23.1**

CPU2006 license: 11


Test date: Jan-2008

Test sponsor: IBM Corporation

Hardware Availability: Jan-2008

Tested by: IBM Corporation

Software Availability: Nov-2007



### Hardware

CPU Name: Intel Xeon X5450  
 CPU Characteristics: 1333MHz system bus  
 CPU MHz: 3000  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores  
 L3 Cache: None  
 Other Cache: None  
 Memory: 16 GB (8 x 2 GB DDR2-5300F ECC)  
 Disk Subsystem: 1 x 36 GB SAS, 15000 RPM  
 Other Hardware: None

### Software

Operating System: SuSE Linux Enterprise Server 10 (x86\_64), Kernel 2.6.16.21-0.8-smp  
 Compiler: Intel C++ Compiler 10.1 for Linux Build 20070913 Package ID: l\_cc\_p\_10.1.008  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Multi-user, run level 3  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: MicroQuill SmartHeap 8.1 Binutils 2.17.50.0.15



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 26.5

IBM System x3650 (Intel Xeon X5450)

SPECint\_base2006 = 23.1

CPU2006 license: 11

Test date: Jan-2008

Test sponsor: IBM Corporation

Hardware Availability: Jan-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	503	19.4	<u>502</u>	<u>19.5</u>	502	19.5	<u>404</u>	<u>24.2</u>	402	24.3	410	23.8
401.bzip2	594	16.3	<u>596</u>	<u>16.2</u>	597	16.2	<u>548</u>	<u>17.6</u>	548	17.6	549	17.6
403.gcc	526	15.3	557	14.5	<u>554</u>	<u>14.5</u>	412	19.5	<u>411</u>	<u>19.6</u>	411	19.6
429.mcf	<u>416</u>	<u>21.9</u>	415	22.0	417	21.9	383	23.8	<u>384</u>	<u>23.8</u>	384	23.8
445.gobmk	<u>534</u>	<u>19.6</u>	534	19.6	535	19.6	<u>482</u>	<u>21.7</u>	482	21.7	483	21.7
456.hmmmer	594	15.7	<u>593</u>	<u>15.7</u>	593	15.7	341	27.3	342	27.3	<u>341</u>	<u>27.3</u>
458.sjeng	684	17.7	<u>685</u>	<u>17.7</u>	687	17.6	<u>613</u>	<u>19.7</u>	612	19.8	613	19.7
462.libquantum	<u>90.0</u>	<u>230</u>	88.6	234	96.3	215	<u>93.7</u>	<u>221</u>	93.4	222	94.3	220
464.h264ref	<u>713</u>	<u>31.0</u>	711	31.1	714	31.0	<u>664</u>	<u>33.3</u>	664	33.3	665	33.3
471.omnetpp	411	15.2	<u>413</u>	<u>15.1</u>	414	15.1	375	16.6	<u>375</u>	<u>16.6</u>	376	16.6
473.astar	<u>467</u>	<u>15.0</u>	467	15.0	473	14.8	428	16.4	425	16.5	<u>425</u>	<u>16.5</u>
483.xalancbmk	269	25.7	269	25.6	<u>269</u>	<u>25.7</u>	269	25.7	269	25.6	<u>269</u>	<u>25.7</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hmmmer, for peak, are compiled in 64-bit mode  
Hardware Sector Prefetch Enabled and Adjacent Sector Prefetch Enabled  
OMP\_NUM\_THREADS set to number of cores  
KMP\_AFFINITY set to physical,0  
KMP\_STACKSIZE set to null  
Powersaved dameon was disabled in OS

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 26.5

IBM System x3650 (Intel Xeon X5450)

SPECint\_base2006 = 23.1

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jan-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

## Base Optimization Flags

C benchmarks:

-fast -vec-guard-write -parallel -par-runtime-control

C++ benchmarks:

-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs  
-L/spec/users/rahul/cpu2006.1.0/lib -lsmarheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/cce/10.1.008/bin/icc  
-L/opt/intel/cce/10.1.008/lib  
-I/opt/intel/cce/10.1.008/include

456.hmmer: /opt/intel/cce/10.1.008/bin/icc  
-L/opt/intel/cce/10.1.008/lib  
-I/opt/intel/cce/10.1.008/include

C++ benchmarks:

icpc

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
401.bzip2: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 26.5

IBM System x3650 (Intel Xeon X5450)

SPECint\_base2006 = 23.1

CPU2006 license: 11

Test date: Jan-2008

Test sponsor: IBM Corporation

Hardware Availability: Jan-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

## Peak Optimization Flags (Continued)

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias  
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-auto-ilp32

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo  
-no-prec-div -ansi-alias

456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive  
-auto-ilp32

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch  
-opt-streaming-stores always -vec-guard-write  
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
-no-prec-div -ansi-alias -opt-ra-region-strategy=block  
-Wl,-z,muldefs  
-L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine  
-Wl,-z,muldefs  
-L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation	SPECint2006 =	26.5
-----------------	---------------	------

IBM System x3650 (Intel Xeon X5450)	SPECint_base2006 =	23.1
-------------------------------------	--------------------	------

<b>CPU2006 license:</b> 11	<b>Test date:</b> Jan-2008
<b>Test sponsor:</b> IBM Corporation	<b>Hardware Availability:</b> Jan-2008
<b>Tested by:</b> IBM Corporation	<b>Software Availability:</b> Nov-2007

The flags file that was used to format this result can be browsed at  
<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.14.html>

You can also download the XML flags source by saving the following link:  
<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.14.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
 For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
 Report generated on Tue Jul 22 16:18:00 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
 Originally published on 6 February 2008.