



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint®\_rate2006 = 54.6

IBM System x3500 (Intel Xeon E5405)

SPECint\_rate\_base2006 = 46.1

CPU2006 license: 11


Test date: Feb-2008

Test sponsor: IBM Corporation

Hardware Availability: Jan-2008

Tested by: IBM Corporation

Software Availability: Nov-2007



## Hardware

CPU Name: Intel Xeon E5405  
 CPU Characteristics: 1333MHz system bus  
 CPU MHz: 2000  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores  
 L3 Cache: None  
 Other Cache: None  
 Memory: 16 GB (8 x 2 GB DDR2-5300F ECC)  
 Disk Subsystem: 1 x 80 GB SATA, 7200 RPM  
 Other Hardware: None

## Software

Operating System: SuSE Linux Enterprise Server 10 (x86\_64), Kernel 2.6.16.21-0.8-smp  
 Compiler: Intel C++ Compiler 10.1 for Linux Build 20070913 Package ID: l\_cc\_p\_10.1.008  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Multi-user, run level 3  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: MicroQuill SmartHeap 8.1 Binutils 2.17.50.0.15



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint\_rate2006 = 54.6

IBM System x3500 (Intel Xeon E5405)

SPECint\_rate\_base2006 = 46.1

CPU2006 license: 11

Test date: Feb-2008

Test sponsor: IBM Corporation

Hardware Availability: Jan-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	<b><u>754</u></b>	<b><u>51.9</u></b>	751	52.0	754	51.8	4	621	63.0	625	62.6	<b><u>621</u></b>	<b><u>62.9</u></b>
401.bzip2	4	<b><u>937</u></b>	<b><u>41.2</u></b>	933	41.4	940	41.1	4	875	44.1	<b><u>882</u></b>	<b><u>43.7</u></b>	883	43.7
403.gcc	4	680	47.4	<b><u>687</u></b>	<b><u>46.8</u></b>	697	46.2	4	694	46.4	<b><u>688</u></b>	<b><u>46.8</u></b>	687	46.9
429.mcf	4	782	46.6	<b><u>784</u></b>	<b><u>46.5</u></b>	786	46.4	4	765	47.7	<b><u>764</u></b>	<b><u>47.8</u></b>	760	48.0
445.gobmk	4	793	52.9	799	52.5	<b><u>794</u></b>	<b><u>52.9</u></b>	4	<b><u>742</u></b>	<b><u>56.5</u></b>	731	57.4	744	56.4
456.hmmmer	4	885	42.2	<b><u>884</u></b>	<b><u>42.2</u></b>	884	42.2	4	<b><u>517</u></b>	<b><u>72.2</u></b>	518	72.1	517	72.2
458.sjeng	4	<b><u>987</u></b>	<b><u>49.0</u></b>	991	48.8	985	49.1	4	<b><u>887</u></b>	<b><u>54.6</u></b>	887	54.6	888	54.5
462.libquantum	4	2581	32.1	<b><u>2580</u></b>	<b><u>32.1</u></b>	2569	32.3	1	275	75.3	<b><u>276</u></b>	<b><u>75.2</u></b>	278	74.6
464.h264ref	4	1051	84.2	1053	84.1	<b><u>1051</u></b>	<b><u>84.2</u></b>	4	1001	88.4	<b><u>1002</u></b>	<b><u>88.3</u></b>	1003	88.2
471.omnetpp	4	<b><u>730</u></b>	<b><u>34.2</u></b>	730	34.3	730	34.2	4	689	36.3	692	36.1	<b><u>691</u></b>	<b><u>36.2</u></b>
473.astar	4	<b><u>844</u></b>	<b><u>33.3</u></b>	843	33.3	850	33.1	4	774	36.3	771	36.4	<b><u>772</u></b>	<b><u>36.4</u></b>
483.xalancbmk	4	473	58.3	<b><u>473</u></b>	<b><u>58.3</u></b>	474	58.3	4	473	58.3	<b><u>473</u></b>	<b><u>58.3</u></b>	474	58.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hmmmer, for peak, are compiled in 64-bit mode  
Hardware Sector Prefetch Enabled and Adjacent Sector Prefetch Disabled  
OMP\_NUM\_THREADS set to number of cores  
KMP\_AFFINITY set to physical,0  
KMP\_STACKSIZE set to 64M  
taskset utility used to bind CPU(s) to processes

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint\_rate2006 = 54.6

IBM System x3500 (Intel Xeon E5405)

SPECint\_rate\_base2006 = 46.1

CPU2006 license: 11

Test date: Feb-2008

Test sponsor: IBM Corporation

Hardware Availability: Jan-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

## Base Optimization Flags

C benchmarks:

-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:

-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs  
-L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/cce/10.1.008/bin/icc  
-L/opt/intel/cce/10.1.008/lib  
-I/opt/intel/cce/10.1.008/include

456.hmmer: /opt/intel/cce/10.1.008/bin/icc  
-L/opt/intel/cce/10.1.008/lib  
-I/opt/intel/cce/10.1.008/include

C++ benchmarks:

icpc

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
401.bzip2: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint\_rate2006 = 54.6

IBM System x3500 (Intel Xeon E5405)

SPECint\_rate\_base2006 = 46.1

CPU2006 license: 11

Test date: Feb-2008

Test sponsor: IBM Corporation

Hardware Availability: Jan-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

## Peak Optimization Flags (Continued)

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias  
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo  
-no-prec-div -ansi-alias

456.hmmr: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch  
-opt-streaming-stores always -vec-guard-write  
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
-no-prec-div -ansi-alias -opt-ra-region-strategy=block  
-Wl,-z,muldefs  
-L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine  
-Wl,-z,muldefs  
-L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-INT-ia32-linux-flags.20090714.05.html>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint\_rate2006 = 54.6

IBM System x3500 (Intel Xeon E5405)

SPECint\_rate\_base2006 = 46.1

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Feb-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-INT-ia32-linux-flags.20090714.05.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 15:42:15 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 5 March 2008.