SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel Desktop Board DQ35JO (Intel Core 2 Duo E8200)

SPECint®_rate2006 = 36.8

SPECint_rate_base2006 = 33.8

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Feb-2008
Hardware Availability: Feb-2008
Software Availability: Nov-2007



Hardware

CPU Name:	Intel Core 2 Duo E8200
CPU Characteristics:	2.66 GHz, 1333 FSB
CPU MHz:	2667
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	6 MB I+D on chip per chip
L3 Cache:	None
Other Cache:	None
Memory:	2 GB (2x1GB Micron DDR2-800 CL5)
Disk Subsystem:	Seagate 320GB NCQ SATA, 16MB cache, 7200 RPM
Other Hardware:	None

Software

Operating System:	Windows Vista Ultimate (64-bit)
Compiler:	Intel C++ Compiler for IA32 version 10.1 Build 20070913 Package ID: w_cc_p_10.1.011 Microsoft Visual Studio 2005 SP1 (for libraries)
Auto Parallel:	Yes
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	SmartHeap Library Version 8.1 from http://www.microquill.com/

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel Desktop Board DQ35JO (Intel Core 2 Duo E8200)

SPECint_rate2006 = 36.8

SPECint_rate_base2006 = 33.8

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Feb-2008
Hardware Availability: Feb-2008
Software Availability: Nov-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	2	605	32.3	608	32.1	**606**	**32.2**	2	**460**	**42.5**	462	42.3	459	42.5
401.bzip2	2	**694**	**27.8**	695	27.8	691	27.9	2	671	28.8	**671**	**28.7**	673	28.7
403.gcc	2	494	32.6	500	32.2	**498**	**32.3**	2	481	33.5	480	33.6	**481**	**33.5**
429.mcf	2	425	42.9	427	42.7	**426**	**42.8**	2	432	42.2	**431**	**42.3**	431	42.3
445.gobmk	2	**589**	**35.6**	589	35.6	588	35.7	2	539	38.9	**539**	**38.9**	540	38.9
456.hmmer	2	**670**	**27.9**	670	27.9	670	27.8	2	619	30.2	**618**	**30.2**	618	30.2
458.sjeng	2	**758**	**31.9**	758	31.9	758	31.9	2	671	36.1	**671**	**36.1**	671	36.1
462.libquantum	2	**990**	**41.8**	985	42.1	993	41.7	1	436	47.5	435	47.6	**436**	**47.5**
464.h264ref	2	**803**	**55.1**	803	55.1	803	55.1	2	**762**	**58.1**	762	58.1	762	58.1
471.omnetpp	2	460	27.2	**460**	**27.2**	461	27.1	2	**428**	**29.2**	427	29.3	428	29.2
473.astar	2	580	24.2	**580**	**24.2**	580	24.2	2	**527**	**26.6**	527	26.6	527	26.6
483.xalancbmk	2	369	37.4	**369**	**37.4**	368	37.5	2	**355**	**38.8**	355	38.9	356	38.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply
Product description located as of 03/2008:
http://www.intel.com/products/motherboard/DQ35JO/index.htm
The system bus runs at 1333 MHz
System was configured with Asus EN8800GTX discrete graphics card
Binaries were built on Windows Vista Ultimate (32-bit)
The following VS 2005 SP1 updates were applied: KB926601 and KB932232
OMP_NUM_THREADS was set to number of logical processors as seen by the OS
KMP_AFFINITY was set to physical,0
submit was disabled for 462.libquantum at peak.
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc8 -Qc99
```

C++ benchmarks:

```
icl -Qvc8
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Continued on next page

Base Portability Flags (Continued)

483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Base Optimization Flags

C benchmarks:
`-fast -Qvec-guard-write /F512000000`

C++ benchmarks:
`-fast -Qcxx_features /F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks:
`icl -Qvc8 -Qc99`

C++ benchmarks:
`icl -Qvc8`

Peak Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`
483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Peak Optimization Flags

C benchmarks:

400.perlbench: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast -Qansi-alias -Qprefetch /F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

Continued on next page

Peak Optimization Flags (Continued)

401.bzip2: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qprefetch /F512000000

403.gcc: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000

429.mcf: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qprefetch /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

445.gobmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxT -O2 -Qipo -Qprec-div- -Qansi-alias /F512000000

456.hmmer: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll2 -Qansi-alias -Qopt-multi-version-aggressive /F512000000

458.sjeng: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll4 /F512000000

462.libquantum: -fast -Qunroll4 -Ob0 -Qprefetch -Qopt-streaming-stores:always -Qparallel -Qpar-runtime-control /F512000000

464.h264ref: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll2 -Qansi-alias /F512000000

C++ benchmarks:

471.omnetpp: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias -Qopt-ra-region-strategy=block -Qcxx_features /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

473.astar: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias -Qopt-ra-region-strategy=routine -Qcxx_features /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

483.xalancbmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias -Qcxx_features /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic10.1-win32-flags.html

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic10.1-win32-flags.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 15:27:35 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 19 March 2008.