



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited

SPECfp®2006 = 24.6

Fujitsu SPARC Enterprise M8000

SPECfp\_base2006 = 21.7

CPU2006 license: 6


Test sponsor: Fujitsu Limited

Tested by: Sun Microsystems

Test date: Feb-2008

Hardware Availability: Apr-2007

Software Availability: May-2008



## Hardware

CPU Name: SPARC64 VI  
 CPU Characteristics:  
 CPU MHz: 2400  
 FPU: Integrated  
 CPU(s) enabled: 32 cores, 16 chips, 2 cores/chip, 2 threads/core  
 CPU(s) orderable: 1 to 4 CMUs; each CMU contains 2 or 4 chips  
 Primary Cache: 128 KB I + 128 KB D on chip per core  
 Secondary Cache: 6 MB I+D on chip per chip

Continued on next page

## Software

Operating System: Solaris 10 5/08 s10s\_u5wos\_08  
 Compiler: Sun Studio 12, Patch 124867-02  
 (see patch info below)  
 Auto Parallel: Yes  
 File System: ufs  
 System State: Default  
 Base Pointers: 32-bit  
 Peak Pointers: 32-bit

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited

SPECfp2006 = 24.6

Fujitsu SPARC Enterprise M8000

SPECfp\_base2006 = 21.7

CPU2006 license: 6

Test sponsor: Fujitsu Limited

Tested by: Sun Microsystems

Test date: Feb-2008

Hardware Availability: Apr-2007

Software Availability: May-2008

L3 Cache: None  
Other Cache: None  
Memory: 256 GB (128 x 2 GB DIMMs)  
Disk Subsystem: 408 GB SVM RAID 1+0 on 12 x 73 GB  
10,000 RPM Fujitsu MAY2073RC SAS  
Other Hardware: None

Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	38.5	353	37.7	360	<b>38.5</b>	<b>353</b>	<b>32.5</b>	<b>418</b>	32.5	418	32.5	418
416.gamess	1874	10.4	<b>1873</b>	<b>10.5</b>	1872	10.5	1833	10.7	1833	10.7	<b>1833</b>	<b>10.7</b>
433.milc	1205	7.62	1215	7.56	<b>1211</b>	<b>7.58</b>	826	11.1	<b>826</b>	<b>11.1</b>	836	11.0
434.zeusmp	<b>1039</b>	<b>8.76</b>	1039	8.76	1039	8.76	1039	8.76	<b>1039</b>	<b>8.76</b>	1040	8.75
435.gromacs	684	10.4	683	10.5	<b>683</b>	<b>10.5</b>	619	11.5	615	11.6	<b>616</b>	<b>11.6</b>
436.cactusADM	52.7	227	51.9	230	<b>52.1</b>	<b>230</b>	53.1	225	51.2	233	<b>51.7</b>	<b>231</b>
437.leslie3d	<b>257</b>	<b>36.5</b>	256	36.7	258	36.5	210	44.8	208	45.2	<b>209</b>	<b>45.0</b>
444.namd	<b>729</b>	<b>11.0</b>	729	11.0	730	11.0	710	11.3	710	11.3	<b>710</b>	<b>11.3</b>
447.dealII	<b>845</b>	<b>13.5</b>	844	13.5	875	13.1	<b>793</b>	<b>14.4</b>	798	14.3	793	14.4
450.soplex	<b>1084</b>	<b>7.70</b>	1083	7.70	1084	7.69	910	9.17	917	9.09	<b>916</b>	<b>9.10</b>
453.povray	523	10.2	519	10.3	<b>521</b>	<b>10.2</b>	370	14.4	<b>372</b>	<b>14.3</b>	373	14.3
454.calculix	653	12.6	<b>654</b>	<b>12.6</b>	654	12.6	634	13.0	<b>633</b>	<b>13.0</b>	632	13.1
459.GemsFDTD	246	43.1	245	43.3	<b>245</b>	<b>43.3</b>	246	43.1	245	43.3	<b>245</b>	<b>43.3</b>
465.tonto	1134	8.68	1138	8.64	<b>1136</b>	<b>8.66</b>	<b>693</b>	<b>14.2</b>	693	14.2	696	14.1
470.lbm	57.7	238	<b>57.5</b>	<b>239</b>	57.5	239	56.0	245	55.8	246	<b>55.9</b>	<b>246</b>
481.wrf	<b>707</b>	<b>15.8</b>	708	15.8	705	15.8	<b>707</b>	<b>15.8</b>	708	15.8	705	15.8
482.sphinx3	1704	11.4	1700	11.5	<b>1703</b>	<b>11.4</b>	1539	12.7	<b>1541</b>	<b>12.6</b>	1565	12.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

Sun Studio compiler patches are available at  
[http://developers.sun.com/sunstudio/downloads/patches/ss12\\_patches.jsp](http://developers.sun.com/sunstudio/downloads/patches/ss12_patches.jsp)  
The tested configuration included patch 124867-02, 124861-04,  
124863-02, and 127000-02

## Operating System Notes

Stack size set to unlimited via "ulimit -s unlimited"

Program threads were bound to processors with:  
Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited

SPECfp2006 = 24.6

Fujitsu SPARC Enterprise M8000

SPECfp\_base2006 = 21.7

CPU2006 license: 6

Test sponsor: Fujitsu Limited

Tested by: Sun Microsystems

Test date: Feb-2008

Hardware Availability: Apr-2007

Software Availability: May-2008

## Operating System Notes (Continued)

```
SUNW_MP_PROCBIND="1 3 5 7 9 11 13 15 17 19 21 23 25 27 29 31 33 35 37
39 41 43 45 47 49 51 53 55 57 59 61 63"
```

Behavior of parallel threads was set with:

```
SUNW_MP_THR_IDLE=SPIN
```

SPIN specifies that an idle thread should spin while waiting at barrier or waiting for new parallel regions to work on.

The maximum number of threads a program can create was set with:

```
OMP_NUM_THREADS=32
```

System Tunables:

```
(/etc/system parameters)
```

```
maxphys=4194304
```

Defines the maximum size of I/O requests, in bytes.

```
maxpgio=1024
```

Defines the maximum number of page I/O requests that can be queued by the paging system.

```
tune_t_fsflushr=4
```

Controls how many seconds elapse between runs of the page flush daemon, fsflush.

```
autoup=60
```

Causes pages older than the listed number of seconds to be written by fsflush.

```
bufhwm=3000
```

Memory byte limit for caching I/O buffers

```
segmap_percent=1
```

Set maximum percent memory for file system cache

## Platform Notes

This result is measured on a Sun SPARC Enterprise M8000 Server. Note that the Sun SPARC Enterprise M8000 and Fujitsu SPARC Enterprise M8000 are electrically equivalent.

Memory is 8-way interleaved by filling all slots with the same capacity DIMMs.

## Base Compiler Invocation

C benchmarks:

```
cc
```

C++ benchmarks:

```
CC
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

<b>Fujitsu Limited</b>	<b>SPECfp2006 =</b>	<b>24.6</b>
<b>Fujitsu SPARC Enterprise M8000</b>	<b>SPECfp_base2006 =</b>	<b>21.7</b>

<b>CPU2006 license:</b> 6	<b>Test date:</b> Feb-2008
<b>Test sponsor:</b> Fujitsu Limited	<b>Hardware Availability:</b> Apr-2007
<b>Tested by:</b> Sun Microsystems	<b>Software Availability:</b> May-2008

## Base Compiler Invocation (Continued)

Fortran benchmarks:  
f90

Benchmarks using both Fortran and C:  
cc f90

## Base Optimization Flags

C benchmarks:  
-fast -xipo=2 -fma=fused -xpagesize=4M -xprefetch=latx:2 -xautopar  
-xreduction -xprefetch\_level=3  
-xprefetch\_auto\_type=indirect\_array\_access

C++ benchmarks:  
-library=stlport4 -fast -xipo=2 -fma=fused -xpagesize=4M  
-xprefetch=latx:2 -xautopar -xreduction -xprefetch\_level=2  
-xalias\_level=compatible

Fortran benchmarks:  
-fast -xipo=2 -fma=fused -xpagesize=4M -xprefetch=latx:2 -xautopar  
-xreduction -xprefetch\_level=2

Benchmarks using both Fortran and C:  
-fast(cc) -fast(f90) -xipo=2 -fma=fused -xpagesize=4M  
-xprefetch=latx:2 -xautopar -xreduction -xprefetch\_level=3  
-xprefetch\_auto\_type=indirect\_array\_access -xprefetch\_level=2

## Base Other Flags

C benchmarks:  
-xjobs=64

C++ benchmarks:  
-xjobs=64

Fortran benchmarks:  
-xjobs=64

Benchmarks using both Fortran and C:  
-xjobs=64



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited

SPECfp2006 = 24.6

Fujitsu SPARC Enterprise M8000

SPECfp\_base2006 = 21.7

CPU2006 license: 6

Test date: Feb-2008

Test sponsor: Fujitsu Limited

Hardware Availability: Apr-2007

Tested by: Sun Microsystems

Software Availability: May-2008

## Peak Compiler Invocation

C benchmarks:

cc

C++ benchmarks:

CC

Fortran benchmarks:

f90

Benchmarks using both Fortran and C:

cc f90

## Peak Optimization Flags

C benchmarks:

```
433.milc: -fast -xipo=2 -fma=fused -xpagesize=4M -xprefetch=latx:2
-xalias_level=std -xprefetch_level=3
-xprefetch_auto_type=indirect_array_access
-xalias_level=strong -xprefetch_level=2
```

```
470.lbm: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -fma=fused
-xpagesize=4M -xprefetch=latx:2 -xalias_level=std
-xprefetch_level=3 -xprefetch_auto_type=indirect_array_access
-xarch=v8plusb -xprefetch_level=2 -xautopar -xreduction
```

```
482.sphinx3: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -fma=fused
-xalias_level=std
```

C++ benchmarks:

```
444.namd: -library=stlport4 -fast -xipo=2 -fma=fused -xpagesize=4M
-xprefetch=latx:2 -xalias_level=compatible -xdepend
```

```
447.deallI: -library=stlport4 -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -fma=fused
-xalias_level=compatible -xdepend -xrestrict
-xprefetch=latx:4.5
```

```
450.soplex: -library=stlport4 -fast -xipo=2 -fma=fused -xpagesize=4M
-xprefetch=latx:2 -xdepend -xprefetch_level=2
-xprefetch_auto_type=indirect_array_access
-Qoption cg -Qlp-ol=1 -Qoption cg -Qlp-it=3
-Qoption cg -Qlp-imb=1 -Qoption iropt -Apf:pdl=3
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited

SPECfp2006 = 24.6

Fujitsu SPARC Enterprise M8000

SPECfp\_base2006 = 21.7

CPU2006 license: 6

Test date: Feb-2008

Test sponsor: Fujitsu Limited

Hardware Availability: Apr-2007

Tested by: Sun Microsystems

Software Availability: May-2008

## Peak Optimization Flags (Continued)

453.povray: -library=stlport4 -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -fma=fused  
-xpagesize=4M -xprefetch=latx:2 -xalias\_level=compatible  
-xdepend -xrestrict -xprefetch=latx:4.5

Fortran benchmarks:

410.bwaves: -fast -xipo=2 -fma=fused -xpagesize=512K -xprefetch=latx:2  
-xprefetch\_level=2 -xautopar -xreduction

416.gamess: -fast -xipo=2 -fma=fused -xpagesize=4M -xprefetch=latx:2  
-xprefetch\_level=2

434.zeusmp: -fast -xipo=2 -fma=fused -xpagesize=4M -xprefetch=latx:2  
-xautopar -xreduction

437.leslie3d: -fast -xipo=2 -xautopar -xreduction -fma=fused  
-xprefetch\_level=2 -xprefetch=latx:8.0

459.GemsFDTD: basepeak = yes

465.tonto: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -fma=fused  
-xpagesize=4M -xprefetch=latx:2 -xarch=v8plusa  
-xprefetch=latx:12 -lfast

Benchmarks using both Fortran and C:

435.gromacs: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast(cc) -fast(f90)  
-xipo=2 -fma=fused -xalias\_level=std

436.cactusADM: -fast(cc) -fast(f90) -xipo=2 -fma=fused -xpagesize=4M  
-xprefetch=latx:2 -xalias\_level=std -xprefetch\_level=3  
-xprefetch\_auto\_type=indirect\_array\_access -xautopar  
-xreduction

454.calculix: -fast(cc) -fast(f90) -xipo=2 -fma=fused -xalias\_level=std

481.wrf: basepeak = yes

## Peak Other Flags

C benchmarks:

-xjobs=64

C++ benchmarks:

-xjobs=64

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited	SPECfp2006 =	24.6
Fujitsu SPARC Enterprise M8000	SPECfp_base2006 =	21.7

CPU2006 license: 6

Test sponsor: Fujitsu Limited

Tested by: Sun Microsystems

Test date: Feb-2008

Hardware Availability: Apr-2007

Software Availability: May-2008

## Peak Other Flags (Continued)

Fortran benchmarks:  
-xjobs=64

Benchmarks using both Fortran and C:  
-xjobs=64

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12-and-gccfss4.2.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12-and-gccfss4.2.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.1.  
Report generated on Tue Jul 22 16:39:59 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 24 March 2008.