



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 42.4

Acer Altos R720 (Intel Xeon X5260)

SPECint_rate_base2006 = 37.0

CPU2006 license: 97


Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Mar-2008

Hardware Availability: Nov-2007

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon X5260
CPU Characteristics: 1333MHz system bus
CPU MHz: 3333
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1, 2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 6 MB I+D on chip per chip
L3 Cache: None
Other Cache: None
Memory: 16 GB (8 x 2048MB ECC FB-DIMM DDR2-667 CL5-5-5)
Disk Subsystem: 1 x 73GB 10000PRM SAS HDD
Other Hardware: None

Software

Operating System: SuSE Linux Enterprise Server 10 SP1 (x86_64)
Compiler: Kernel 2.6.16.46-0.12-smp
Auto Parallel: Intel C++ Compiler 10.1 for Linux
File System: Build 20070913 Package ID: l_cc_p_10.1.008
System State: Yes
Base Pointers: ReiserFS
Peak Pointers: Multi-user, level 3
Other Software: 32-bit
Microquill SmartHeap V8.1
Binutils 2.17.50.0.15



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 42.4

Acer Altos R720 (Intel Xeon X5260)

SPECint_rate_base2006 = 37.0

CPU2006 license: 97

Test date: Mar-2008

Test sponsor: Acer Incorporated

Hardware Availability: Nov-2007

Tested by: Acer Incorporated

Software Availability: Nov-2007

Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|----------------|--------|------------|-------------|------------|-------------|-------------|-------------|--------|------------|-------------|------------|-------------|------------|-------------|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 400.perlbench | 2 | 464 | 42.1 | 466 | 41.9 | 466 | 41.9 | 2 | 385 | 50.7 | 388 | 50.3 | 386 | 50.7 |
| 401.bzip2 | 2 | 629 | 30.7 | 630 | 30.6 | 630 | 30.6 | 2 | 602 | 32.0 | 595 | 32.4 | 602 | 32.0 |
| 403.gcc | 2 | 480 | 33.5 | 479 | 33.6 | 477 | 33.7 | 2 | 479 | 33.6 | 484 | 33.3 | 479 | 33.6 |
| 429.mcf | 2 | 506 | 36.0 | 509 | 35.8 | 508 | 35.9 | 2 | 506 | 36.1 | 506 | 36.1 | 507 | 36.0 |
| 445.gobmk | 2 | 493 | 42.6 | 493 | 42.5 | 485 | 43.2 | 2 | 448 | 46.8 | 451 | 46.5 | 448 | 46.8 |
| 456.hammer | 2 | 531 | 35.2 | 530 | 35.2 | 531 | 35.1 | 2 | 308 | 60.6 | 307 | 60.7 | 308 | 60.6 |
| 458.sjeng | 2 | 621 | 39.0 | 620 | 39.1 | 623 | 38.9 | 2 | 568 | 42.6 | 566 | 42.7 | 564 | 42.9 |
| 462.libquantum | 2 | 1187 | 34.9 | 1188 | 34.9 | 1187 | 34.9 | 1 | 376 | 55.2 | 377 | 54.9 | 376 | 55.2 |
| 464.h264ref | 2 | 635 | 69.7 | 632 | 70.0 | 633 | 69.9 | 2 | 604 | 73.3 | 604 | 73.3 | 605 | 73.1 |
| 471.omnetpp | 2 | 511 | 24.5 | 512 | 24.4 | 512 | 24.4 | 2 | 479 | 26.1 | 478 | 26.2 | 478 | 26.2 |
| 473.astar | 2 | 515 | 27.3 | 516 | 27.2 | 516 | 27.2 | 2 | 477 | 29.4 | 477 | 29.5 | 477 | 29.4 |
| 483.xalancbmk | 2 | 305 | 45.3 | 304 | 45.4 | 304 | 45.4 | 2 | 305 | 45.3 | 304 | 45.4 | 304 | 45.4 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

This result was measured on the Acer Altos R520.

The Altos R720 and Altos R520 are electronically equivalent.

All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hammer, for peak, are compiled in 64-bit mode

BIOS Settings

Hardware Prefetcher set to ON

Adjacent Cache Line Prefetch set to ON

All results but peak 462.libquantum used taskset to bind processes to cores.

"ulimit -s unlimited" was set for stacksize unlimited
OMP_NUM_THREADS set to number of cores

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 42.4

Acer Altos R720 (Intel Xeon X5260)

SPECint_rate_base2006 = 37.0

CPU2006 license: 97

Test date: Mar-2008

Test sponsor: Acer Incorporated

Hardware Availability: Nov-2007

Tested by: Acer Incorporated

Software Availability: Nov-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:

-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

456.hmmr: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

C++ benchmarks:

icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmr: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 42.4

Acer Altos R720 (Intel Xeon X5260)

SPECint_rate_base2006 = 37.0

CPU2006 license: 97

Test date: Mar-2008

Test sponsor: Acer Incorporated

Hardware Availability: Nov-2007

Tested by: Acer Incorporated

Software Availability: Nov-2007

Peak Portability Flags (Continued)

483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo
-no-prec-div -ansi-alias

456.hmmer: -fast -unroll12 -ansi-alias -opt-multi-version-aggressive

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll14 -Ob0 -prefetch
-opt-streaming-stores always -vec-guard-write
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=block
-Wl,-z,muldefs
-L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine
-Wl,-z,muldefs
-L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

483.xalancbmk: basepeak = yes



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 42.4

Acer Altos R720 (Intel Xeon X5260)

SPECint_rate_base2006 = 37.0

CPU2006 license: 97

Test date: Mar-2008

Test sponsor: Acer Incorporated

Hardware Availability: Nov-2007

Tested by: Acer Incorporated

Software Availability: Nov-2007

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-int-linux64-revC.20090713.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-int-linux64-revC.20090713.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 18:09:12 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 9 April 2008.