



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint®_rate2006 = 59.9

PowerEdge R200 (Intel Xeon X3320, 2.50 GHz)

SPECint_rate_base2006 = 53.4

CPU2006 license: 55


Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Mar-2008

Hardware Availability: Mar-2008

Software Availability: Nov-2007



SPECint_rate_base2006 = 53.4

SPECint_rate2006 = 59.9

Hardware

CPU Name: Intel Xeon X3320
CPU Characteristics: 1333 MHz system bus
CPU MHz: 2500
FPU: Integrated
CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
CPU(s) orderable: 1 chip
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 6 MB I+D on chip per chip, 3 MB shared / 2 cores
L3 Cache: None
Other Cache: None
Memory: 8 GB (4 x 2GB 800MHz DDR2)
Disk Subsystem: 1 x 750 GB 7200 RPM SATA
Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
Compiler: Intel C++ Compiler for Linux32 and Linux64 version 10.1 Build 20070725
Auto Parallel: Yes
File System: ReiserFS
System State: Run level 3 (multi-user)
Base Pointers: 32-bit
Peak Pointers: 32/64-bit
Other Software: Microquill SmartHeap library V8.1



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint_rate2006 = 59.9

PowerEdge R200 (Intel Xeon X3320, 2.50 GHz)

SPECint_rate_base2006 = 53.4

CPU2006 license: 55

Test date: Mar-2008

Test sponsor: Dell Inc.

Hardware Availability: Mar-2008

Tested by: Dell Inc.

Software Availability: Nov-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	617	63.3	606	64.4	606	64.5	4	519	75.3	513	76.2	520	75.1
401.bzip2	4	961	40.2	957	40.3	957	40.3	4	915	42.2	913	42.3	912	42.3
403.gcc	4	633	50.9	634	50.8	642	50.1	4	636	50.6	639	50.4	636	50.6
429.mcf	4	742	49.2	742	49.1	742	49.2	4	768	47.5	767	47.6	769	47.4
445.gobmk	4	633	66.3	635	66.1	633	66.3	4	591	71.0	590	71.1	591	71.0
456.hammer	4	722	51.7	723	51.6	725	51.5	4	433	86.1	432	86.4	431	86.5
458.sjeng	4	786	61.6	786	61.6	786	61.6	4	710	68.2	710	68.2	709	68.3
462.libquantum	4	2060	40.2	2059	40.3	2060	40.2	1	360	57.5	361	57.4	360	57.5
464.h264ref	4	868	102	866	102	868	102	4	831	107	830	107	831	106
471.omnetpp	4	632	39.6	636	39.3	632	39.5	4	603	41.4	603	41.4	603	41.4
473.astar	4	733	38.3	733	38.3	731	38.4	4	676	41.5	674	41.7	675	41.6
483.xalancbmk	4	440	62.8	441	62.6	440	62.7	4	440	62.8	441	62.6	440	62.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

OMP_NUM_THREADS set to number of cores

KMP_STACK_SIZE set to 64M

KMP_AFFINITY set to physical,0

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs

Platform Notes

BIOS Settings:

Adjacent Cache Line Prefetch = Disabled (default Enabled)

Hardware Prefetcher = Disabled (default Enabled)

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R200 (Intel Xeon X3320, 2.50 GHz)

SPECint_rate2006 = 59.9

CPU2006 license: 55

Test date: Mar-2008

Test sponsor: Dell Inc.

Hardware Availability: Mar-2008

Tested by: Dell Inc.

Software Availability: Nov-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:

-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/home/cmpllr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc
-L/home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib
-I/home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include

456.hmmr: /home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc
-L/home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib
-I/home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include

C++ benchmarks:

icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmr: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint_rate2006 = 59.9

PowerEdge R200 (Intel Xeon X3320, 2.50 GHz)

SPECint_rate_base2006 = 53.4

CPU2006 license: 55

Test date: Mar-2008

Test sponsor: Dell Inc.

Hardware Availability: Mar-2008

Tested by: Dell Inc.

Software Availability: Nov-2007

Peak Portability Flags (Continued)

483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias  
                  -prefetch  
  
401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
  
403.gcc: -fast -inline-calloc -opt-malloc-options=3  
  
429.mcf: -fast -prefetch  
  
445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo  
                  -no-prec-div -ansi-alias  
  
456.hmmer: -fast -unroll12 -ansi-alias -opt-multi-version-aggressive  
  
458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
  
462.libquantum: -fast -unroll14 -O0 -prefetch  
                  -opt-streaming-stores always -vec-guard-write  
                  -opt-malloc-options=3 -parallel -par-runtime-control  
  
464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12  
                  -ansi-alias
```

C++ benchmarks:

```
471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
                  -no-prec-div -ansi-alias -opt-ra-region-strategy=block  
                  -Wl,-z,muldefs  
                  -L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap  
  
473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
                  -no-prec-div -ansi-alias -opt-ra-region-strategy=routine  
                  -Wl,-z,muldefs  
                  -L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap
```

483.xalancbmk: basepeak = yes



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint_rate2006 = 59.9

PowerEdge R200 (Intel Xeon X3320, 2.50 GHz)

SPECint_rate_base2006 = 53.4

CPU2006 license: 55

Test date: Mar-2008

Test sponsor: Dell Inc.

Hardware Availability: Mar-2008

Tested by: Dell Inc.

Software Availability: Nov-2007

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090713.03.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090713.03.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 18:18:00 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 15 April 2008.