# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale T810 E1
(Intel Xeon E3110, 3.00 GHz)

SPECfp®_rate2006 = 34.3

SPECfp_rate_base2006 = 31.7

**CPU2006 license:** 20
**Test sponsor:** Bull SAS
**Tested by:** Bull SAS

**Test date:** May-2008
**Hardware Availability:** Jan-2008
**Software Availability:** Nov-2007




### Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon E3110 |
| CPU Characteristics: | 1333 MHz system bus |
| CPU MHz: | 3000 |
| FPU: | Integrated |
| CPU(s) enabled: | 2 cores, 1 chip, 2 cores/chip |
| CPU(s) orderable: | 1 chip |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 6 MB I+D on chip per chip |

Continued on next page

### Software

| | |
|---|---|
| Operating System: | SUSE LINUX Enterprise Server 10 SP1<br>Kernel 2.6.16.46-0.12-smp for x86_64 |
| Compiler: | Intel C++ and Fortran Compiler 10.1 for Linux<br>Build 20070913 Package ID: l_cc_p_10.1.008,<br>l_fc_p_10.1.008 |
| Auto Parallel: | Yes |
| File System: | ext2 |
| System State: | Run level 3 (multi-user) |
| Base Pointers: | 64-bit |

Continued on next page

# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale T810 E1
(Intel Xeon E3110, 3.00 GHz)

SPECfp_rate2006 = 34.3

SPECfp_rate_base2006 = 31.7

**CPU2006 license:** 20
**Test sponsor:** Bull SAS
**Tested by:** Bull SAS

**Test date:** May-2008
**Hardware Availability:** Jan-2008
**Software Availability:** Nov-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8x2 GB) FB-DIMM PC2-6400E ECC CL6
Disk Subsystem: 1x80 GB SATA, 7200 RPM
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: Binutils 2.17.50.0.15

## Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 2 | 842 | 32.3 | 847 | 32.1 | **843** | **32.2** | 2 | **837** | **32.5** | 835 | 32.5 | 837 | 32.5 |
| 416.gamess | 2 | 886 | 44.2 | 889 | 44.0 | **889** | **44.1** | 2 | **877** | **44.7** | 875 | 44.8 | 877 | 44.7 |
| 433.milc | 2 | **975** | **18.8** | 979 | 18.7 | 975 | 18.8 | 2 | **972** | **18.9** | 972 | 18.9 | 971 | 18.9 |
| 434.zeusmp | 2 | 518 | 35.2 | **517** | **35.2** | 516 | 35.2 | 2 | **515** | **35.3** | 515 | 35.3 | 515 | 35.3 |
| 435.gromacs | 2 | 370 | 38.6 | 370 | 38.6 | **370** | **38.6** | 2 | **368** | **38.8** | 371 | 38.5 | 367 | 38.9 |
| 436.cactusADM | 2 | 633 | 37.8 | 633 | 37.8 | **633** | **37.8** | 1 | **298** | **40.2** | 294 | 40.7 | 298 | 40.0 |
| 437.leslie3d | 2 | 882 | 21.3 | 858 | 21.9 | **881** | **21.3** | 2 | 878 | 21.4 | **879** | **21.4** | 880 | 21.4 |
| 444.namd | 2 | 506 | 31.7 | **505** | **31.7** | 504 | 31.8 | 2 | 502 | 32.0 | 502 | 32.0 | **502** | **32.0** |
| 447.dealII | 2 | 417 | 54.9 | 416 | 55.0 | **417** | **54.9** | 2 | 394 | 58.1 | **397** | **57.7** | 401 | 57.0 |
| 450.soplex | 2 | 687 | 24.3 | **688** | **24.3** | 692 | 24.1 | 2 | 626 | 26.6 | 622 | 26.8 | **626** | **26.7** |
| 453.povray | 2 | 211 | 50.4 | 212 | 50.1 | **211** | **50.4** | 2 | 180 | 59.1 | **181** | **58.9** | 181 | 58.8 |
| 454.calculix | 2 | 503 | 32.8 | **503** | **32.8** | 503 | 32.8 | 2 | 345 | 47.8 | 350 | 47.1 | **346** | **47.7** |
| 459.GemsFDTD | 2 | 1126 | 18.8 | **1149** | **18.5** | 1154 | 18.4 | 2 | 1104 | 19.2 | 1107 | 19.2 | **1106** | **19.2** |
| 465.tonto | 2 | 489 | 40.2 | **491** | **40.1** | 493 | 39.9 | 2 | 476 | 41.4 | **474** | **41.6** | 473 | 41.6 |
| 470.lbm | 2 | **1695** | **16.2** | 1694 | 16.2 | 1696 | 16.2 | 1 | 553 | 24.9 | **555** | **24.8** | 557 | 24.7 |
| 481.wrf | 2 | 609 | 36.7 | 609 | 36.7 | **609** | **36.7** | 2 | 609 | 36.7 | 608 | 36.8 | **608** | **36.7** |
| 482.sphinx3 | 2 | 1064 | 36.6 | **1066** | **36.6** | 1068 | 36.5 | 2 | **994** | **39.2** | 993 | 39.2 | 997 | 39.1 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
 OMP_NUM_THREADS set to number of cores
 KMP_AFFINITY set to physical,0
 KMP_STACKSIZE set to 64M
```

## General Notes

```
All benchmarks compiled in 64-bit mode except 450.soplex,
470.lbm and 482.sphinx3, at peak, are compiled in 32-bit mode

The Bull NovaScale T810 E1(Intel Xeon E3110, 3.00 GHz),
the Bull NovaScale T830 E1(Intel Xeon E3110, 3.00 GHz) and
the Bull NovaScale R410 E1(Intel Xeon E3110, 3.00 GHz) models are electronically equivalent.
The results have been measured on a Bull NovaScale T810 E1(Intel Xeon E3110, 3.00 GHz) model.
```

## Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

## Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

## Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:
-fast

## Peak Compiler Invocation

C benchmarks (except as noted below):
`/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib -I/opt/intel/cc/10.1.008/include`

433.milc: `icc`

C++ benchmarks (except as noted below):
`icpc`

450.soplex: `/opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib -I/opt/intel/cc/10.1.008/include`

Fortran benchmarks (except as noted below):
`ifort`

437.leslie3d: `/opt/intel/fc/10.1.008/bin/ifort -L/opt/intel/fc/10.1.008/lib -I/opt/intel/fc/10.1.008/include`

Benchmarks using both Fortran and C:
`icc ifort`

## Peak Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`
416.gamess: `-DSPEC_CPU_LP64`
433.milc: `-DSPEC_CPU_LP64`
434.zeusmp: `-DSPEC_CPU_LP64`
435.gromacs: `-DSPEC_CPU_LP64 -nofor_main`
436.cactusADM: `-DSPEC_CPU_LP64 -nofor_main`
444.namd: `-DSPEC_CPU_LP64`
447.dealII: `-DSPEC_CPU_LP64`
453.povray: `-DSPEC_CPU_LP64`
454.calculix: `-DSPEC_CPU_LP64 -nofor_main`
459.GemsFDTD: `-DSPEC_CPU_LP64`
465.tonto: `-DSPEC_CPU_LP64`
481.wrf: `-DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX`

## Peak Optimization Flags

C benchmarks:

433.milc: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -fno-alias -auto-ilp32`

470.lbm: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll2 -scalar-rep- -prefetch -opt-malloc-options=3`

Continued on next page

# Peak Optimization Flags (Continued)

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias -auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast -opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch -opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0 -prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch -auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/EM64T_Intel101_fp_flags.20090713.00.html

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale T810 E1
(Intel Xeon E3110, 3.00 GHz)

SPECfp_rate2006 = 34.3

SPECfp_rate_base2006 = 31.7

**CPU2006 license:** 20
**Test sponsor:** Bull SAS
**Tested by:** Bull SAS

**Test date:** May-2008
**Hardware Availability:** Jan-2008
**Software Availability:** Nov-2007

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/EM64T_Intel101_fp_flags.20090713.00.xml`

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 19:49:35 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 July 2008.