



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

**SPECint®2006 = 14.0**

### IBM BladeCenter LS42 (AMD Opteron 8356)

**SPECint\_base2006 = 12.5**

CPU2006 license: 11


Test date: Aug-2008

Test sponsor: IBM Corporation

Hardware Availability: Sep-2008

Tested by: IBM Corporation

Software Availability: May-2008



### Hardware

CPU Name: AMD Opteron 8356  
 CPU Characteristics:  
 CPU MHz: 2300  
 FPU: Integrated  
 CPU(s) enabled: 16 cores, 4 chips, 4 cores/chip  
 CPU(s) orderable: 1,2,3,4 chips  
 Primary Cache: 64 KB I + 64 KB D on chip per core  
 Secondary Cache: 512 KB I+D on chip per core  
 L3 Cache: 2 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 64 GB (16 x 4 GB DDR2-6400 ECC)  
 Disk Subsystem: 1 x 73 GB SAS, 10000 RPM  
 Other Hardware: None

### Software

Operating System: SuSE Linux Enterprise Server 10 (x86\_64) SP1, Kernel 2.6.16.46-0.12-smp  
 Compiler: PGI Server Complete Version 7.2  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Run level 3 (Full multiuser with network)  
 Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: SmartHeap 8.1 32-bit Library for Linux binutils 2.18.50



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 14.0

IBM BladeCenter LS42 (AMD Opteron 8356)

SPECint\_base2006 = 12.5

CPU2006 license: 11

Test date: Aug-2008

Test sponsor: IBM Corporation

Hardware Availability: Sep-2008

Tested by: IBM Corporation

Software Availability: May-2008

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	936	10.4	<b><u>942</u></b>	<b><u>10.4</u></b>	959	10.2	<b><u>746</u></b>	<b><u>13.1</u></b>	748	13.1	744	13.1
401.bzip2	1013	9.52	995	9.70	<b><u>997</u></b>	<b><u>9.68</u></b>	<b><u>999</u></b>	<b><u>9.65</u></b>	999	9.66	1001	9.64
403.gcc	908	8.86	<b><u>907</u></b>	<b><u>8.87</u></b>	906	8.89	<b><u>893</u></b>	<b><u>9.01</u></b>	894	9.01	893	9.02
429.mcf	899	10.1	<b><u>900</u></b>	<b><u>10.1</u></b>	967	9.43	<b><u>602</u></b>	<b><u>15.2</u></b>	602	15.2	602	15.1
445.gobmk	915	11.5	915	11.5	<b><u>915</u></b>	<b><u>11.5</u></b>	<b><u>944</u></b>	<b><u>11.1</u></b>	943	11.1	944	11.1
456.hammer	609	15.3	611	15.3	<b><u>610</u></b>	<b><u>15.3</u></b>	375	24.9	<b><u>374</u></b>	<b><u>24.9</u></b>	374	24.9
458.sjeng	1003	12.1	1006	12.0	<b><u>1006</u></b>	<b><u>12.0</u></b>	<b><u>1012</u></b>	<b><u>12.0</u></b>	1010	12.0	1014	11.9
462.libquantum	436	47.6	423	49.0	<b><u>423</u></b>	<b><u>49.0</u></b>	<b><u>356</u></b>	<b><u>58.1</u></b>	356	58.3	358	57.9
464.h264ref	1167	19.0	1189	18.6	<b><u>1172</u></b>	<b><u>18.9</u></b>	<b><u>1251</u></b>	<b><u>17.7</u></b>	1272	17.4	1250	17.7
471.omnetpp	717	8.71	<b><u>719</u></b>	<b><u>8.69</u></b>	719	8.69	717	8.71	<b><u>719</u></b>	<b><u>8.69</u></b>	719	8.69
473.astar	786	8.93	784	8.95	<b><u>786</u></b>	<b><u>8.94</u></b>	747	9.39	<b><u>746</u></b>	<b><u>9.41</u></b>	746	9.41
483.xalancbmk	666	10.4	674	10.2	<b><u>670</u></b>	<b><u>10.3</u></b>	581	11.9	581	11.9	<b><u>581</u></b>	<b><u>11.9</u></b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.

## Operating System Notes

```
'numactl' was used to bind copies to the cores.
Environment stack size set to 'unlimited'.
'ulimit -l 2097152' was used to set environment locked pages in memory quantity.
NCPUS set to number of cores.
PGI_HUGE_PAGES set to 896.
Set vm/nr_hugepages=14336 in /etc/sysctl.conf
mount -t hugetlbfs none /mnt/hugepages
Processor Performance States Disabled in BIOS
Memory ChipKill Disabled in BIOS
```

## Base Compiler Invocation

C benchmarks:

pgcc

C++ benchmarks:

pgcpp



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 14.0

IBM BladeCenter LS42 (AMD Opteron 8356)

SPECint\_base2006 = 12.5

CPU2006 license: 11

Test date: Aug-2008

Test sponsor: IBM Corporation

Hardware Availability: Sep-2008

Tested by: IBM Corporation

Software Availability: May-2008

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64  
401.bzip2: -DSPEC\_CPU\_LP64  
403.gcc: -DSPEC\_CPU\_LP64  
429.mcf: -DSPEC\_CPU\_LP64  
445.gobmk: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
458.sjeng: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
464.h264ref: -DSPEC\_CPU\_LP64  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-fastsse -Msmartalloc=huge:896 -Mloop32 -Mconcur=innermost  
-Mfprelaxed -Mipa=fast -Mipa=inline -tp barcelona-64 -Bstatic\_pgi

C++ benchmarks:

-fastsse -Msmartalloc=huge:896 -Mloop32 -Mfprelaxed --zc\_eh  
-Mipa=fast -Mipa=inline -tp barcelona-32 -Bstatic\_pgi

## Base Other Flags

C benchmarks:

-Mipa=jobs:8

C++ benchmarks:

-Mipa=jobs:8

## Peak Compiler Invocation

C benchmarks:

pgcc

C++ benchmarks:

pgcpp

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64  
401.bzip2: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 14.0

IBM BladeCenter LS42 (AMD Opteron 8356)

SPECint\_base2006 = 12.5

CPU2006 license: 11

Test date: Aug-2008

Test sponsor: IBM Corporation

Hardware Availability: Sep-2008

Tested by: IBM Corporation

Software Availability: May-2008

## Peak Portability Flags (Continued)

445.gobmk: -DSPEC\_CPU\_LP64  
 456.hmmer: -DSPEC\_CPU\_LP64  
 458.sjeng: -DSPEC\_CPU\_LP64  
 462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
 464.h264ref: -DSPEC\_CPU\_LP64  
 483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=inline(pass 2) -fastsse  
 -O4 -Msmartalloc=huge:896 -Mnovect -Mnounroll -Mfprelaxed  
 -tp barcelona-64 -Bstatic\_pgi

401.bzp2: -Mpfi=indirect(pass 1) -Mpfo=indirect(pass 2) -fastsse -O4  
 -Msmartalloc=huge:896 -Mprefetch=t0 -Mnounroll  
 -tp barcelona-64 -Bstatic\_pgi

403.gcc: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=fast(pass 2)  
 -Mipa=inline(pass 2) -fastsse -Msmartalloc=huge:896  
 -Mprefetch=t0 -Mnodalign -Mloop32 -Mfprelaxed  
 -tp barcelona-32 -Bstatic\_pgi

429.mcf: -fastsse -Msmartalloc=huge:896 -Mipa=fast -Mipa=inline:1  
 -tp barcelona-32 -Bstatic\_pgi

445.gobmk: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=fast(pass 2) -fastsse  
 -O4 -Msmartalloc=huge:896 -Mnovect -Mfprelaxed  
 -tp barcelona-64 -Bstatic\_pgi

456.hmmer: -fastsse -Mvect=partial -Munroll=n:8 -Msmartalloc=huge:896  
 -Msafeptr -Mprefetch=t0 -Mfprelaxed -Mipa=const -Mipa=ptr  
 -Mipa=arg -Mipa=inline -tp barcelona-64 -Bstatic\_pgi

458.sjeng: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=fast(pass 2)  
 -Mipa=inline:1(pass 2) -Mipa=noarg(pass 2) -fastsse  
 -Msmartalloc=huge:896 -Mfprelaxed -tp barcelona-64  
 -Bstatic\_pgi

462.libquantum: -fastsse -Munroll=m:8 -Msmartalloc=huge:896  
 -Mprefetch=distance:8 -Mconcur=innermost -Mconcur=noaltcode  
 -Mfprelaxed -Mipa=fast -Mipa=noarg -tp barcelona-64  
 -Bstatic\_pgi

464.h264ref: -Mpfi=indirect(pass 1) -Mpfo=indirect(pass 2)  
 -Mipa=fast(pass 2) -Mipa=inline(pass 2) -fastsse  
 -Msmartalloc=huge:896 -Mfprelaxed -tp barcelona-64  
 -Bstatic\_pgi

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 14.0

IBM BladeCenter LS42 (AMD Opteron 8356)

SPECint\_base2006 = 12.5

CPU2006 license: 11

Test date: Aug-2008

Test sponsor: IBM Corporation

Hardware Availability: Sep-2008

Tested by: IBM Corporation

Software Availability: May-2008

## Peak Optimization Flags (Continued)

C++ benchmarks:

471.omnetpp: basepeak = yes

473.astar: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=fast(pass 2)  
-Mipa=inline:6(pass 2) -fastsse -O4 -Msmartalloc=huge:896  
-Msafeptr=global -Mloop32 -Mfprelaxed --zc\_eh  
-tp barcelona-32 -Bstatic\_pgi

483.xalancbmk: --zc\_eh -fastsse -O4 -Mfprelaxed -Msmartalloc -Mipa=fast  
-Mipa=inline -tp barcelona-32 -Bstatic\_pgi -lsmarheap

## Peak Other Flags

C benchmarks (except as noted below):

-Mipa=jobs:8(pass 2)

401.bzip2: No flags used

C++ benchmarks (except as noted below):

-Mipa=jobs:8(pass 2)

483.xalancbmk: -Mipa=jobs:8 -L/proj/qa/smarheap/SmartHeap\_8.1/lib

The flags file that was used to format this result can be browsed at

[http://www.spec.org/cpu2006/flags/pgi72\\_flags.html](http://www.spec.org/cpu2006/flags/pgi72_flags.html)

You can also download the XML flags source by saving the following link:

[http://www.spec.org/cpu2006/flags/pgi72\\_flags.xml](http://www.spec.org/cpu2006/flags/pgi72_flags.xml)

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 19:08:59 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 2 September 2008.