



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant DL580 G5  
(2.66 GHz, Intel Xeon X7460)

**SPECfp®2006 = 23.4**

**SPECfp\_base2006 = 22.1**

CPU2006 license: 3


Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Aug-2008

Hardware Availability: Sep-2008

Software Availability: Nov-2008



**SPECfp\_base2006 = 22.1**

**SPECfp®2006 = 23.4**

### Hardware

CPU Name: Intel Xeon X7460  
CPU Characteristics: 2.66 GHz, 16 MB L3 shared, 1333 MHz system bus  
CPU MHz: 2667  
FPU: Integrated  
CPU(s) enabled: 24 cores, 4 chips, 6 cores/chip  
CPU(s) orderable: 2,4 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 9 MB I+D on chip per chip, 3 MB shared / 2 cores

### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP1, Kernel 2.6.16.46-0.12-smp  
Compiler: Intel C++ and Fortran Compiler 11.0 for Linux Build 20080730 Package ID: l\_cproc\_b\_11.0.042, l\_fproc\_b\_11.0.042  
Auto Parallel: Yes  
File System: ext3  
System State: Run level 3 (multi-user)  
Base Pointers: 64-bit

Continued on next page

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant DL580 G5  
(2.66 GHz, Intel Xeon X7460)

**SPECfp2006 = 23.4**

**SPECfp\_base2006 = 22.1**

CPU2006 license: 3

Test date: Aug-2008

Test sponsor: Hewlett-Packard Company

Hardware Availability: Sep-2008

Tested by: Hewlett-Packard Company

Software Availability: Nov-2008

L3 Cache: 16 MB I+D on chip per chip  
Other Cache: None  
Memory: 64 GB (16x4 GB PC2-5300F CL5)  
Disk Subsystem: 1x146 GB 10 K SAS  
Other Hardware: None

Peak Pointers: 32/64-bit  
Other Software: Binutils 2.18.50.0.7.20080502

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	287	47.4	<b>287</b>	<b>47.4</b>	286	47.5	286	47.5	287	47.4	<b>287</b>	<b>47.4</b>
416.gamess	1118	17.5	<b>1117</b>	<b>17.5</b>	1116	17.6	964	20.3	961	20.4	<b>962</b>	<b>20.4</b>
433.milc	808	11.4	807	11.4	<b>808</b>	<b>11.4</b>	808	11.4	807	11.4	<b>808</b>	<b>11.4</b>
434.zeusmp	<b>495</b>	<b>18.4</b>	495	18.4	495	18.4	<b>495</b>	<b>18.4</b>	495	18.4	495	18.4
435.gromacs	<b>404</b>	<b>17.7</b>	405	17.6	404	17.7	399	17.9	<b>400</b>	<b>17.9</b>	402	17.7
436.cactusADM	72.9	164	<b>72.9</b>	<b>164</b>	73.3	163	72.9	164	<b>72.9</b>	<b>164</b>	73.3	163
437.leslie3d	608	15.5	609	15.4	<b>608</b>	<b>15.5</b>	608	15.5	609	15.4	<b>608</b>	<b>15.5</b>
444.namd	553	14.5	<b>553</b>	<b>14.5</b>	555	14.4	553	14.5	<b>553</b>	<b>14.5</b>	555	14.4
447.dealII	480	23.8	481	23.8	<b>481</b>	<b>23.8</b>	445	25.7	<b>445</b>	<b>25.7</b>	445	25.7
450.soplex	696	12.0	<b>703</b>	<b>11.9</b>	703	11.9	623	13.4	616	13.5	<b>618</b>	<b>13.5</b>
453.povray	<b>243</b>	<b>21.9</b>	242	22.0	244	21.8	202	26.4	202	26.3	<b>202</b>	<b>26.4</b>
454.calculix	423	19.5	424	19.5	<b>423</b>	<b>19.5</b>	391	21.1	390	21.1	<b>391</b>	<b>21.1</b>
459.GemsFDTD	<b>413</b>	<b>25.7</b>	413	25.7	414	25.6	398	26.6	400	26.5	<b>399</b>	<b>26.6</b>
465.tonto	691	14.2	699	14.1	<b>694</b>	<b>14.2</b>	486	20.3	<b>487</b>	<b>20.2</b>	487	20.2
470.lbm	442	31.1	<b>441</b>	<b>31.1</b>	440	31.2	442	31.1	<b>441</b>	<b>31.1</b>	440	31.2
481.wrf	<b>643</b>	<b>17.4</b>	643	17.4	643	17.4	645	17.3	648	17.2	<b>646</b>	<b>17.3</b>
482.sphinx3	748	26.1	<b>744</b>	<b>26.2</b>	744	26.2	748	26.1	<b>744</b>	<b>26.2</b>	744	26.2

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
OMP\_NUM\_THREADS set to number of cores  
KMP\_AFFINITY set to physical,0  
KMP\_STACKSIZE set to 200M

## Platform Notes

BIOS configuration:  
Power Regulator set to Static High Performance Mode



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant DL580 G5  
(2.66 GHz, Intel Xeon X7460)

**SPECfp2006 = 23.4**

**SPECfp\_base2006 = 22.1**

**CPU2006 license:** 3

**Test sponsor:** Hewlett-Packard Company

**Tested by:** Hewlett-Packard Company

**Test date:** Aug-2008

**Hardware Availability:** Sep-2008

**Software Availability:** Nov-2008

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

## Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

## Base Optimization Flags

C benchmarks:  
-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

C++ benchmarks:  
-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Fortran benchmarks:  
-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:  
-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant DL580 G5  
(2.66 GHz, Intel Xeon X7460)

**SPECfp2006 = 23.4**

**SPECfp\_base2006 = 22.1**

**CPU2006 license:** 3

**Test sponsor:** Hewlett-Packard Company

**Tested by:** Hewlett-Packard Company

**Test date:** Aug-2008

**Hardware Availability:** Sep-2008

**Software Availability:** Nov-2008

## Peak Compiler Invocation

C benchmarks:  
icc

C++ benchmarks (except as noted below):  
icpc

```
450.soplex: /opt/intel/Compiler/11.0/042/bin/ia32/icpc
             -L/opt/intel/Compiler/11.0/042/ipp/ia32/lib
             -I/opt/intel/Compiler/11.0/042/ipp/ia32/include
```

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

## Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

## Peak Optimization Flags

C benchmarks:

```
433.milc: basepeak = yes
470.lbm: basepeak = yes
482.sphinx3: basepeak = yes
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant DL580 G5  
(2.66 GHz, Intel Xeon X7460)

**SPECfp2006 = 23.4**

**SPECfp\_base2006 = 22.1**

**CPU2006 license:** 3

**Test sponsor:** Hewlett-Packard Company

**Tested by:** Hewlett-Packard Company

**Test date:** Aug-2008

**Hardware Availability:** Sep-2008

**Software Availability:** Nov-2008

## Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: basepeak = yes

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -unroll2 -ansi-alias -scalar-rep-  
-opt-prefetch

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch  
-parallel

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -unroll2 -Obo -ansi-alias  
-scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -unroll2 -Obo -opt-prefetch  
-parallel

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -opt-prefetch -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: -xSSE4.1 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: -xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch  
-parallel -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revD.html>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant DL580 G5  
(2.66 GHz, Intel Xeon X7460)

**SPECfp2006 =** 23.4

**SPECfp\_base2006 =** 22.1

**CPU2006 license:** 3

**Test sponsor:** Hewlett-Packard Company

**Tested by:** Hewlett-Packard Company

**Test date:** Aug-2008

**Hardware Availability:** Sep-2008

**Software Availability:** Nov-2008

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revD.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 19:37:36 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 16 September 2008.