




SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge M805 (AMD Opteron 2350, 2.0 GHz)

SPECint®2006 = 12.8



Hardware

CPU Name:	AMD Opteron 2350
CPU Characteristics:	
CPU MHz:	2000
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	2 chips
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	2 MB I+D on chip per chip
Other Cache:	None
Memory:	16 GB (8x2GB, DDR2-667, CL5, Reg, Dual Rank)
Disk Subsystem:	1 x 73 SATA 15000 RPM
Other Hardware:	None

Software

Operating System:	SUSE Linux Enterprise Server 10 (x86_64) SP2, Kernel 2.6.16-60.0.21-smp
Compiler:	PGI Server Complete Version 7.2
Auto Parallel:	PathScale Compiler Suite Version 3.1
File System:	No
System State:	ReiserFS
Base Pointers:	Run level 3 (multi-user)
Peak Pointers:	32/64-bit
Other Software:	32/64-bit
	SmartHeap 8.0 32-bit Library for Linux



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge M805 (AMD Opteron 2350, 2.0 GHz)

SPECint2006 = 12.8

CPU2006 license: 55

Test date: Aug-2008

Test sponsor: Dell Inc.

Hardware Availability: Aug-2008

Tested by: Dell Inc.

Software Availability: May-2008

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	1016	9.61	1009	9.68	1008	9.70	770	12.7	778	12.6	758	12.9
401.bzip2	1163	8.29	1165	8.29	1165	8.28	1091	8.85	1091	8.85	1093	8.83
403.gcc	922	8.73	921	8.74	925	8.70	882	9.13	882	9.12	885	9.09
429.mcf	817	11.2	817	11.2	816	11.2	646	14.1	647	14.1	644	14.2
445.gobmk	1140	9.20	1141	9.19	1141	9.20	915	11.5	916	11.5	916	11.4
456.hmmer	699	13.3	697	13.4	691	13.5	443	21.0	446	20.9	444	21.0
458.sjeng	1243	9.74	1249	9.68	1248	9.69	1134	10.7	1132	10.7	1127	10.7
462.libquantum	691	30.0	690	30.0	693	29.9	576	36.0	574	36.1	574	36.1
464.h264ref	1462	15.1	1484	14.9	1468	15.1	1401	15.8	1430	15.5	1417	15.6
471.omnetpp	658	9.49	658	9.50	660	9.47	658	9.49	658	9.50	660	9.47
473.astar	849	8.27	848	8.27	849	8.27	874	8.04	878	8.00	874	8.03
483.xalancbmk	682	10.1	679	10.2	680	10.2	601	11.5	589	11.7	590	11.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'numactl' was used to bind copies to the cores
Environment variable PGI_HUGE_PAGES set to 150
'unlimit -s unlimited' was used to set environment stack size
'unlimit -l 2457600' was used to set environment locked pages in memory quantity
Set vm.nr_hugepages = 1200 in /etc/sysctl.conf
mount -t hugetlbfs nodev /mnt/hugepages
```

Base Compiler Invocation

C benchmarks:
pgcc

C++ benchmarks:
pgcpp

Base Portability Flags

```
400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge M805 (AMD Opteron 2350, 2.0 GHz)

SPECint2006 = 12.8

CPU2006 license: 55

Test date: Aug-2008

Test sponsor: Dell Inc.

Hardware Availability: Aug-2008

Tested by: Dell Inc.

Software Availability: May-2008

Base Portability Flags (Continued)

458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-fast -Mipa=fast -Mipa=inline -Mfprelaxed -Msmartralloc=huge:150
-tp barcelona-64 -Bstatic_pgi

C++ benchmarks:

-fastsse -Mipa=fast -Mipa=inline -Mfprelaxed -Msmartralloc=huge:150
--zc_eh -tp barcelona -Bstatic_pgi

Base Other Flags

C benchmarks:

-w -Mipa=jobs:4

C++ benchmarks:

-w -Mipa=jobs:4

Peak Compiler Invocation

C benchmarks (except as noted below):

pgcc

400.perlbench: pathcc

403.gcc: pathcc

445.gobmk: pathcc

C++ benchmarks (except as noted below):

pathCC

471.omnetpp: pgcpp



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint2006 = 12.8

PowerEdge M805 (AMD Opteron 2350, 2.0 GHz)

SPECint_base2006 = 11.1

CPU2006 license: 55

Test date: Aug-2008

Test sponsor: Dell Inc.

Hardware Availability: Aug-2008

Tested by: Dell Inc.

Software Availability: May-2008

Peak Portability Flags

```
400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
 401.bzip2: -DSPEC_CPU_LP64
 445.gobmk: -DSPEC_CPU_LP64
 456.hmmer: -DSPEC_CPU_LP64
 458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
 464.h264ref: -DSPEC_CPU_LP64
 483.xalancbmk: -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -march=barcelona -fb_create fbdata(pass 1)
  -fb_opt fbdata(pass 2) -Ofast -IPA:plimit=20000 -LNO:opt=0
  -WOPT:if_conv=0 -CG:local_sched_alg=1

401.bzip2: -Mpfi(pass 1) -Mpfo(pass 2) -fast -O4
  -Msmartralloc=huge:150 -Mnounroll -tp barcelona-64
  -Bstatic_pgi

403.gcc: -march=barcelona -fb_create fbdata(pass 1)
  -fb_opt fbdata(pass 2) -m32 -O3 -OPT:Ofast

429.mcf: -fastsse -Mipa=fast -Mipa=inline:1 -Msmartralloc=huge:150
  -tp barcelona -Bstatic_pgi

445.gobmk: -march=barcelona -fb_create fbdata(pass 1)
  -fb_opt fbdata(pass 2) -O3 -OPT:alias=restrict -LNO:opt=0
  -CG:p2align=on

456.hmmer: -fastsse -Munroll=n:8 -Msmartralloc=huge:150 -Mfprelaxed
  -Mvect=partial -Msafepr -Mipa=const -Mipa=ptr -Mipa=arg
  -Mipa=inline -tp barcelona-64 -Bstatic_pgi

458.sjeng: -Mpfi(pass 1) -Mipa=fast(pass 2) -Mipa=inline:1(pass 2)
  -Mipa=noarg(pass 2) -Mpfo(pass 2) -fastsse
  -Msmartralloc=huge:150 -Mfprelaxed -tp barcelona-64
  -Bstatic_pgi

462.libquantum: -fastsse -Mfprelaxed -Msmartralloc=huge:150 -Munroll=m:8
  -Mipa=fast -Mipa=inline -Mipa=noarg -tp barcelona-64
  -Bstatic_pgi

464.h264ref: -Mpfi=indirect(pass 1) -Mipa=fast(pass 2)
  -Mipa=inline(pass 2) -Mpfo=indirect(pass 2) -fastsse
  -Msmartralloc=huge:150 -Mfprelaxed -tp barcelona-64
  -Bstatic_pgi
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge M805 (AMD Opteron 2350, 2.0 GHz)

SPECint2006 = 12.8

SPECint_base2006 = 11.1

CPU2006 license: 55

Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Aug-2008

Hardware Availability: Aug-2008

Software Availability: May-2008

Peak Optimization Flags (Continued)

C++ benchmarks:

471.omnetpp: basepeak = yes

473.astar: -march=barcelona -Ofast -TENV:frame_pointer=off
-WOPT;if_conv=0 -GRA:optimize_boundary=on -IPA:plimit=525
-m32 -lsmartheap

483.xalancbmk: -march=barcelona -Ofast -m32 -OPT:unroll_times_max=8
-CG:push_pop_int_saved_regs=off -CG:ptr_load_use=0
-lsmartheap

Peak Other Flags

C benchmarks (except as noted below):

-w -Mipa=jobs:4(pass 2)

400.perlbench: No flags used

401.bzip2: -w

403.gcc: No flags used

445.gobmk: No flags used

C++ benchmarks (except as noted below):

-L/root/work/cpu2006/amd123GH.libs/32

471.omnetpp: -w -Mipa=jobs:4

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/amd123GH-flags.20090713.01.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/amd123GH-flags.20090713.01.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.1.

Report generated on Tue Jul 22 19:42:32 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 16 September 2008.