



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/R140a-4
(Intel Xeon E7450)

SPECfp[®]_rate2006 = 71.8

SPECfp_rate_base2006 = 66.3

CPU2006 license: 9006


Test sponsor: NEC Corporation

Tested by: Bull SAS

Test date: Jan-2009

Hardware Availability: Nov-2008

Software Availability: Nov-2008



Hardware

CPU Name: Intel Xeon E7450
 CPU Characteristics: 1066 MHz system bus
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 12 cores, 2 chips, 6 cores/chip
 CPU(s) orderable: 1,2,3,4 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 9 MB I+D on chip per chip, 3 MB shared / 2 cores

Continued on next page

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP2, Kernel 2.6.16.60-0.21-smp
 Compiler: Intel C++ and Fortran Compiler 11.0 for Linux Build 20080730 Package ID: l_cproc_b_11.0.042, l_fproc_b_11.0.042
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Run level 3 (multi-user)
 Base Pointers: 64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/R140a-4
(Intel Xeon E7450)

SPECfp_rate2006 = 71.8

SPECfp_rate_base2006 = 66.3

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: Bull SAS

Test date: Jan-2009

Hardware Availability: Nov-2008

Software Availability: Nov-2008

L3 Cache: 12 MB I+D on chip per chip
Other Cache: None
Memory: 32 GB (16 x 2GB DDR2-667 FBDIMM)
Disk Subsystem: 1x146 GB SAS, 10000 RPM
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: Binutils 2.18.50.0.7.20080502

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	12	5678	28.7	<u>5671</u>	<u>28.8</u>	5671	28.8	12	5671	28.8	5672	28.7	<u>5672</u>	<u>28.8</u>
416.gamess	12	1100	214	<u>1098</u>	<u>214</u>	1097	214	12	1077	218	<u>1077</u>	<u>218</u>	1080	218
433.milc	12	3310	33.3	3312	33.3	<u>3312</u>	<u>33.3</u>	12	3299	33.4	3301	33.4	<u>3301</u>	<u>33.4</u>
434.zeusmp	12	1685	64.8	1697	64.4	<u>1687</u>	<u>64.7</u>	12	1637	66.7	<u>1643</u>	<u>66.5</u>	1647	66.3
435.gromacs	12	<u>523</u>	<u>164</u>	523	164	523	164	12	520	165	516	166	<u>516</u>	<u>166</u>
436.cactusADM	12	2073	69.2	2071	69.2	<u>2072</u>	<u>69.2</u>	1	120	99.4	120	99.8	<u>120</u>	<u>99.8</u>
437.leslie3d	12	4327	26.1	4334	26.0	<u>4329</u>	<u>26.1</u>	12	4317	26.1	4314	26.1	<u>4316</u>	<u>26.1</u>
444.namd	12	625	154	625	154	<u>625</u>	<u>154</u>	12	637	151	628	153	<u>636</u>	<u>151</u>
447.dealII	12	1227	112	1224	112	<u>1227</u>	<u>112</u>	12	<u>1168</u>	<u>118</u>	1168	118	1174	117
450.soplex	12	<u>3270</u>	<u>30.6</u>	3265	30.7	3271	30.6	12	2967	33.7	2969	33.7	<u>2969</u>	<u>33.7</u>
453.povray	12	269	237	<u>269</u>	<u>237</u>	273	234	12	<u>226</u>	<u>282</u>	227	282	226	283
454.calculix	12	618	160	<u>609</u>	<u>162</u>	607	163	12	<u>610</u>	<u>162</u>	615	161	605	164
459.GemsFDTD	12	5220	24.4	<u>5219</u>	<u>24.4</u>	5218	24.4	12	5224	24.4	<u>5224</u>	<u>24.4</u>	5223	24.4
465.tonto	12	1207	97.8	<u>1210</u>	<u>97.6</u>	1220	96.8	12	1170	101	<u>1154</u>	<u>102</u>	1151	103
470.lbm	12	6281	26.3	6281	26.3	<u>6281</u>	<u>26.3</u>	6	<u>2699</u>	<u>30.5</u>	2699	30.5	2700	30.5
481.wrf	12	2994	44.8	<u>2992</u>	<u>44.8</u>	2991	44.8	12	2994	44.8	<u>2992</u>	<u>44.8</u>	2991	44.8
482.sphinx3	12	5656	41.3	5651	41.4	<u>5654</u>	<u>41.4</u>	6	<u>1829</u>	<u>63.9</u>	1826	64.0	1838	63.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
taskset was used to bind processes to cores except for 436.cactusADM peak
For peak modules using 1/2 the number of available cores, copies were each assigned to a single L2 cache using mysubmit.pl script.
See the flags description file for mysubmit.pl details.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to physical,0
KMP_STACKSIZE set to 64M



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECfp_rate2006 = 71.8

Express5800/R140a-4
(Intel Xeon E7450)

SPECfp_rate_base2006 = 66.3

CPU2006 license: 9006

Test date: Jan-2009

Test sponsor: NEC Corporation

Hardware Availability: Nov-2008

Tested by: Bull SAS

Software Availability: Nov-2008

Platform Notes

BIOS Settings:
Adjacent Cache Line Prefetch = Disabled
Hardware Prefetcher = Disabled
High Bandwidth option = Enabled

General Notes

The NEC Express5800/R140a-4(Intel Xeon E7450) and the Bull NovaScale R480 E1(Intel Xeon E7450, 2.40 GHz) models are electronically equivalent. The results have been measured on a Bull NovaScale R480 E1(Intel Xeon E7450, 2.40 GHz) model.

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/R140a-4
(Intel Xeon E7450)

SPECfp_rate2006 = 71.8

SPECfp_rate_base2006 = 66.3

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: Bull SAS

Test date: Jan-2009

Hardware Availability: Nov-2008

Software Availability: Nov-2008

Base Optimization Flags

C benchmarks:

`-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch`

C++ benchmarks:

`-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch`

Fortran benchmarks:

`-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch`

Benchmarks using both Fortran and C:

`-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch`

Peak Compiler Invocation

C benchmarks (except as noted below):

`icc`

482.sphinx3: `/opt/intel/Compiler/11.0/042/bin/ia32/icc
-L/opt/intel/Compiler/11.0/042/ipp/ia32/lib
-I/opt/intel/Compiler/11.0/042/ipp/ia32/include`

C++ benchmarks (except as noted below):

`icpc`

450.soplex: `/opt/intel/Compiler/11.0/042/bin/ia32/icpc
-L/opt/intel/Compiler/11.0/042/ipp/ia32/lib
-I/opt/intel/Compiler/11.0/042/ipp/ia32/include`

Fortran benchmarks (except as noted below):

`ifort`

437.leslie3d: `/opt/intel/Compiler/11.0/042/bin/ia32/ifort
-L/opt/intel/Compiler/11.0/042/ipp/ia32/lib
-I/opt/intel/Compiler/11.0/042/ipp/ia32/include`

Benchmarks using both Fortran and C:

`icc ifort`

Peak Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`
416.gamess: `-DSPEC_CPU_LP64`
433.milc: `-DSPEC_CPU_LP64`
434.zeusmp: `-DSPEC_CPU_LP64`
435.gromacs: `-DSPEC_CPU_LP64 -nofor_main`

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/R140a-4
(Intel Xeon E7450)

SPECfp_rate2006 = 71.8

SPECfp_rate_base2006 = 66.3

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: Bull SAS

Test date: Jan-2009

Hardware Availability: Nov-2008

Software Availability: Nov-2008

Peak Portability Flags (Continued)

```

436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

```

Peak Optimization Flags

C benchmarks:

```

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
         -no-prec-div -static -fno-alias

```

```

470.lbm: -xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch
        -auto-ilp32

```

```

482.sphinx3: -xSSE4.1 -ipo -O3 -no-prec-div -static -unroll2

```

C++ benchmarks:

```

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
         -no-prec-div -static -fno-alias -auto-ilp32

```

```

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
          -no-prec-div -static -unroll2 -ansi-alias -scalar-rep-

```

```

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
          -no-prec-div -static -opt-malloc-options=3

```

```

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
          -no-prec-div -static -unroll4 -ansi-alias

```

Fortran benchmarks:

```

410.bwaves: -xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

```

```

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
          -no-prec-div -static -unroll2 -Ob0 -ansi-alias
          -scalar-rep-

```

```

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
          -no-prec-div -static

```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/R140a-4
(Intel Xeon E7450)

SPECfp_rate2006 = 71.8

SPECfp_rate_base2006 = 66.3

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: Bull SAS

Test date: Jan-2009

Hardware Availability: Nov-2008

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -opt-malloc-options=3 -opt-prefetch

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll2 -Ob0 -opt-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -opt-prefetch -auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll2 -opt-prefetch -parallel
-auto-ilp32

454.calculix: -xSSE4.1 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090713.04.html>

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090713.01.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090713.04.xml>

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090713.01.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 23:05:22 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 3 March 2009.