



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

**SPECint®2006 = 34.8**

Dell Precision T3500 (Intel Xeon W3570, 3.20 GHz)

**SPECint\_base2006 = 32.0**

CPU2006 license: 55


Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Mar-2009

Hardware Availability: Apr-2009

Software Availability: Feb-2008



**SPECint\_base2006 = 32.0**

**SPECint2006 = 34.8**

## Hardware

CPU Name:	Intel Xeon W3570
CPU Characteristics:	Intel Turbo Boost Technology up to 3.46 GHz
CPU MHz:	3200
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	8 MB I+D on chip per chip
Other Cache:	None
Memory:	12 GB (3x4 GB, DDR3_1333R, ECC, CL9)
Disk Subsystem:	1 x 80 GB SATA 7200 RPM
Other Hardware:	None

## Software

Operating System:	Windows Vista Ultimate SP1 (64-bit)
Compiler:	Intel C++ Compiler for IA-32, Version 11.0 Build 20090131 Package ID: w_cproc_p_11.0.072 Microsoft Visual Studio 2008 SP1
Auto Parallel:	Yes
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	MicroQuill SmartHeap Library 8.1



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

**SPECint2006 = 34.8**

Dell Precision T3500 (Intel Xeon W3570, 3.20 GHz)

**SPECint\_base2006 = 32.0**

CPU2006 license: 55

Test date: Mar-2009

Test sponsor: Dell Inc.

Hardware Availability: Apr-2009

Tested by: Dell Inc.

Software Availability: Feb-2008

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	<b>404</b>	<b>24.2</b>	403	24.2	404	24.2	290	33.7	<b>290</b>	<b>33.7</b>	290	33.7
401.bzip2	520	18.6	<b>520</b>	<b>18.6</b>	520	18.6	498	19.4	498	19.4	<b>498</b>	<b>19.4</b>
403.gcc	287	28.0	<b>287</b>	<b>28.0</b>	288	28.0	259	31.1	259	31.0	<b>259</b>	<b>31.1</b>
429.mcf	185	49.3	<b>184</b>	<b>49.5</b>	184	49.6	188	48.6	185	49.2	<b>186</b>	<b>49.1</b>
445.gobmk	<b>437</b>	<b>24.0</b>	437	24.0	437	24.0	380	27.6	<b>380</b>	<b>27.6</b>	381	27.6
456.hmmer	387	24.1	387	24.1	<b>387</b>	<b>24.1</b>	381	24.5	<b>381</b>	<b>24.5</b>	381	24.5
458.sjeng	465	26.0	465	26.0	<b>465</b>	<b>26.0</b>	451	26.8	452	26.8	<b>451</b>	<b>26.8</b>
462.libquantum	<b>91.3</b>	<b>227</b>	91.5	226	91.2	227	<b>91.3</b>	<b>227</b>	91.5	226	91.2	227
464.h264ref	<b>576</b>	<b>38.4</b>	576	38.5	576	38.4	538	41.1	<b>538</b>	<b>41.1</b>	538	41.1
471.omnetpp	250	25.0	249	25.1	<b>250</b>	<b>25.1</b>	213	29.3	<b>214</b>	<b>29.3</b>	214	29.3
473.astar	383	18.3	<b>383</b>	<b>18.3</b>	383	18.3	345	20.3	346	20.3	<b>346</b>	<b>20.3</b>
483.xalancbmk	222	31.1	<b>222</b>	<b>31.0</b>	222	31.0	222	31.1	<b>222</b>	<b>31.0</b>	222	31.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Platform Notes

### BIOS Settings

Hyper-Threading Technology set to OFF.

## General Notes

Binaries were built on Windows Vista Business (64-bit)

## Base Compiler Invocation

C benchmarks:

icl -Qvc9 -Qstd=c99

C++ benchmarks:

icl -Qvc9

## Base Portability Flags

403.gcc: -DSPEC\_CPU\_WIN32

464.h264ref: -DSPEC\_CPU\_NO\_INTTYPES -DWIN32

483.xalancbmk: -Qoption,cpp, --no\_wchar\_t\_keyword



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

Dell Precision T3500 (Intel Xeon W3570, 3.20 GHz)

**SPECint2006 = 34.8**

**SPECint\_base2006 = 32.0**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Mar-2009

**Hardware Availability:** Apr-2009

**Software Availability:** Feb-2008

## Base Optimization Flags

C benchmarks:

```
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel  
-Qpar-runtime-control -Qvec-guard-write /F512000000
```

C++ benchmarks:

```
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx_features  
/F5120000000 shlw32m.lib  
-link /FORCE:MULTIPLE
```

## Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

## Peak Compiler Invocation

C benchmarks:

```
icl -Qvc9 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc9
```

## Peak Portability Flags

```
403.gcc: -DSPEC_CPU_WIN32  
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32  
483.xalancbmk: -Qoption,cpp,--no_wchar_t_keyword
```

## Peak Optimization Flags

C benchmarks:

```
400.perlbench: -Qprof_gen(pass 1) -QxSSE4.2 -Qprof_use(pass 2) -Qipo -O3  
-Qprec-div- -Qansi-alias -Qopt-prefetch /F5120000000  
shlw32m.lib  
-link /FORCE:MULTIPLE
```

```
401.bzip2: -Qprof_gen(pass 1) -QxSSE4.2(pass 2) -Qprof_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch  
/F512000000
```

```
403.gcc: -Qprof_gen(pass 1) -QxSSE4.2 -Qprof_use(pass 2) -Qipo -O3  
-Qprec-div- /F512000000
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.	<b>SPECint2006 =</b>	<b>34.8</b>
Dell Precision T3500 (Intel Xeon W3570, 3.20 GHz)	<b>SPECint_base2006 =</b>	<b>32.0</b>
<b>CPU2006 license:</b> 55	<b>Test date:</b>	Mar-2009
<b>Test sponsor:</b> Dell Inc.	<b>Hardware Availability:</b>	Apr-2009
<b>Tested by:</b> Dell Inc.	<b>Software Availability:</b>	Feb-2008

## Peak Optimization Flags (Continued)

429.mcf: -QxSSE4.2 -Qipo -O3 -Qprec-div- -Qopt-prefetch  
/F512000000

445.gobmk: -Qprof\_gen(pass 1) -QxSSE4.2(pass 2) -Qprof\_use(pass 2)  
-Qipo -O2 -Qprec-div- -Qansi-alias /F512000000

456.hmmr: -QxSSE4.2 -Qipo -O3 -Qprec-div- -Qunroll12 -Qansi-alias  
/F512000000

458.sjeng: -Qprof\_gen(pass 1) -QxSSE4.2(pass 2) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qunroll14 /F512000000

462.libquantum: basepeak = yes

464.h264ref: -Qprof\_gen(pass 1) -QxSSE4.2(pass 2) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qunroll12 -Qansi-alias /F512000000

C++ benchmarks:

471.omnetpp: -Qprof\_gen(pass 1) -QxSSE4.2(pass 2) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qansi-alias  
-Qopt-ra-region-strategy=block /F5120000000 shlw32m.lib  
-link /FORCE:MULTIPLE

473.astar: -Qprof\_gen(pass 1) -QxSSE4.2(pass 2) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qansi-alias  
-Qopt-ra-region-strategy=routine /F5120000000 shlw32m.lib  
-link /FORCE:MULTIPLE

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/dell.ic11.0.windows.flags.20090710.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/dell.ic11.0.windows.flags.20090710.xml>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

**SPECint2006 = 34.8**

Dell Precision T3500 (Intel Xeon W3570, 3.20 GHz)

**SPECint\_base2006 = 32.0**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Mar-2009

**Hardware Availability:** Apr-2009

**Software Availability:** Feb-2008

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 23:59:56 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 2 April 2009.